



Spare parts for:

Consumables



Suitable for:

DIXELL



This catalogue is automatically generated.
Therefore, the sequence of the items might
not be always shown at best.
Updates will be issued in case of additions
and/or amendments.

*Suitable **universal spare parts** may not be included*





Suitable for:

DIXELL




Suitable for:

Electronic controllers

3445347 CONTROLLER DIXELL XW270K-5N0C0

230V 50/60Hz
day-board
1 relay output 20A for compressor
1 relay output 16A for light
1 relay output 8A for evaporator fans
1 relay output 8A for defrosting
1 relay output 8A for alarm
1 relay output 16A for aux
3 NTC probes (not included)
1 programmable digital input
1 door microswitch digital input



DIXELL X0W5JFBNC500-S00

3445207 CONTROLLER DIXELL XR04CX-5N0C1

230V 50/60Hz
1 relay output 20A for compressor
1 relay output 8A for fans
2 probes NTC/PTC selectable (not included)
frontal dimension 74x32 depth 50 mm
mounting hole 71x29 mm
serial output Hot Key/TTL



DIXELL LIIEBX5AA

DIXELL LIIEBX5AA-000

3445170 CONTROLLER DIXELL XR20CX-0N0C1

12Vac/dc
1 relay output 20A for compressor
1 programmable digital input (clean contact)
pause defrosting
selectable NTC/PTC probe (not included)
front dimension 78x37 depth 60 mm
mounting hole 71x29 mm
Hot Key/TTL serial output



DIXELL LGCCBxB100

DIXELL LGCCBxB100-S00

DIXELL X0LGCCBxB100-S00

3445171 CONTROLLER DIXELL XR20CX-5N0C1

230V 50/60Hz
ON-OFF control with 1 actuation point
1 relay output 20A for compressor
1 programmable digital input (clean contact)
pause defrosting
selectable NTC/PTC probe (not included)
frontal dimension 78x37x60 mm
mounting hole 71x29 mm
serial output Hot Key/TTL



DIXELL LBCBxB500

DIXELL LIACBx500

DIXELL LGCCBxB500

DIXELL XR02CX

DIXELL LGCCBxB500-S00

DIXELL X0LGCCBxB500-S00

3445172 CONTROLLER DIXELL XR30CX-0N0C1

12Vac/dc
1 relay output 20A for compressor
1 relay output 8A for alarm
1 programmable digital input (clean contact)
pause defrosting
selectable NTC/PTC probe (not included)
front dimension 78x37 depth 60 mm
mounting hole 71x29 mm
Hot Key/TTL serial output



DIXELL LGFEBxB100

DIXELL X0LGFEBxB100-S00

3445167 PROBE NTC IP68 1500 mm

temperature range -50°+110°C
bulb ø 5x20 mm watertight





Suitable for:

3445154 PROBE NTC IP68 3000 m m
temperature range $-40^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm watertight



3445157 PROBE NTC PVC 1500 m m
temperature range $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445156 PROBE NTC PVC 3000 m m
temperature range $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445107 PTC PVC PROBE 3000 m m
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445155 SILICONE PROBE NTC 3000 m m
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



DIXELL

Suitable for:

3445335 PROBE NTC IP68 3000 m m
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 5x20 mm watertight



3445184 PROBE NTC PVC 1500 m m IP68
temperature range $-40^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm watertight



3445070 PTC PVC PROBE 1500 m m
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445913 SILICONE PROBE NTC 1500 m m
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



DIXELL NS6S

3445183 SILICONE PTC PROBE 3000 m m
2-wire probe temperature range $-55+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm





Suitable for:

3445959 SILICONE PTC PROBE 5000 mm
temperature range $-55^{\circ}+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



DIXELL



Suitable for:

3445173 CONTROLLER DIXELL XR30CX-5N0C1
230V 50/60Hz
1 relay output 20A for compressor
1 relay output 8A for alarm
1 programmable digital input (clean contact)
pause defrosting
selectable NTC/PTC probe (not included)
frontal dimension 78x37 depth 60 mm
mounting hole 71x29 mm
serial output Hot Key/TTL



DIXELL LGFEBXB500

DIXELL LGFEBXB500-S00

DIXELL X0LGFEBXB500-S00

3445154 PROBE NTC IP68 3000 mm
temperature range $-40^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm watertight



3445167 PROBE NTC IP68 1500 mm
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 5x20 mm watertight



3445335 PROBE NTC IP68 3000 mm
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 5x20 mm watertight



3445157 PROBE NTC PVC 1500 mm
temperature range $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445184 PROBE NTC PVC 1500 mm IP68
temperature range $-40^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm watertight



3445156 PROBE NTC PVC 3000 mm
temperature range $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445070 PTC PVC PROBE 1500 mm
2-wire probe temperature range $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm





Suitable for:

3445107 PTC PVC PROBE 3000 mm
2-wire probe temperature range -30+80°C
bulb ø 6x40 mm



3445155 SILICONE PROBE NTC 3000 mm
temperature range -50°+110°C
bulb ø 6x40 mm



3445959 SILICONE PTC PROBE 5000 mm
temperature range -55°+150°C
bulb ø 6x40 mm



DIXELL



Suitable for:

3445913 SILICONE PROBE NTC 1500 mm
temperature range -50+110°C
bulb ø 6x40 mm



DIXELL NS6S

3445183 SILICONE PTC PROBE 3000 mm
2-wire probe temperature range -55+150°C
bulb ø 6x40 mm



3445174 CONTROLLER DIXELL XR40CX-0N0C1
12Vac/dc
1 relay output 20A for compressor
1 relay output 8A for defrosting
1 programmable digital input (clean contact)
2 selectable NTC/PTC probes (not included)
front dimension 78x37 depth 60 mm
mounting hole 71x29 mm
Hot Key/TTL serial output



DIXELL LGIEBxB100

DIXELL X0LGIEBxB100-S00

3445175 CONTROLLER DIXELL XR40CX-5N0C1
230V 50/60Hz
1 relay output 20A for compressor
1 relay output 8A for defrosting
1 programmable digital input (clean contact)
2 selectable NTC/PTC probes (not included)
frontal dimension 78x37 depth 60 mm
mounting hole 71x29 mm
serial output Hot Key/TTL



DIXELL LBIDBYB500

DIXELL X0LGIEBxB500-S00

DIXELL LGIEBxB500

DIXELL XR40C



Suitable for:

DIXELL



Suitable for:

3445298 CONTROLLER DIXELL XR60CX-0N0C3
 12Vac/dc
 1 relay output 16A for compressor
 1 relay output 8A for defrosting
 1 relay output 8A for evaporator fan
 1 programmable digital input (clean contact)
 2 selectable NTC/PTC probes (not included)
 front dimension 78x37 depth 60 mm
 mounting hole 71x29 mm
 Hot Key/TTL serial output



DIXELL LGOFBxB100

DIXELL X0LGONBxB100-S00

3445297 CONTROLLER DIXELL XR60CX-5N0C1
 230V 50/60Hz
 1 relay output 20A for compressor
 1 relay output 8A for defrosting
 1 relay output 5A for evaporator fans
 1 programmable digital input (clean contact)
 2 selectable NTC/PTC probes (not included)
 frontal dimension 78x37 depth 60 mm
 mounting hole 71x29 mm
 serial output Hot Key/TTL



DIXELL LBOMBYB500

DIXELL LGOFBxB500

DIXELL LGOFBxB500-S00

DIXELL X0LGGBxB500-S00

3445156 PROBE NTC PVC 3000 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



3445157 PROBE NTC PVC 1500 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



3445070 PTC PVC PROBE 1500 mm
 2-wire probe temperature range -30+80°C
 bulb ø 6x40 mm



3445107 PTC PVC PROBE 3000 mm
 2-wire probe temperature range -30+80°C
 bulb ø 6x40 mm



3445248 CONTROLLER DIXELL XR70CX-0N0C8

12Vac/dc
 1 relay output 16A for compressor
 1 relay output 16A for defrosting
 1 relay output 16A for fans
 1 relay output 16A for light/alarm
 2 selectable NTC/PTC probes (not included)
 1 programmable digital input
 front dimension 78x37 depth 60 mm
 mounting hole 71x29 mm



DIXELL LGQOBXJ100

DIXELL X0LGQOBXJ100-S00

3445390 CONTROLLER DIXELL XR70CX-5N0C3

230V 50/60Hz
 1 relay output 16A for compressor
 1 relay output 5A for ventilator
 1 relay output 8A for defrosting
 1 relay output 8A for light/alarm
 2 selectable NTC/PTC probes (not included)
 1 programmable digital input
 front dimension 78x37 depth 60 mm
 mounting hole 71x29 mm



DIXELL LGQHXB500

DIXELL X0LGQHXB500-S00

3445157 PROBE NTC PVC 1500 mm

temperature range -30°+80°C
 bulb ø 6x40 mm



3445070 PTC PVC PROBE 1500 mm

2-wire probe temperature range -30+80°C
 bulb ø 6x40 mm



3445180 CONTROLLER DIXELL XW20L-5N0C1

230V 50/60Hz
 depth 76 mm
 1 relay output 20A for compressor - faston 6.3 mm
 1 relay output 8A for light - faston 6.3 mm
 1 NTC/PTC probe (not included)
 1 programmable digital input
 frontal dimension 185x38 mm
 mounting hole 150x31 mm



DIXELL WG3PBNC500

DIXELL WG3PBNC500-S00

DIXELL X0WG3PBNC500-S00

3445178 CONTROLLER DIXELL XW20LS-5N0C1

230V 50/60Hz
 depth 48 mm
 1 relay output 20A for compressor - faston 6.3 mm
 1 relay output 8A for light - faston 6.3 mm
 1 NTC/PTC probe (not included) - faston 2.8 mm
 frontal dimension 185x38 mm
 mounting hole 150x31 mm



DIXELL WF3PBNC500

DIXELL X0WF3PBNC500-S00



Suitable for:

DIXELL



3445182 CONTROLLER DIXELL XW20VS-5N0C0
 230V 50/60Hz
 depth 40 mm
 1 relay output 16A for compressor - faston 6.3 mm
 1 relay output 8A for light - faston 6.3 mm
 2 NTC/PTC probes (not included) - faston 2.8 mm
 1 programmable digital input - faston 2.8 mm
 frontal dimension 100x64 mm
 mounting hole 56x72 mm




DIXELL WM3PBNC500

DIXELL WM3PBNC500-S00

DIXELL X0WM3PBNC500-S00

3445246 CONTROLLER DIXELL XW220K-5N0C0
 230V 50/60Hz
 day-board
 1 relay output 20A for compressor
 1 relay output 16A for light
 2 NTC probes (not included)
 1 programmable digital input
 1 microdoor digital input



DIXELL X0W5BBNC500-S00

3445257 CONTROLLER DIXELL XW220L-5N0C1
 230V 50/60Hz
 depth 76 mm
 1 relay output 20A for compressor
 1 relay output 16A for light
 2 NTC probes (not included)
 1 digital input for microdoor
 1 programmable digital input
 output for remote display X-REP
 frontal dimension 185x38 mm
 mounting hole 150x31 mm




DIXELL X0W2BBBPC500-S00

3445322 CONTROLLER DIXELL XW230L-5N0C0
 230V 50/60Hz
 depth 76 mm
 1 relay output 20A for compressor
 1 relay output 16A for light
 1 relay output 16A for aux
 1 relay output 8A for alarm
 1 door microswitch digital input
 1 programmable digital input
 2 NTC probes (not included)
 front dimension 185x38 mm
 mounting hole 150x31 mm



DIXELL X0W2CDBNC500-S00

3445247 CONTROLLER DIXELL XW260K-5N0C0
 230V 50/60Hz
 day-board
 1 relay output 20A for compressor
 1 relay output 16A for light
 1 relay output 8A for evaporator fans
 1 relay output 8A for defrosting
 3 NTC probes (not included)
 1 configurable digital input
 1 digital input microdoor



DIXELL X0W5FDBNC500-S00

3445231 CONTROLLER DIXELL XW260L-5N0C5
 230V 50/60Hz
 depth 76 mm
 1 relay output 20A for compressor
 1 relay output 8A for defrosting
 1 relay output 8A for fans
 1 relay output 16A for light
 3 NTC probes (not included)
 1 microdoor digital input
 1 programmable digital input
 output for remote display X-REP
 serial output TTL RS485
 frontal dimension 185x38 mm
 mounting hole 150x31 mm



DIXELL W0W2FDBPG500-S00

DIXELL X0W4FDBPC500-S00

3445251 CONTROLLER DIXELL XW264L-5N0C5

230V 50/60Hz
depth 76 mm
1 relay outlet 20A for compressor
1 relay outlet 8A for defrosting 1
1 relay outlet 8A for defrosting 2
1 relay outlet 8A for fans
1 relay outlet 16A for on/off
1 outlet relay 16A for light
3 NTC probes (no included)
1 digital inlet for micro door
1 digital configurable inlet
outlet display remote X-REP
serial outlet TTL RS485
frontal dimension 185x38 mm
mounting hole 150x31 mm



DIXELL W4HFBPC500

DIXELL W4HFBPC500-S00

DIXELL X0W4HFBPC500-S00

3445237 CONTROLLER DIXELL XW271L-5N0C1

230V 50/60Hz
depth 76 mm
1 relay output 20A for compressor
1 relay output 8A for defrosting
1 relay output 8A for fans
1 relay output 16A for light
1 relay output 8A for alarm
1 relay output 16A for demisting heating elements
1 digital input for microdoor
1 programmable digital input
3 NTC probes (not included)
output for X-REP remote display
frontal dimension 185x38 mm
mounting hole 150x31 mm



DIXELL X0W2KFBPC500-S00

3445197 CONTROLLER DIXELL XW30L-00000

230V 50/60Hz
depth 48 mm
1 relay output 20A for compressor - faston 6.3 mm
1 relay output 8A for fans - faston 6.3 mm
1 relay output 8A for light - faston 6.3 mm
2 NTC probes (not included) - faston 2.8 mm
frontal dimensions 185x38 mm
mounting hole 150x31 mm



DIXELL AI002AA075

DIXELL XAI002AA075-S00

3445299 CONTROLLER DIXELL XW35VS-5N0C0

230V 50/60Hz
depth 40 mm
1 relay output 16A for compressor - faston 6.3 mm
1 relay output 8A for fans - faston 6.3 mm
1 relay output 16A for light - faston 6.3 mm
2 NTC/PTC probes (not included) - faston 2.8 mm
1 programmable digital input - faston 2.8 mm
front dimension 100x64 mm
mounting hole 56x72 mm



DIXELL X0WM4QBNC500-S00

3445230 CONTROLLER DIXELL XW40L-5N0C1

230V 50/60Hz
depth 76 mm
1 relay output 20A for compressor - faston 6.3 mm
1 relay output 8A for defrosting - faston 6.3 mm
1 relay output 8A for light - faston 6.3 mm
2 NTC/PTC probes (not included)
1 programmable digital input
frontal dimension 185x38 mm
mounting hole 150x31 mm



DIXELL X0WG5QBNC500-S00

3445236 CONTROLLER DIXELL XW40LS-5N0C1

230V 50/60Hz
depth 48 mm
1 relay output 20A for compressor - faston 6.3 mm
1 relay output 8A for defrosting - faston 6.3 mm
1 relay output 8A for light - faston 6.3 mm
2 NTC/PTC probes (not included) - faston 2.8 mm
1 programmable digital input
frontal dimension 185x38 mm
mounting hole 150x31 mm



DIXELL X0WQEIBNC500-S00



Suitable for:

Suitable for:

3445181 CONTROLLER DIXELL XW60L-5N0C1
 230V 50/60Hz
 depth 76 mm
 1 relay output 20A for compressor - faston 6.3 mm
 1 relay output 8A for defrosting - faston 6.3 mm
 1 relay output 8A for fans - faston 6.3 mm
 1 relay output 8A for light - faston 6.3 mm
 2 NTC/PTC probes (not included)
 1 programmable digital input
 frontal dimension 185x38 mm
 mounting hole 150x31 mm



3445179 CONTROLLER DIXELL XW60LS-5N0C1
 230V 50/60Hz
 depth 48 mm
 1 relay output 20A for compressor - faston 6.3 mm
 1 relay output 8A for defrosting - faston 6.3 mm
 1 relay output 8A for fans - faston 6.3 mm
 1 relay output 8A for fans - faston 6.3 mm
 2 NTC/PTC probes (not included) - faston 2.8 mm
 frontal dimension 185x38 mm
 mounting hole 150x31 mm



DIXELL WG7RBNC500

DIXELL WG7RBNC500-S00

DIXELL X0WG7RBNC500-S00

DIXELL WF7QBNC500

DIXELL WF7QBNC500-S00

DIXELL X0WF7QBNC500-S00

3445301 CONTROLLER DIXELL XW60V-5N0C1
 230V 50/60Hz
 depth 59 mm
 1 relay output 20A for compressor - faston 6.3 mm
 1 relay output 8A for defrosting - faston 6.3 mm
 1 relay output 16A for fans - faston 6.3 mm
 1 relay output 16A for light - faston 6.3 mm
 2 NTC/PTC probes (not included)
 1 programmable digital input
 frontal dimension 100x64 mm
 mounting hole 56x72 mm



DIXELL X0W17RBNC500-S00

3445300 CONTROLLER DIXELL XW60VS-5N0C0
 230V 50/60Hz
 depth 40 mm
 1 relay output 16A for compressor - faston 6.3 mm
 1 relay output 16A for defrosting - faston 6.3 mm
 1 relay output 8A for fans - faston 6.3 mm
 3 NTC/PTC probes (not included) - faston 2.8 mm
 1 programmable digital input - faston 2.8 mm
 front dimension 100x64 mm
 mounting hole 56x72 mm






















DIXELL X0WM7QBNC500-S00

The data herewith contained may change without notice and LF SpA cannot be held responsible for possible errors stated or resulting by the use of this document. All rights reserved. No part of this publication may be reproduced without written permission by LF SpA.



Distributing Components, Spare Parts & Accessories in original quality worldwide

-
-  **LF SpA HEADQUARTERS**
via Voltri, 80 - 47522 Cesena (FC) ITALY
Tel. +39 0547 34 11 11 - Fax +39 0547 34 11 10
www.lfircambi724.it - www.lfircambi724.mobi
info@lfircambi.it
Export Dept.: Tel. +39 0547 34 11 50 - Fax: +39 0547 34 11 55
www.lfspareparts724.com - www.lfspareparts724.mobi
export@lfspareparts.com
-  **LF SpA HOUSEHOLD COMPONENTS DIVISION**
Via Padriciano, 34149 Trieste - Italia - AREA Science Park
Tel. +39 0547 34 12 42 - Fax +39 0547 34 12 48
www.lfspareparts724.com - www.lfspareparts724.mobi
info@lfspareparts.com
-  **EPGC Sas FRANCE**
13, Rue des Forts - 59960 Neuville en Ferrain
Tel. +33 (0)3 20 25 06 21
Fax +33 (0)3 20 25 34 12
www.epgc.com
www.epgc724.mobi
epgc@epgc.com
-  **LF GmbH GERMANY**
Junkersstrasse, 3 - D-82178 Puchheim - München
Tel. +49 89 89 45 78 66
Fax +49 89 89 45 78 88
www.lfersatzteile724.de
www.lfersatzteile724.mobi
info@lfersatzteile.de
-  **LF China REPUBLIC OF CHINA**
Room 403, No.2, Huadu Mansion, Lane 422, Huanghua Rd.
Minhang Dist. - 201103 Shanghai
Tel. +86 (0)21 33 53 66 31
Fax +86 (0)21 33 53 66 32
www.lfspareparts724.com
www.lfspareparts724.mobi
china@lfspareparts.com
-  **OOO LF RUSSIAN FEDERATION**
Ul. Anatoliya Zhivova, 8 - office 1 - 123100 Moscow
Tel./Fax +7 495 725 26 53
www.lfspareparts724.ru
www.lfspareparts724.mobi
info@lfspareparts.ru
-  **LF Repuestos Horeca S.L.U. SPAIN**
Poligono Industrial Carpetania - C/Miguel Faraday, 8 - 28906 Getafe
Tel. +34 91 477 91 00
Fax +34 91 477 90 81
www.lfrepuestos-horeca724.es
www.lfrepuestos724.mobi
info@lfrepuestos.es
-  **LF SpA Cesena (IT) Swiss Branch Steinhausen SWITZERLAND**
Sennweidstrasse, 45 - CH-6312 Steinhausen
Tel. +41 (0)41 760 15 80-1
Fax +41 (0)41 760 15 85
www.lfersatzteile724.ch
www.lfersatzteile724.mobi
info@lfersatzteile.ch
-  **LF Spare Parts Ltd. UNITED KINGDOM**
A10a Lakeside Business Park, Broadway Lane
South Cerney, Gloucestershire GL7 5XL
Tel. +44 (0)1285 86 16 25
Fax +44 (0)1285 86 39 49
www.lfspareparts724.co.uk
www.lfspareparts724.mobi
info@lfspareparts.co.uk
-
-  **AUSTRALIA AND NEW ZEALAND**
www.lfspareparts724.com
andrea.calvio@lfspareparts.com
-  **AUSTRIA**
www.lfersatzteile724.at
info@lfersatzteile.at
-  **BALKAN COUNTRIES**
www.lfspareparts724.com
matijaramov@lfspareparts.com
-  **BALTIC COUNTRIES**
www.lfspareparts724.com
inara.silina@lfspareparts.com
-  **CENTRAL AND EASTERN EUROPE**
www.lfspareparts724.cz
jiri.kremla@lfspareparts.cz
-  **DENMARK**
www.lfspareparts724.dk
michael.leth@lfspareparts.com
-  **JAPAN**
www.lfspareparts724.jp
hiroshi.ukai@lfspareparts.jp
-  **SOUTH KOREA**
www.lfspareparts724.com
fabio.doni@lfspareparts.com
-  **TURKEY**
www.lfyedekparca724.com
basar.ergun@lfyedekparca.com
-  **USA AND CANADA**
www.lfspareparts724.us
sauro.dallaglio@lfspareparts.us
howard.truitt@lfspareparts.us