



Spare parts for:

Consumables



Suitable for:

ELIWELL



This catalogue is automatically generated.
Therefore, the sequence of the items might
not be always shown at best.

Updates will be issued in case of additions
and/or amendments.

*Suitable **universal spare parts** may not be included*





Suitable for:

ELIWELL

Suitable for:



Electric boards

- 3445158 CONTROLLER ELIWELL WM961/A**
 230V 50/60Hz
 dimensions 124x80x25 mm
 1 relay output 16A for compressor
 1 selectable NTC/PTC probe input
 1 voltage free digital input (clean contact)
 with parameter setting
 parameter selectable decimal point



ELIWELL WM1GDL00BH00

Electronic controllers

- 3445088 CONTROLLER ELIWELL IC PLUS 915**
 12Vac/dc
 2 dependent/independent relay outputs 8A or
 with neutral zone with parameter setting
 1 NTC/PTC probe (not included)
 TTL serial port



ELIWELL ICP22DI350000

ELIWELL IC12DI0XCD300

ELIWELL IC12DI0XCH300

- 3445089 CONTROLLER ELIWELL IC PLUS 915**
 230V 50/60Hz
 2 dependent/independent relay outputs 8A or
 with neutral zone with parameter setting
 1 NTC/PTC probe
 TTL serial port



ELIWELL ICP22DI750000

ELIWELL IC12DI0XCD700

ELIWELL IC12DI0XCH700

- 3445157 PROBE NTC PVC 1500 mm**
 temperature range -30°+80°C
 bulb ø 6x40 mm



ELIWELL SN8P0A1500

- 3445070 PTC PVC PROBE 1500 mm**
 2-wire probe temperature range -30+80°C
 bulb ø 6x40 mm



ELIWELL SN7P0A1500

Suitable for:

Suitable for:

3445375 CONTROLLER ELIWELL ID PLUS 902
 230V 50/60Hz
 1 relay output 8A for compressor
 1 selectable NTC/PTC/PT1000 probe (not included)
 1 programmable digital/temperature input
 TTL input for copy card connection
 front dimension 74x32xdepth 59 mm
 mounting hole 71x29 mm



3445167 PROBE NTC IP68 1500 mm
 temperature range -50°+110°C
 bulb ø 5x20 mm watertight



- | | | | |
|-----------------------|-----------------------|-----------------------|--------------------|
| ELIWELL EW11D10XB4780 | ELIWELL IC11C10MHD700 | ELIWELL IC11C10XCD700 | ELIWELL SN8T6H1502 |
| ELIWELL IC11C10XHD700 | ELIWELL IC11C00TCA700 | ELIWELL IC11C00TCD700 | |
| ELIWELL IC11C00TCF700 | ELIWELL IC11C00TCH700 | ELIWELL IC11C00THA700 | |
| ELIWELL IC11C00THD700 | ELIWELL IC11D10XCD700 | ELIWELL IC11D00TCA700 | |
| ELIWELL IC11D00TCD700 | ELIWELL IC11D00THA700 | ELIWELL IC11D00THD700 | |
| ELIWELL IC16C00TCA700 | ELIWELL IC16C00TCD700 | ELIWELL IC16D00TCA700 | |
| ELIWELL IC16D00TCD700 | ELIWELL IC16D00THA700 | ELIWELL IC16D00THF700 | |
| ELIWELL IC17C00TCA700 | ELIWELL IDP11D0700000 | ELIWELL T1B1CCC300 | |

3445154 PROBE NTC IP68 3000 mm
 temperature range -40°+110°C
 bulb ø 6x40 mm watertight



3445335 PROBE NTC IP68 3000 mm
 temperature range -50+110°C
 bulb ø 5x20 mm watertight



ELIWELL SN8T6A3002

ELIWELL SN8T6H3002

3445157 PROBE NTC PVC 1500 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



3445184 PROBE NTC PVC 1500 mm IP68
 temperature range -40°+110°C
 bulb ø 6x40 mm watertight



ELIWELL SN8P0A1500

ELIWELL SN8T6A1502

3445156 PROBE NTC PVC 3000 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



3445028 PROBE NTC PVC 4000 mm
 temperature field -30°+80°C
 bulb ø 6x20 mm



ELIWELL SN8P0A3000



Suitable for:

3445379 PROBE PT1000 PVC 1500 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



ELIWELL SN9DAE11502C6

3445070 PTC PVC PROBE 1500 mm
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7P0A1500

3445913 SILICONE PROBE NTC 1500 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN8S0A1500

3445183 SILICONE PTC PROBE 3000 mm
2-wire probe temperature range $-55+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7S0A3000

3445110 TRANSFORMER 230V/12V 3VA
primary tension 230Vca 50/60Hz
secondary tension 12Vca 3VA
room temperature $0+60^{\circ}\text{C}$
screw terminal block
IMQ approved



ELIWELL EWTCM3

ELIWELL TF111173

ELIWELL



Suitable for:

3445380 PROBE PT1000 PVC 3000 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



ELIWELL SN9DAE13002C6

3445107 PTC PVC PROBE 3000 mm
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7P0A3000

3445155 SILICONE PROBE NTC 3000 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN8S0A3000

3445959 SILICONE PTC PROBE 5000 mm
temperature range $-55+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7S0A5000

3445111 TRANSFORMER 24V/12V 3VA
primary tension 24Vca 50/60Hz
secondary tension 12Vca 3VA
room temperature $0\div 60^{\circ}\text{C}$
screw terminal block
IMQ approved



ELIWELL EWTCM3

ELIWELL TF111115

Suitable for:

Suitable for:

3445399 CONTROLLER ELIWELL ID PLUS 902
 12Vac/dc
 1 relay output 8A for compressor
 1 selectable NTC/PTC/PT1000 probe (not included)
 1 programmable digital/temperature input
 TTL input for copy card connection
 front dimension 74x32x59 mm
 mounting hole 71x29 mm



ELIWELL IC11C10XCD300
 ELIWELL IC11C00TCA300
 ELIWELL IC11C00TCH300
 ELIWELL IC11C00THD300
 ELIWELL IC11D00TCA300
 ELIWELL IC16C00TCA300
 ELIWELL IC16D00TCD300
 ELIWELL T1A1ACH300

ELIWELL IC11C10XHD300
 ELIWELL IC11C00TCD300
 ELIWELL IC11C00TCL300
 ELIWELL IC11C00THF300
 ELIWELL IC11D00TCD300
 ELIWELL IC16C00TCD300
 ELIWELL IC17C00TCA300
 ELIWELL T1B1CCH300

ELIWELL IC11C10XHD700
 ELIWELL IC11C00TCF300
 ELIWELL IC11C00THA300
 ELIWELL IC11D10XCD300
 ELIWELL IC11D00TCH300
 ELIWELL IC16D00TCA300
 ELIWELL IDP11D0300000

3445167 PROBE NTC IP68 1500 mm
 temperature range -50°+110°C
 bulb ø 5x20 mm watertight



ELIWELL SN8T6H1502

3445154 PROBE NTC IP68 3000 mm
 temperature range -40°+110°C
 bulb ø 6x40 mm watertight



ELIWELL SN8T6A3002

3445335 PROBE NTC IP68 3000 mm
 temperature range -50+110°C
 bulb ø 5x20 mm watertight



ELIWELL SN8T6H3002

3445157 PROBE NTC PVC 1500 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



ELIWELL SN8P0A1500

3445184 PROBE NTC PVC 1500 mm IP68
 temperature range -40°+110°C
 bulb ø 6x40 mm watertight



ELIWELL SN8T6A1502

3445156 PROBE NTC PVC 3000 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



ELIWELL SN8P0A3000

3445028 PROBE NTC PVC 4000 mm
 temperature field -30°+80°C
 bulb ø 6x20 mm





Suitable for:

3445379 PROBE PT1000 PVC 1500 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



ELIWELL SN9DAE11502C6

3445070 PTC PVC PROBE 1500 mm
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7P0A1500

3445913 SILICONE PROBE NTC 1500 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN8S0A1500

3445183 SILICONE PTC PROBE 3000 mm
2-wire probe temperature range $-55+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7S0A3000

3445110 TRANSFORMER 230V/12V 3VA
primary tension 230Vca 50/60Hz
secondary tension 12Vca 3VA
room temperature $0+60^{\circ}\text{C}$
screw terminal block
IMQ approved



ELIWELL EWTCM3

ELIWELL TF111173

ELIWELL



Suitable for:

3445380 PROBE PT1000 PVC 3000 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



ELIWELL SN9DAE13002C6

3445107 PTC PVC PROBE 3000 mm
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7P0A3000

3445155 SILICONE PROBE NTC 3000 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN8S0A3000

3445959 SILICONE PTC PROBE 5000 mm
temperature range $-55+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7S0A5000

3445111 TRANSFORMER 24V/12V 3VA
primary tension 24Vca 50/60Hz
secondary tension 12Vca 3VA
room temperature $0\div 60^{\circ}\text{C}$
screw terminal block
IMQ approved



ELIWELL EWTCM3

ELIWELL TF111115



Suitable for:

3445376 CONTROLLER ELIWELL ID PLUS 961
 230V 50/60Hz
 1 relay output 2Hp for compressor
 1 selectable NTC/PTC/PT1000 probe (not included)
 1 programmable digital/temperature input
 pause defrosting
 TTL input for copy card connection
 front dimension 74x32xdepth 59 mm
 mounting hole 71x29 mm



ELIWELL IDP17D0700000
 ELIWELL ID11DM0XCD700
 ELIWELL ID16C00TCA700
 ELIWELL ID17C00TCA700
 ELIWELL ID11C00TCA700
 ELIWELL ID11D00TCA700
 ELIWELL ID16D10XCH700
 ELIWELL ID17D00TCA700

3445154 PROBE NTC IP68 3000 m m
 temperature range $-40^{\circ}+110^{\circ}\text{C}$
 bulb \varnothing 6x40 mm watertight



ELIWELL SN8T6A3002

3445157 PROBE NTC PVC 1500 m m
 temperature range $-30^{\circ}+80^{\circ}\text{C}$
 bulb \varnothing 6x40 mm



ELIWELL SN8P0A1500

3445156 PROBE NTC PVC 3000 m m
 temperature range $-30^{\circ}+80^{\circ}\text{C}$
 bulb \varnothing 6x40 mm



ELIWELL SN8P0A3000

Suitable for:

3445167 PROBE NTC IP68 1500 m m
 temperature range $-50^{\circ}+110^{\circ}\text{C}$
 bulb \varnothing 5x20 mm watertight



ELIWELL SN8T6H1502

3445335 PROBE NTC IP68 3000 m m
 temperature range $-50^{\circ}+110^{\circ}\text{C}$
 bulb \varnothing 5x20 mm watertight



ELIWELL SN8T6H3002

3445184 PROBE NTC PVC 1500 m m IP68
 temperature range $-40^{\circ}+110^{\circ}\text{C}$
 bulb \varnothing 6x40 mm watertight



ELIWELL SN8T6A1502

3445028 PROBE NTC PVC 4000 m m
 temperature field $-30^{\circ}+80^{\circ}\text{C}$
 bulb \varnothing 6x20 mm





Suitable for:

3445379 PROBE PT1000 PVC 1500 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



ELIWELL SN9DAE11502C6

3445070 PTC PVC PROBE 1500 mm
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7P0A1500

3445913 SILICONE PROBE NTC 1500 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN8S0A1500

3445183 SILICONE PTC PROBE 3000 mm
2-wire probe temperature range $-55+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7S0A3000

3445110 TRANSFORMER 230V/12V 3VA
primary tension 230Vca 50/60Hz
secondary tension 12Vca 3VA
room temperature $0+60^{\circ}\text{C}$
screw terminal block
IMQ approved



ELIWELL EWTM3

ELIWELL TF111173

ELIWELL



Suitable for:

3445380 PROBE PT1000 PVC 3000 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



ELIWELL SN9DAE13002C6

3445107 PTC PVC PROBE 3000 mm
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7P0A3000

3445155 SILICONE PROBE NTC 3000 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN8S0A3000

3445959 SILICONE PTC PROBE 5000 mm
temperature range $-55+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7S0A5000

3445111 TRANSFORMER 24V/12V 3VA
primary tension 24Vca 50/60Hz
secondary tension 12Vca 3VA
room temperature $0\div 60^{\circ}\text{C}$
screw terminal block
IMQ approved



ELIWELL EWTM3

ELIWELL TF111115



Suitable for:

Suitable for:

3445400 CONTROLLER ELIWELL ID PLUS 961
 12Vac/dc
 1 relay output 2Hp for compressor
 1 selectable NTC/PTC/PT1000 probe (not included)
 1 programmable digital/temperature input
 pause defrosting
 TTL input for copy card connection
 front dimension 74x32xdepth 59 mm
 mounting hole 71x29 mm



ELIWELL IDP17D0300000
 ELIWELL ID16C00TCA300
 ELIWELL ID17C00TCL300

ELIWELL ID11C00TCA300
 ELIWELL ID16D10XCH300
 ELIWELL ID17D00TCA300

ELIWELL ID11D10XCH300
 ELIWELL ID16D00TCA300

3445167 PROBE NTC IP68 1500 mm
 temperature range -50°+110°C
 bulb ø 5x20 mm watertight



ELIWELL SN8T6H1502

3445154 PROBE NTC IP68 3000 mm
 temperature range -40°+110°C
 bulb ø 6x40 mm watertight



ELIWELL SN8T6A3002

3445335 PROBE NTC IP68 3000 mm
 temperature range -50°+110°C
 bulb ø 5x20 mm watertight



ELIWELL SN8T6H3002

3445157 PROBE NTC PVC 1500 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



ELIWELL SN8P0A1500

3445184 PROBE NTC PVC 1500 mm IP68
 temperature range -40°+110°C
 bulb ø 6x40 mm watertight



ELIWELL SN8T6A1502

3445156 PROBE NTC PVC 3000 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



ELIWELL SN8P0A3000

3445028 PROBE NTC PVC 4000 mm
 temperature field -30°+80°C
 bulb ø 6x20 mm



ELIWELL SN8T6A1502



Suitable for:

3445379 PROBE PT1000 PVC 1500 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



ELIWELL SN9DAE11502C6

3445070 PTC PVC PROBE 1500 mm
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7P0A1500

3445913 SILICONE PROBE NTC 1500 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN8S0A1500

3445183 SILICONE PTC PROBE 3000 mm
2-wire probe temperature range $-55+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7S0A3000

ELIWELL



Suitable for:

3445380 PROBE PT1000 PVC 3000 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



ELIWELL SN9DAE13002C6

3445107 PTC PVC PROBE 3000 mm
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7P0A3000

3445155 SILICONE PROBE NTC 3000 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN8S0A3000

3445959 SILICONE PTC PROBE 5000 mm
temperature range $-55+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7S0A5000

Suitable for:

Suitable for:

3445377 CONTROLLER ELIWELL ID PLUS 971
 230V 50/60Hz
 1 relay output 2Hp for compressor
 1 relay output 8A for defrosting
 2 selectable NTC/PTC/PT1000 probes (not included)
 1 programmable digital/temperature input
 1 programmable digital input
 TTL input for copy card connection
 with buzzer
 front dimension 74x32xdepth 59 mm
 mounting hole 71x29 mm



3445167 PROBE NTC IP68 1500 mm
 temperature range -50°+110°C
 bulb ø 5x20 mm watertight



ELIWELL EW29DIOXCH780
 ELIWELL ID1ACB0TCA700
 ELIWELL ID11CB0TCA700
 ELIWELL ID12DIOXCH700
 ELIWELL ID22DB0TCH700
 ELIWELL ID28C00TCD700
 ELIWELL ID28D00TCH700
 ELIWELL T1G2CCC300

ELIWELL EW29DIOXC4780
 ELIWELL ID1AC00TCA700
 ELIWELL ID12C00TCD700
 ELIWELL ID12D00TCD700
 ELIWELL ID22DIOXCH700
 ELIWELL ID28D00TCD700
 ELIWELL ID29DIOXCH700

ELIWELL IDP29DB700000
 ELIWELL ID1ADB0TCA700
 ELIWELL ID12C00TCH700
 ELIWELL ID22C00TCH700
 ELIWELL ID22D00TCH700
 ELIWELL ID28D00TCD780
 ELIWELL ID29D00TCH700

ELIWELL SN8T6H1502

3445154 PROBE NTC IP68 3000 mm
 temperature range -40°+110°C
 bulb ø 6x40 mm watertight



ELIWELL SN8T6A3002

3445157 PROBE NTC PVC 1500 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



ELIWELL SN8P0A1500

3445156 PROBE NTC PVC 3000 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



ELIWELL SN8P0A3000

3445335 PROBE NTC IP68 3000 mm
 temperature range -50+110°C
 bulb ø 5x20 mm watertight



ELIWELL SN8T6H3002

3445184 PROBE NTC PVC 1500 mm IP68
 temperature range -40°+110°C
 bulb ø 6x40 mm watertight



ELIWELL SN8T6A1502

3445028 PROBE NTC PVC 4000 mm
 temperature field -30°+80°C
 bulb ø 6x20 mm





Suitable for:

3445379 PROBE PT1000 PVC 1500 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



ELIWELL SN9DAE11502C6

3445070 PTC PVC PROBE 1500 mm
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7P0A1500

3445913 SILICONE PROBE NTC 1500 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN8S0A1500

3445183 SILICONE PTC PROBE 3000 mm
2-wire probe temperature range $-55+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7S0A3000

3445110 TRANSFORMER 230V/12V 3VA
primary tension 230Vca 50/60Hz
secondary tension 12Vca 3VA
room temperature $0+60^{\circ}\text{C}$
screw terminal block
IMQ approved



ELIWELL EWTM3

ELIWELL TF111173

ELIWELL



Suitable for:

3445380 PROBE PT1000 PVC 3000 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



ELIWELL SN9DAE13002C6

3445107 PTC PVC PROBE 3000 mm
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7P0A3000

3445155 SILICONE PROBE NTC 3000 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN8S0A3000

3445959 SILICONE PTC PROBE 5000 mm
temperature range $-55+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7S0A5000

3445111 TRANSFORMER 24V/12V 3VA
primary tension 24Vca 50/60Hz
secondary tension 12Vca 3VA
room temperature $0\div 60^{\circ}\text{C}$
screw terminal block
IMQ approved



ELIWELL EWTM3

ELIWELL TF111115

Suitable for:

Suitable for:

3445401 CONTROLLER ELIWELL ID PLUS 971
 12Vac/dc
 1 relay output 2Hp for compressor
 1 relay output 8A for defrosting
 2 selectable NTC/PTC/PT1000 probes (not included)
 1 programmable digital/temperature input
 1 programmable digital input
 TTL input for copy card connection
 with buzzer
 front dimension 74x32xdepth 59 mm
 mounting hole 71x29 mm



3445167 PROBE NTC IP68 1500 mm
 temperature range -50°+110°C
 bulb ø 5x20 mm watertight



ELIWELL IDP29DB300000
 ELIWELL ID1ADL0XCH300
 ELIWELL ID12C00TCD300
 ELIWELL ID16CB0TCA300
 ELIWELL ID22C00TCH300
 ELIWELL ID22D10XCH300
 ELIWELL ID28C00TCD300
 ELIWELL T1E1ACC350

ELIWELL ID1AC00TCA300
 ELIWELL ID1AD00TCA300
 ELIWELL ID12D10XCH300
 ELIWELL ID18C00TCD300
 ELIWELL ID22DB0TCJ300
 ELIWELL ID22DL0XCH300
 ELIWELL ID28D00TCD300

ELIWELL ID1ADB0TCA300
 ELIWELL ID11DL0XCH300
 ELIWELL ID12D00TCD300
 ELIWELL ID18D00TCD300
 ELIWELL ID22D10MCH300
 ELIWELL ID22D00TCH300
 ELIWELL ID29D00TCH300

ELIWELL SN8T6H1502

3445154 PROBE NTC IP68 3000 mm
 temperature range -40°+110°C
 bulb ø 6x40 mm watertight



ELIWELL SN8T6A3002

3445157 PROBE NTC PVC 1500 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



ELIWELL SN8P0A1500

3445156 PROBE NTC PVC 3000 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



ELIWELL SN8P0A3000

3445335 PROBE NTC IP68 3000 mm
 temperature range -50+110°C
 bulb ø 5x20 mm watertight



ELIWELL SN8T6H3002

3445184 PROBE NTC PVC 1500 mm IP68
 temperature range -40°+110°C
 bulb ø 6x40 mm watertight



ELIWELL SN8T6A1502

3445028 PROBE NTC PVC 4000 mm
 temperature field -30°+80°C
 bulb ø 6x20 mm





Suitable for:

3445379 PROBE PT1000 PVC 1500 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



ELIWELL SN9DAE11502C6

3445070 PTC PVC PROBE 1500 mm
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7P0A1500

3445913 SILICONE PROBE NTC 1500 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN8S0A1500

3445183 SILICONE PTC PROBE 3000 mm
2-wire probe temperature range $-55+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7S0A3000

ELIWELL



Suitable for:

3445380 PROBE PT1000 PVC 3000 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



ELIWELL SN9DAE13002C6

3445107 PTC PVC PROBE 3000 mm
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7P0A3000

3445155 SILICONE PROBE NTC 3000 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN8S0A3000

3445959 SILICONE PTC PROBE 5000 mm
temperature range $-55+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7S0A5000



Suitable for:

Suitable for:

3445378 CONTROLLER ELIWELL ID PLUS 974
 230V 50/60Hz
 1 relay output 2Hp for compressor
 1 relay output 8A for defrosting
 1 relay output 5A for fans
 2 selectable NTC/PTC/PT1000 probes (not included)
 1 programmable digital/temperature input
 1 programmable digital input
 TTL input for copy card connection
 with buzzer
 front dimension 74x32xdepth 59 mm
 mounting hole 71x29 mm



3445167 PROBE NTC IP68 1500 mm
 temperature range $-50^{\circ}+110^{\circ}\text{C}$
 bulb \varnothing 5x20 mm watertight



ELIWELL EW2EDI0XCH780
 ELIWELL EW2EDL0XCH790
 ELIWELL ID2EDB0TCHH00
 ELIWELL ID23C00TCD700
 ELIWELL ID23DIOXCH750
 ELIWELL ID23DS0XCD700
 ELIWELL T1L2CCC300

ELIWELL EW2EDI0XC4780
 ELIWELL IDP2EDB700000
 ELIWELL ID2EDI0XCHI00
 ELIWELL ID23DB0TCH700
 ELIWELL ID23DL0XCH700
 ELIWELL ID23D00TCD700
 ELIWELL T7M8DDC330

ELIWELL EW2EDI0XC6780
 ELIWELL ID2CD00TCH700
 ELIWELL ID23CB0TCH700
 ELIWELL ID23DIOXCH700
 ELIWELL ID23DM0XCD700
 ELIWELL ID23D00TCH700

ELIWELL SN8T6H1502

3445154 PROBE NTC IP68 3000 mm
 temperature range $-40^{\circ}+110^{\circ}\text{C}$
 bulb \varnothing 6x40 mm watertight



3445335 PROBE NTC IP68 3000 mm
 temperature range $-50^{\circ}+110^{\circ}\text{C}$
 bulb \varnothing 5x20 mm watertight



ELIWELL SN8T6A3002

ELIWELL SN8T6H3002

3445157 PROBE NTC PVC 1500 mm
 temperature range $-30^{\circ}+80^{\circ}\text{C}$
 bulb \varnothing 6x40 mm



3445184 PROBE NTC PVC 1500 mm IP68
 temperature range $-40^{\circ}+110^{\circ}\text{C}$
 bulb \varnothing 6x40 mm watertight



ELIWELL SN8P0A1500

ELIWELL SN8T6A1502

3445156 PROBE NTC PVC 3000 mm
 temperature range $-30^{\circ}+80^{\circ}\text{C}$
 bulb \varnothing 6x40 mm



3445028 PROBE NTC PVC 4000 mm
 temperature field $-30^{\circ}+80^{\circ}\text{C}$
 bulb \varnothing 6x20 mm



ELIWELL SN8P0A3000



Suitable for:

3445379 PROBE PT1000 PVC 1500 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



ELIWELL SN9DAE11502C6

3445070 PTC PVC PROBE 1500 mm
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7P0A1500

3445913 SILICONE PROBE NTC 1500 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN8S0A1500

3445183 SILICONE PTC PROBE 3000 mm
2-wire probe temperature range $-55+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7S0A3000

ELIWELL



Suitable for:

3445380 PROBE PT1000 PVC 3000 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



ELIWELL SN9DAE13002C6

3445107 PTC PVC PROBE 3000 mm
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7P0A3000

3445155 SILICONE PROBE NTC 3000 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN8S0A3000

3445959 SILICONE PTC PROBE 5000 mm
temperature range $-55+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7S0A5000



Suitable for:

Suitable for:

3445402 CONTROLLER ELIWELL ID PLUS 974
 12Vac/dc
 1 relay output 2Hp for compressor
 1 relay output 8A for defrosting
 1 relay output 5A for fans
 2 selectable NTC/PTC/PT1000 probes (not included)
 1 programmable digital/temperature input
 1 programmable digital input
 TTL input for copy card connection
 with buzzer
 front dimension 74x32xdepth 59 mm
 mounting hole 71x29 mm



3445167 PROBE NTC IP68 1500 mm
 temperature range -50°+110°C
 bulb ø 5x20 mm watertight



ELIWELL IDP2EDB300000
 ELIWELL ID23CB0TCH300
 ELIWELL ID23C00TCD300
 ELIWELL ID23DIOXCH300
 ELIWELL ID23D00TCD300

ELIWELL ID2CDB0TCH300
 ELIWELL ID23CB0TCJ300
 ELIWELL ID23C00TCF300
 ELIWELL ID23DLOXCH300

ELIWELL ID2CD00TCH300
 ELIWELL ID23CIOXCH300
 ELIWELL ID23DB0TCH300
 ELIWELL ID23DLOXCJ300

ELIWELL SN8T6H1502

3445154 PROBE NTC IP68 3000 mm
 temperature range -40°+110°C
 bulb ø 6x40 mm watertight



ELIWELL SN8T6A3002

3445335 PROBE NTC IP68 3000 mm
 temperature range -50°+110°C
 bulb ø 5x20 mm watertight



ELIWELL SN8T6H3002

3445157 PROBE NTC PVC 1500 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



ELIWELL SN8P0A1500

3445184 PROBE NTC PVC 1500 mm IP68
 temperature range -40°+110°C
 bulb ø 6x40 mm watertight



ELIWELL SN8T6A1502

3445156 PROBE NTC PVC 3000 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



ELIWELL SN8P0A3000

3445028 PROBE NTC PVC 4000 mm
 temperature field -30°+80°C
 bulb ø 6x20 mm





Suitable for:

3445379 PROBE PT1000 PVC 1500 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



ELIWELL SN9DAE11502C6

3445070 PTC PVC PROBE 1500 mm
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7P0A1500

3445913 SILICONE PROBE NTC 1500 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN8S0A1500

3445183 SILICONE PTC PROBE 3000 mm
2-wire probe temperature range $-55+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7S0A3000

ELIWELL



Suitable for:

3445380 PROBE PT1000 PVC 3000 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



ELIWELL SN9DAE13002C6

3445107 PTC PVC PROBE 3000 mm
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7P0A3000

3445155 SILICONE PROBE NTC 3000 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN8S0A3000

3445959 SILICONE PTC PROBE 5000 mm
temperature range $-55+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



ELIWELL SN7S0A5000

Suitable for:

Suitable for:

3445066 CONTROLLER ELIWELL ID975LX
 12Vac/dc
 1 relay output 8A for compressor
 1 relay output 8A for defrosting
 1 relay output 5A for evaporator fans
 1 relay outlet 5A for alarm/light
 2 selectable NTC/PTC probes (not included)
 internal buzzer and serial port
 front dimension 74x32xdepth 67 mm
 mounting hole 71x29 mm

3445067 CONTROLLER ELIWELL ID985LX CK
 12Vac/dc
 1 relay output 8A for compressor
 1 relay output 8A for defrosting
 1 relay output 8A for evaporator fans
 1 relay outlet 5A for alarm/light
 2 programmable digital inputs (not included)
 3 selectable NTC/PTC probes (not included)
 LINK- and LINK+ connection
 with RTC function
 TTL serial door
 front dimension 74x32xdepth 67 mm
 mounting hole 71x29 mm



ELIWELL ID24DB0XCD300

ELIWELL ID34DF1XCD300

3445079 CONTROLLER ELIWELL IWC720 SHORT
 230V 50/60Hz
 depth 45 mm
 1 relay output 16A for compressor - faston 6.3 mm
 1 relay output 8A for light - faston 6.3 mm
 1 NTC probe (not included) - faston 2.8 mm
 1 programmable digital input - faston 2.8 mm
 TTL input f/copy card or TELEVIS system connection
 mounting hole 150x31 mm
 front dimension 180x37 mm

3445064 PROBE NTC 1500 mm faston 2.8 mm
 temperature range -30°+80°C



ELIWELL WC12DI0TQD701

ELIWELL SN8P0A1502

3445085 CONTROLLER ELIWELL IWC730 SHORT
 230V 50/60Hz
 depth 45 mm
 1 relay output 16A for compressor - faston 6.3 mm
 1 relay output 20A for defrosting - faston 6.3 mm
 1 relay output 8A for fans - faston 6.3 mm
 2 NTC probes (not included) - faston 2.8 mm
 1 programmable digital input - faston 2.8 mm
 TTL input f/copy card or TELEVIS system connection
 mounting hole 150x31 mm
 front dimension 180x37 mm

3445064 PROBE NTC 1500 mm faston 2.8 mm
 temperature range -30°+80°C



ELIWELL WC23DI0TQD780

ELIWELL SN8P0A1502



Suitable for:

ELIWELL



Suitable for:

3445078 CONTROLLER ELIWELL IWC750
 230V 50/60Hz
 depth 69 mm (without terminals)
 1 relay output 16A for compressor
 1 relay output 20A for defrosting
 1 relay output 8A for fans
 1 relay output 8A for alarm
 1 relay output 8A for aux/light
 2 NTC probes (not included)
 terminals not included
 TTL input for copy card or TELEVIS system
 mounting hole 150x31 mm
 front dimension 180x37 mm



3445319 FEMALE TERMINAL BLOCK KIT FOR IWC750



ELIWELL WC25DI0TCD790

ELIWELL ZZ000075

3445044 HUMIDITY REGULATOR ELIWELL IC PLUS 902 V
 230V 50/60Hz
 1 outlet relay 8A
 relative humidity scale %RH
 inlet: 0-1V 0-5V 0-10V 0-20 mA 4-20 mA selectable
 front dimensions 32x74 x depth 60 mm
 mounting hole 71x29 mm



3445051 HUMIDITY PROBE EWHS 284
 dimensions 103x25 mm
 operating temperature -10+60°C
 humidity measurement range 15/90% RH
 output signal 4..20mA
 power supply 9..28Vdc
 humidity resistive sensor



ELIWELL ICP1110750000

ELIWELL IR11100TUD700

ELIWELL IR11100XUD700

ELIWELL EWHS28

ELIWELL SN5PPN116I3M0

3445043 PRESSURE SWITCH ELIWELL IC915LX/P
 230V 50/60Hz
 2 relay outputs 8A
 BAR pressure scale
 selectable input: 0-20 mA or 4-20 mA
 selectable decimal point
 front dimension 32x74xdepth 60 mm



3445052 PRESSURE PROBE FWPA 007
 operating field -0.5+8 bar
 current output 4..20 mA
 connection with 2000 mm cable
 pressure connection 1/4"saе M
 power supply 8..32 V cc



ELIWELL ICP2210750000

ELIWELL IP11100TRD700

ELIWELL IP12100XR700

ELIWELL TD200107

ELIWELL TD220007



Suitable for:

3445053 PRESSURE PROBE FWPA 030
 operating range 0/+30 bar
 flow output 4..20 mA
 connection with 2000 mm cable
 pressure connection 1/4" sae M
 power supply 8..32 V cc



ELIWELL TD200130

ELIWELL TD220030

ELIWELL



Suitable for:

7107950 THERMOSTAT ELIWELL ID PLUS 961
 12Vac/dc
 1 relay output 2 HP compressor
 1 NTC probe included 1500 mm silicone
 1 digital input / configurable temperature
 defrost stop
 TTL input for Copy Card
 Front dimensions 74x32 59mm depth
 cutout 71x29 mm



ELIWELL IDP17Y03F0001

3445913 SILICONE PROBE NTC 1500 mm
 temperature range -50+110°C
 bulb ø 6x40 mm




ELIWELL SN8S0A1500

7107951 THERMOSTAT ELIWELL ID PLUS 961
 230V 50/60Hz
 1 relay output 2 HP compressor
 1 NTC probe included 1500 mm silicone
 1 NTC probe included 1500 mm silicone
 defrost stop
 TTL input for Copy Card
 Front dimensions 74x32 59mm depth
 cutout 71x29 mm




ELIWELL IDP17Y07F0001

7101290 PROTECTION THERMOSTAT DIXELL



7101290 PROTECTION THERMOSTAT DIXELL





Suitable for:

3445913 SILICONE PROBE NTC 1500 mm
temperature range -50+110°C
bulb ø 6x40 mm



ELIWELL

Suitable for:



ELIWELL SN8S0A1500

7107952 THERMOSTAT ELIWELL ID PLUS 971
12Vac/dc
1 relay output 2 HP compressor
1 relay output 8A for defrosting
1 NTC probe included 1500 mm silicone
1 digital input / configurable temperature
1 digital input configurable
TTL input for Copy Card
with alarm
Front dimensions 74x32x 59 mm depth
cutout 71x29 mm



7101290 PROTECTION THERMOSTAT DIXELL



ELIWELL IDP29YB3F0001

3445913 SILICONE PROBE NTC 1500 mm
temperature range -50+110°C
bulb ø 6x40 mm



ELIWELL SN8S0A1500

7107953 THERMOSTAT ELIWELL ID PLUS 971
230V 50/60Hz
1 relay output 2 HP compressor
1 relay output 8A for defrosting
1 relay output 5A Propeller
1 digital input / configurable temperature
1 digital input configurable
TTL input for Copy Card
with alarm
Front dimensions 74x32x 59 mm depth
cutout 71x29 mm



7101290 PROTECTION THERMOSTAT DIXELL



ELIWELL IDP29YB7F0001



Suitable for:

3445913 SILICONE PROBE NTC 1500 mm
temperature range -50+110°C
bulb ø 6x40 mm



ELIWELL

Suitable for:




ELIWELL SN8S0A1500

7107954 THERMOSTAT ELIWELL ID PLUS 974
12Vac/dc
1 relay output 2 HP compressor
1 relay output 8A for defrosting
1 relay output 5A Propeller
2 NTC probe included 1500 mm silicone
1 digital input / configurable temperature
1 digital input configurable
TTL input for Copy Card
with alarm
Front dimensions 74x32x 59 mm depth
cutout 71x29 mm



7101290 PROTECTION THERMOSTAT DIXELL



ELIWELL IDP2EYB3F0001

3445913 SILICONE PROBE NTC 1500 mm
temperature range -50+110°C
bulb ø 6x40 mm



ELIWELL SN8S0A1500

7107955 THERMOSTAT ELIWELL ID PLUS 974
230V 50/60Hz
1 relay output 2 HP compressor
1 relay output 8A for defrosting
1 sortie relais 5A pour hélices
2 NTC probe included 1500 mm silicone
1 digital input / configurable temperature
1 digital input configurable
TTL input for Copy Card
with alarm
Front dimensions 74x32x 59 mm depth
cutout 71x29 mm



7101290 PROTECTION THERMOSTAT DIXELL



ELIWELL IPD2EYB7F0001



Suitable for:

3445913 SILICONE PROBE NTC 1500 mm
temperature range -50+110°C
bulb \varnothing 6x40 mm



ELIWELL

Suitable for:



ELIWELL SN8S0A1500

Transformers

3445196 TRANSFORMER 230/12V 5VA
primary voltage 230Vac
secondary voltage 12Vac 5VA
room temperature 0 \pm 60°C
screwed terminal block
IMQ approval





















ELIWELL TF111112

The data herewith contained may change without notice and LF SpA cannot be held responsible for possible errors stated or resulting by the use of this document. All rights reserved. No part of this publication may be reproduced without written permission by LF SpA.



Distributing Components, Spare Parts & Accessories in original quality worldwide

-
-  **LF SpA HEADQUARTERS**
via Voltri, 80 - 47522 Cesena (FC) ITALY
Tel. +39 0547 34 11 11 - Fax +39 0547 34 11 10
www.lfircambi724.it - www.lfircambi724.mobi
info@lfircambi.it
Export Dept.: Tel. +39 0547 34 11 50 - Fax: +39 0547 34 11 55
www.lfspareparts724.com - www.lfspareparts724.mobi
export@lfspareparts.com
-  **LF SpA HOUSEHOLD COMPONENTS DIVISION**
Via Padriciano, 34149 Trieste - Italia - AREA Science Park
Tel. +39 0547 34 12 42 - Fax +39 0547 34 12 48
www.lfspareparts724.com - www.lfspareparts724.mobi
info@lfspareparts.com
-  **EPGC Sas FRANCE**
13, Rue des Forts - 59960 Neuville en Ferrain
Tel. +33 (0)3 20 25 06 21
Fax +33 (0)3 20 25 34 12
www.epgc.com
www.epgc724.mobi
epgc@epgc.com
-  **LF GmbH GERMANY**
Junkersstrasse, 3 - D-82178 Puchheim - München
Tel. +49 89 89 45 78 66
Fax +49 89 89 45 78 88
www.lfersatzteile724.de
www.lfersatzteile724.mobi
info@lfersatzteile.de
-  **LF China REPUBLIC OF CHINA**
Room 403, No.2, Huadu Mansion, Lane 422, Huanghua Rd.
Minhang Dist. - 201103 Shanghai
Tel. +86 (0)21 33 53 66 31
Fax +86 (0)21 33 53 66 32
www.lfspareparts724.com
www.lfspareparts724.mobi
china@lfspareparts.com
-  **OOO LF RUSSIAN FEDERATION**
Ul. Anatoliya Zhivova, 8 - office 1 - 123100 Moscow
Tel./Fax +7 495 725 26 53
www.lfspareparts724.ru
www.lfspareparts724.mobi
info@lfspareparts.ru
-  **LF Repuestos Horeca S.L.U. SPAIN**
Poligono Industrial Carpetania - C/Miguel Faraday, 8 - 28906 Getafe
Tel. +34 91 477 91 00
Fax +34 91 477 90 81
www.lfrepuestos-horeca724.es
www.lfrepuestos724.mobi
info@lfrepuestos.es
-  **LF SpA Cesena (IT) Swiss Branch Steinhausen SWITZERLAND**
Sennweidstrasse, 45 - CH-6312 Steinhausen
Tel. +41 (0)41 760 15 80-1
Fax +41 (0)41 760 15 85
www.lfersatzteile724.ch
www.lfersatzteilech724.mobi
info@lfersatzteile.ch
-  **LF Spare Parts Ltd. UNITED KINGDOM**
A10a Lakeside Business Park, Broadway Lane
South Cerney, Gloucestershire GL7 5XL
Tel. +44 (0)1285 86 16 25
Fax +44 (0)1285 86 39 49
www.lfspareparts724.co.uk
www.lfspareparts724.mobi
info@lfspareparts.co.uk
-
-  **AUSTRALIA AND NEW ZEALAND**
www.lfspareparts724.com
andrea.calvio@lfspareparts.com
-  **AUSTRIA**
www.lfersatzteile724.at
info@lfersatzteile.at
-  **BALKAN COUNTRIES**
www.lfspareparts724.com
matijaramov@lfspareparts.com
-  **BALTIC COUNTRIES**
www.lfspareparts724.com
inara.silina@lfspareparts.com
-  **CENTRAL AND EASTERN EUROPE**
www.lfspareparts724.cz
jiri.kremla@lfspareparts.cz
-  **DENMARK**
www.lfspareparts724.dk
michael.leth@lfspareparts.com
-  **JAPAN**
www.lfspareparts724.jp
hiroshi.ukai@lfspareparts.jp
-  **SOUTH KOREA**
www.lfspareparts724.com
fabio.doni@lfspareparts.com
-  **TURKEY**
www.lfyedekparca724.com
basar.ergun@lfyedekparca.com
-  **USA AND CANADA**
www.lfspareparts724.us
sauro.dallaglio@lfspareparts.us
howard.truitt@lfspareparts.us