




Spare parts for:

Cooking equipment

Suitable for:

ELIWELL



This catalogue is automatically generated.
Therefore, the sequence of the items might
not be always shown at best.
Updates will be issued in case of additions
and/or amendments.

*Suitable **universal spare parts** may not be included*





Suitable for:

ELIWELL



Suitable for:

Electronic controllers

3445375 CONTROLLER ELIWELL ID PLUS 902

230V 50/60Hz
1 relay output 8A for compressor
1 selectable NTC/PTC/PT1000 probe (not included)
1 programmable digital/temperature input
TTL input for copy card connection
front dimension 74x32xdepth 59 mm
mounting hole 71x29 mm



ELIWELL EW11D10XB4780
ELIWELL IC11C10XHD700
ELIWELL IC11C00TCF700
ELIWELL IC11C00THD700
ELIWELL IC11D00TCD700
ELIWELL IC16C00TCA700
ELIWELL IC16D00TCD700
ELIWELL IC17C00TCA700

ELIWELL IC11C10MHD700
ELIWELL IC11C00TCA700
ELIWELL IC11C00TCH700
ELIWELL IC11D10XCD700
ELIWELL IC11D00THA700
ELIWELL IC16C00TCD700
ELIWELL IC16D00THA700
ELIWELL IDP11D0700000

ELIWELL IC11C10XCD700
ELIWELL IC11C00TCD700
ELIWELL IC11C00THA700
ELIWELL IC11D00TCA700
ELIWELL IC11D00THD700
ELIWELL IC16D00TCA700
ELIWELL IC16D00THF700
ELIWELL T1B1CCC300

3445399 CONTROLLER ELIWELL ID PLUS 902

12Vac/dc
1 relay output 8A for compressor
1 selectable NTC/PTC/PT1000 probe (not included)
1 programmable digital/temperature input
TTL input for copy card connection
front dimension 74x32x59 mm
mounting hole 71x29 mm



ELIWELL IC11C10XCD300
ELIWELL IC11C00TCA300
ELIWELL IC11C00TCH300
ELIWELL IC11C00THD300
ELIWELL IC11D00TCA300
ELIWELL IC16C00TCA300
ELIWELL IC16D00TCD300
ELIWELL T1A1ACH300

ELIWELL IC11C10XHD300
ELIWELL IC11C00TCD300
ELIWELL IC11C00TCL300
ELIWELL IC11C00THF300
ELIWELL IC11D00TCD300
ELIWELL IC16C00TCD300
ELIWELL IC17C00TCA300
ELIWELL T1B1CCH300

ELIWELL IC11C10XHD700
ELIWELL IC11C00TCF300
ELIWELL IC11C00THA300
ELIWELL IC11D10XCD300
ELIWELL IC11D00TCH300
ELIWELL IC16D00TCA300
ELIWELL IDP11D0300000

3445376 CONTROLLER ELIWELL ID PLUS 961

230V 50/60Hz
1 relay output 2Hp for compressor
1 selectable NTC/PTC/PT1000 probe (not included)
1 programmable digital/temperature input
pause defrosting
TTL input for copy card connection
front dimension 74x32xdepth 59 mm
mounting hole 71x29 mm



ELIWELL EW17D10XB4780
ELIWELL ID11C00TCA700
ELIWELL ID11D00TCA700
ELIWELL ID16D10XCH700
ELIWELL ID17D00TCA700

ELIWELL EW17D10XCH780
ELIWELL ID11D10XCH700
ELIWELL ID11D00TCA780
ELIWELL ID16D00TCA700

ELIWELL IDP17D0700000
ELIWELL ID11DM0XCD700
ELIWELL ID16C00TCA700
ELIWELL ID17C00TCA700

3394331 TELETHERMOMETER EM300 PTC

power supply 12V
setting range -50+120°C
room temperature -5+55°C
PTC type probe (not included)
connections with screw terminal box
front dimensions 76x35x70 mm
mounting hole 71x29 mm



ELIWELL TM10D0000D300

3445070 PTC PVC PROBE 1500 mm

2-wire probe temperature range -30+80°C
bulb ø 6x40 mm



ELIWELL SN7P0A1500



Suitable for:

3445107 PTC PVC PROBE 3000 mm
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb $\varnothing$ 6x40 mm



ELIWELL SN7P0A3000

3445183 SILICONE PTC PROBE 3000 mm
2-wire probe temperature range $-55+150^{\circ}\text{C}$
bulb $\varnothing$ 6x40 mm



ELIWELL SN7S0A3000

3445110 TRANSFORMER 230V/12V 3VA
primary tension 230Vca 50/60Hz
secondary tension 12Vca 3VA
room temperature $0+60^{\circ}\text{C}$
screw terminal block
IMQ approved



ELIWELL EWTCM3

ELIWELL TF111173

3394320 THERMOMETER EM300LX PT100/TCJ/TCK
power supply 12Vac/dc
thermostat setting range $-200+1350^{\circ}\text{C}$
room temperature $-5+55^{\circ}\text{C}$
suitable for TELEVIS SYSTEM
alarm buzzer
probe type PT100-TCJ-TCK (not included)
serial port TTL
connections by screw terminal block
front dimensions 74x32x30 mm
mounting hole 71x29mm



ELIWELL EM300LX

ELIWELL TM10200X0M300

ELIWELL



Suitable for:

3397164 SILICONE PTC PROBE 1500 mm
2 wire probe temperature range $-55+150^{\circ}\text{C}$
bulb $\varnothing$ 6x40 mm



ELIWELL SN650150

ELIWELL SN650170

ELIWELL SN7S0A1500

3445959 SILICONE PTC PROBE 5000 mm
temperature range $-55+150^{\circ}\text{C}$
bulb $\varnothing$ 6x40 mm



ELIWELL SN7S0A5000

3445111 TRANSFORMER 24V/12V 3VA
primary tension 24Vca 50/60Hz
secondary tension 12Vca 3VA
room temperature $0+60^{\circ}\text{C}$
screw terminal block
IMQ approved



ELIWELL EWTCM3

ELIWELL TF111115

3445117 PROBE PT100 VETROTEX 3000 mm
3-wire probe temperature range $0+350^{\circ}\text{C}$
bulb $\varnothing$ 6x100 mm



ELIWELL SN200009



Suitable for:

3445109 PROBE TCJ VETROTEX 3000 mm
2-wire probe temperature range 0+600°C
temperature cable max 350°C
error limit $\pm 0.75\%$ below 0°C
response time 30 sec
bulb $\varnothing$ 6x100 mm



ELIWELL SN300000

ELIWELL TCOT3M

3445110 TRANSFORMER 230V/12V 3VA
primary tension 230Vca 50/60Hz
secondary tension 12Vca 3VA
room temperature 0+60°C
screw terminal block
IMQ approved



ELIWELL EWTOM3

ELIWELL TF111173

3445015 THERMOSTAT EWPC800/T PTC
power supply 220V
ON-OFF control with one actuation point only
1 changeover relay outlet 8(3)A 250V
2 types of programmable temperature alarms
room temperature $-5 \div 65^\circ\text{C}$
probe type PTC (not included)
connections by screw terminal block
front dimensions 72x72x98 mm



ELIWELL T2B1CCC700

3445107 PTC PVC PROBE 3000 mm
2-wire probe temperature range $-30+80^\circ\text{C}$
bulb $\varnothing$ 6x40 mm



ELIWELL SN7P0A3000

ELIWELL



Suitable for:

3397140 THERMOCOUPLE TEMPER. PROBE TCK
2 wires - temperature $-40+1150^\circ\text{C}$
bulb $\varnothing$ 6x140 mm - cable length 3000 mm



ELIWELL SN400011

3445111 TRANSFORMER 24V/12V 3VA
primary tension 24Vca 50/60Hz
secondary tension 12Vca 3VA
room temperature $0 \div 60^\circ\text{C}$
screw terminal block
IMQ approved



ELIWELL EWTOM3

ELIWELL TF111115

3445070 PTC PVC PROBE 1500 mm
2-wire probe temperature range $-30+80^\circ\text{C}$
bulb $\varnothing$ 6x40 mm



ELIWELL SN7P0A1500

3445183 SILICONE PTC PROBE 3000 mm
2-wire probe temperature range $-55+150^\circ\text{C}$
bulb $\varnothing$ 6x40 mm



ELIWELL SN7S0A3000



Suitable for:

3445959 SILICONE PTC PROBE 5000 mm
temperature range $-55^{\circ}+150^{\circ}\text{C}$
bulb $\varnothing 6 \times 40$ mm



ELIWELL SN7S0A5000

3445111 TRANSFORMER 24V/12V 3VA
primary tension 24Vca 50/60Hz
secondary tension 12Vca 3VA
room temperature $0 \div 60^{\circ}\text{C}$
screw terminal block
IMQ approved



ELIWELL EWTOM3

ELIWELL TF111115

3445326 THERMOSTAT ICPUS915 PT100/TCJ/TCK
power supply 230V
thermostat setting range $-150+1350^{\circ}\text{C}$
ON-OFF control with two actuation points
2 changeover relay outputs 8(4)A 250V
room temperature $-5+55^{\circ}\text{C}$
probe type PT100-TCJ-TCK (not included)
connections by screw terminal block
front dimensions 78x37x64 mm
mounting hole 71x29 mm



ELIWELL ICP22J1750000

ELIWELL IC11J10XHD700

ELIWELL IC11P00THD700

3397140 THERMOCOUPLE TEMPER.PROBE TCK
2 wires - temperature $-40+1150^{\circ}\text{C}$
bulb $\varnothing 6 \times 140$ mm - cable length 3000 mm



ELIWELL SN400011

ELIWELL



Suitable for:

3445110 TRANSFORMER 230V/12V 3VA
primary tension 230Vca 50/60Hz
secondary tension 12Vca 3VA
room temperature $0+60^{\circ}\text{C}$
screw terminal block
IMQ approved



ELIWELL EWTOM3

ELIWELL TF111173

3445109 PROBE TCJ VETROTEX 3000 mm
2-wire probe temperature range $0+600^{\circ}\text{C}$
temperature cable max 350°C
error limit $\pm 0.75\%$ below 0°C
response time 30 sec
bulb $\varnothing 6 \times 100$ mm



ELIWELL SN300000

ELIWELL TCOT3M

3445110 TRANSFORMER 230V/12V 3VA
primary tension 230Vca 50/60Hz
secondary tension 12Vca 3VA
room temperature $0+60^{\circ}\text{C}$
screw terminal block
IMQ approved



ELIWELL EWTOM3

ELIWELL TF111173



Suitable for:

3445111 TRANSFORMER 24V/12V 3VA
 primary tension 24Vca 50/60Hz
 secondary tension 12Vca 3VA
 room temperature 0÷60°C
 screw terminal block
 IMQ approved



ELIWELL EWTOM3

ELIWELL TF111115

ELIWELL



Suitable for:

3445327 THERMOSTAT ICPLUS915 PT100/TCJ/TCK
 power supply 12V
 thermostat setting range -150+1350°C
 ON-OFF control with two actuation points
 2 exchange relay outputs 8(4)A 250V
 room temperature -5+55°C
 probe type PT100-TCJ-TCK (not included)
 connections by screwed terminal block
 front dimension 78x37x64 mm
 mounting hole 71x29 mm



ELIWELL ICP22J1350000

ELIWELL IC11J10XHD300

ELIWELL IC11J00THD300

ELIWELL IC11P10XHD300

ELIWELL IC11P00THD300

ELIWELL T1B1CPH300


3445109 PROBE TCJ VETROTEX 3000 mm
 2-wire probe temperature range 0+600°C
 temperature cable max 350°C
 error limit ±0.75% below 0°C
 response time 30 sec
 bulb ø 6x100 mm



ELIWELL SN300000

ELIWELL TCOT3M

3397140 THERMOCOUPLE TEMPER.PROBE TCK
 2 wires - temperature -40+1150°C
 bulb ø 6x140 mm - cable length 3000 mm



ELIWELL SN400011

3445111 TRANSFORMER 24V/12V 3VA
 primary tension 24Vca 50/60Hz
 secondary tension 12Vca 3VA
 room temperature 0÷60°C
 screw terminal block
 IMQ approved



ELIWELL EWTOM3

ELIWELL TF111115

3445110 TRANSFORMER 230V/12V 3VA
 primary tension 230Vca 50/60Hz
 secondary tension 12Vca 3VA
 room temperature 0+60°C
 screw terminal block
 IMQ approved



ELIWELL EWTOM3

ELIWELL TF111173

Suitable for:

Suitable for:

3445019 THERMOSTAT IC912 PT100/TCJ/TCK
 power supply 24V
 thermostat setting range $-150+1350^{\circ}\text{C}$
 control with 1 actuation point
 1 changeover relay output 8(3)A 250V
 serial port for data exchange
 ambient temperature $-5\div 55^{\circ}\text{C}$
 PT100 probe (not included)
 connections by screw terminal block
 front dimensions 74x32x59 mm
 mounting hole 71x29mm



ELIWELL ICP11J0550000

ELIWELL IC11J00THD500

ELIWELL IC11P00THD500

ELIWELL T1B1CPH500

3445109 PROBE TCJ VETROTEX 3000 mm
 2-wire probe temperature range $0+600^{\circ}\text{C}$
 temperature cable max 350°C
 error limit $\pm 0.75\%$ below 0°C
 response time 30 sec
 bulb $\varnothing 6 \times 100$ mm



ELIWELL SN300000

ELIWELL TCOT3M

3397140 THERMOCOUPLE TEMPER.PROBE TCK
 2 wires - temperature $-40+1150^{\circ}\text{C}$
 bulb $\varnothing 6 \times 140$ mm - cable length 3000 mm



ELIWELL SN400011

3445110 TRANSFORMER 230V/12V 3VA
 primary tension 230Vca 50/60Hz
 secondary tension 12Vca 3VA
 room temperature $0+60^{\circ}\text{C}$
 screw terminal block
 IMQ approved



ELIWELL EWTOM3

ELIWELL TF111173

3445111 TRANSFORMER 24V/12V 3VA
 primary tension 24Vca 50/60Hz
 secondary tension 12Vca 3VA
 room temperature $0\div 60^{\circ}\text{C}$
 screw terminal block
 IMQ approved



ELIWELL EWTOM3

ELIWELL TF111115



Suitable for:

ELIWELL




Suitable for:

- 3445328 THERMOSTAT IC912/H/PH PT100/TCJ/TCK**
 power supply 250V
 thermostat setting range $-150+1350^{\circ}\text{C}$
 ON-OFF control with one actuation point only
 1 changeover relay output 8(3)A 250V
 room temperature $-5+55^{\circ}\text{C}$
 probe type PT100-TCJ-TCK (not included)
 connections by screw terminal block
 front dimensions 74x32x59 mm
 mounting hole 71x29 mm



ELIWELL IC11J00THD706

- 3397140 THERMOCOUPLE TEMPER.PROBE TCK**
 2 wires - temperature $-40+1150^{\circ}\text{C}$
 bulb $\varnothing 6 \times 140$ mm - cable length 3000 mm



ELIWELL SN400011

- 3445111 TRANSFORMER 24V/12V 3VA**
 primary tension 24Vca 50/60Hz
 secondary tension 12Vca 3VA
 room temperature $0 \div 60^{\circ}\text{C}$
 screw terminal block
 IMQ approved



ELIWELL EWTCM3

ELIWELL TF111115

- 3446209 TIMER EWTS950 LX 12Vac**
 1 exchange relay outlet 8(3)A 250V
 thermostat display range:
 9999h. 99h and 59'. 99'and 59". 99"and 99 cents
 operating range $0 \div 55^{\circ}\text{C}$
 voltage 12Vca/dc
 connections with screw terminal
 dimensions 74x32x60 mm
 mounting hole 71x29 mm



ELIWELL ET010I0XTT300

ELIWELL ET010I0XTT301

ELIWELL E4SSSS300

- 3445109 PROBE TCJ VETROTEX 3000 mm**
 2-wire probe temperature range $0+600^{\circ}\text{C}$
 temperature cable max 350°C
 error limit $\pm 0.75\%$ below 0°C
 response time 30 sec
 bulb $\varnothing 6 \times 100$ mm



ELIWELL SN300000

ELIWELL TCOT3M

- 3445110 TRANSFORMER 230V/12V 3VA**
 primary tension 230Vca 50/60Hz
 secondary tension 12Vca 3VA
 room temperature $0+60^{\circ}\text{C}$
 screw terminal block
 IMQ approved



ELIWELL EWTCM3

ELIWELL TF111173

Measuring tools

3394207 DIGITAL THERMOMETER -50+70°C BLACK

battery powered
front battery
working temperature 0+50°C
accuracy $\pm 1^\circ\text{C}$
resolution 0.1°C
dimensions 62.5x29.5x19 mm
remote probe 1600 mm



ELIWELL T1M1BT0109

3394209 DIGITAL THERMOMETER T-2919 BLACK

precision $\pm 1^\circ\text{C}$
size frequency: every 10 seconds
lithium battery power 1x1,5V "LR44"
probe with polycarbonate cable 1500 mm
bulb $\varnothing$ 6x30 mm
CE approved
built-in mounting hole 45x25 mm



ELIWELL T1M1BT0107

Probes

3445157 PROBE NTC PVC 1500 mm

temperature range $-30^\circ\text{C}+80^\circ\text{C}$
bulb $\varnothing$ 6x40 mm



ELIWELL SN8P0A1500

3445117 PROBE PT100 VETROTEX 3000 mm

3-wire probe temperature range $0^\circ\text{C}+350^\circ\text{C}$
bulb $\varnothing$ 6x100 mm



ELIWELL SN200009

3445109 PROBE TCJ VETROTEX 3000 mm

2-wire probe temperature range $0^\circ\text{C}+600^\circ\text{C}$
temperature cable max 350°C
error limit $\pm 0.75\%$ below 0°C
response time 30 sec
bulb $\varnothing$ 6x100 mm



ELIWELL SN300000

ELIWELL TCOT3M

3397093 PROBE THERMOCOUPLE TCJ

twin wire - temperature $0^\circ\text{C}-250^\circ\text{C}$
probe length 100 mm
cable length 950 mm



ELIWELL SN300017

3445070 PTC PVC PROBE 1500 mm

2-wire probe temperature range $-30^\circ\text{C}+80^\circ\text{C}$
bulb $\varnothing$ 6x40 mm



ELIWELL SN7P0A1500

3445107 PTC PVC PROBE 3000 mm

2-wire probe temperature range $-30^\circ\text{C}+80^\circ\text{C}$
bulb $\varnothing$ 6x40 mm



ELIWELL SN7P0A3000



Suitable for:

3397164 SILICONE PTC PROBE 1500 mm
2 wire probe temperature range -55+150°C
bulb ø 6x40 mm



ELIWELL SN650150

ELIWELL SN650170

ELIWELL SN7S0A1500

Suitable for:

3445183 SILICONE PTC PROBE 3000 mm
2-wire probe temperature range -55+150°C
bulb ø 6x40 mm



ELIWELL SN7S0A3000


3397140 THERMOCOUPLE TEMPER.PROBE TCK
2 wires - temperature -40+1150°C
bulb ø 6x140 mm - cable length 3000 mm



ELIWELL SN400011


Relays

3351154 BASE OCTAL ES8 10A 400V
8 poles



ELIWELL CN111114

3351158 BASE UNDECAL ES11 10A 400V
11 poles



ELIWELL CN111134

Transformers

3445110 TRANSFORMER 230V/12V 3VA
primary tension 230Vca 50/60Hz
secondary tension 12Vca 3VA
room temperature 0+60°C
screw terminal block
IMQ approved



ELIWELL EWTOM3

ELIWELL TF111173

3445111 TRANSFORMER 24V/12V 3VA
primary tension 24Vca 50/60Hz
secondary tension 12Vca 3VA
room temperature 0÷60°C
screw terminal block
IMQ approved



ELIWELL EWTOM3

ELIWELL TF111115

The data herewith contained may change without notice and LF SpA cannot be held responsible for possible errors stated or resulting by the use of this document. All rights reserved. No part of this publication may be reproduced without written permission by LF SpA.



Distributing Components, Spare Parts & Accessories in original quality worldwide



LF SpA HEADQUARTERS
via Voltri, 80 - 47522 Cesena (FC) ITALY
Tel. +39 0547 34 11 11 - Fax +39 0547 34 11 10
www.lfircambi724.it - www.lfircambi724.mobi - info@lfircambi.it
Export Dept.: Tel. +39 0547 34 11 50 - Fax: +39 0547 34 11 55
www.lfspareparts724.com - www.lfspareparts724.mobi
export@lfspareparts.com



EPGC Sas FRANCE
13, Rue des Forts - 59960 Neuville en Ferrain
Tel. +33 (0)3 20 25 06 21
Fax +33 (0)3 20 25 34 12
www.epgc.com
www.epgc724.mobi
epgc@epgc.com



LF GmbH GERMANY
Junkersstrasse, 3 - D-82178 Puchheim - München
Tel. +49 89 89 45 78 66
Fax +49 89 89 45 78 88
www.lfersatzteile724.de
www.lfersatzteile724.mobi
info@lfersatzteile.de



LF China REPUBLIC OF CHINA
Room 403, No.2, Huadu Mansion, Lane 422, Huanghua Rd.
Minhang Dist. - 201103 Shanghai
Tel. +86 (0)21 33 53 66 31
Fax +86 (0)21 33 53 66 32
www.lfspareparts724.com
www.lfspareparts724.mobi
china@lfspareparts.com



OOO LF RUSSIAN FEDERATION
Ul. Anatoliya Zhivova, 8 - office 1 - 123100 Moscow
Tel./Fax +7 495 725 26 53
www.lfspareparts724.ru
www.lfspareparts724.mobi
info@lfspareparts.ru



LF Repuestos Horeca S.L.U. SPAIN
Calle Ciudad Real, 10 - 45517 Escalonilla - Toledo
Tel. +34 91 477 91 00
Fax +34 91 477 90 81
www.lfrepuestos-horeca724.es
www.lfrepuestos724.mobi
info@lfrepuestos.es



LF SpA Cesena (IT) Swiss Branch Steinhausen SWITZERLAND
Sennweidstrasse, 45 - CH-6312 Steinhausen
Tel. +41 (0)41 760 15 80-1
Fax +41 (0)41 760 15 85
www.lfersatzteile724.ch
www.lfersatzteilech724.mobi
info@lfersatzteile.ch



LF Spare Parts Ltd. UNITED KINGDOM
A10a Lakeside Business Park, Broadway Lane
South Cerney, Gloucestershire GL7 5XL
Tel. +44 (0)1285 86 16 25
Fax +44 (0)1285 86 39 49
www.lfspareparts724.co.uk
www.lfspareparts724.mobi
info@lfspareparts.co.uk



AUSTRALIA AND NEW ZEALAND
www.lfspareparts724.com
andrea.calvio@lfspareparts.com



AUSTRIA
www.lfersatzteile724.at
info@lfersatzteile.at



BALKAN COUNTRIES
www.lfspareparts724.com
matija.ramov@lfspareparts.com



BALTIC COUNTRIES
www.lfspareparts724.com
inara.silina@lfspareparts.com



CENTRAL AND EASTERN EUROPE
www.lfspareparts724.cz
jiri.kremla@lfspareparts.cz



DENMARK
www.lfspareparts724.dk
michael.leth@lfspareparts.com



JAPAN
www.lfspareparts724.jp
hiroshi.ukai@lfspareparts.jp



SOUTH KOREA
www.lfspareparts724.com
fabio.doni@lfspareparts.com



TURKEY
www.lfyedekparca724.com
basar.ergun@lfyedekparca.com



USA AND CANADA
www.lfspareparts724.us
sauro.dallaglio@lfspareparts.us
howard.truitt@lfspareparts.us