




Spare parts for:

Cooking equipment



Suitable for:

FIAMMA RST



This catalogue is automatically generated.
Therefore, the sequence of the items might
not be always shown at best.

Updates will be issued in case of additions
and/or amendments.

Suitable universal spare parts may not be included





Suitable for:

FIAMMA RST



Suitable for:

Axial motors

3240502 AXIAL FAN SUNON 80x80x25 mm
ball bearings
230V 50/60Hz 14W 2450rpm
SF23080AT-2082HBL.GN



FIAMMA RST 91100.05.026

Burners, flame spreaders and accessories

3025300 BURNER CAP ø 120 mm 7Kw



FIAMMA RST 91110.36.032

3025306 BURNER ø 120 mm 7Kw



3025299 BURNER ø 120 mm 7Kw



5017735 BURNER ø 120 mm 7Kw



3020093 BURNER INJECTOR ASSEMBLY
with LPG and natural gas nozzles M9x1
pipe ø 12 mm



3025314 SPARKING PLUG SUPPORT
for burners ø 120 mm



3025315 THERMOCOUPLE SUPPORT
for burners ø 120 mm




3025301 VENTURI F/BURNER CAP 120 mm 7Kw





Suitable for:

3025307 VENTURI F/BURNER CAP 120 mm 7Kw




FIAMMA RST

Suitable for:



3025134 FLAME SPREADER \varnothing 100 mm 10KW



FIAMMA RST 91140.05.011

3186317 O-RING 02131 RED SILICONE
for pod punch



3025133 BURNER BODY \varnothing 100 mm 10KW



3025132 VENTURI F/FLAME SPREADER 100 mm 10kW



3025135 VENTURI SUPPORT 6-10Kw



3025326 FLAME SPREADER \varnothing 130 mm 3.6KW



FIAMMA RST 91140.220.126

3025327 FLAME SPREADER \varnothing 60 mm




FIAMMA RST 91140.220.127

3025328 BURNER \varnothing 130 mm 3.6KW



3025339 VENTURI F/FLAME SPREADER 130 mm 3.6KW






Suitable for:

FIAMMA RST



Suitable for:

3025327 FLAME SPREADER \varnothing 60 mm



FIAMMA RST 91140.220.127

Cables for piezo igniters


3001032 IGNITION CABLE 600 mm
with faston terminal \varnothing 2.4 mm for ignition
with faston hole \varnothing 4 mm for plug



FIAMMA RST 91161.129.006

Contact thermostats


7105114 CONTACT THERMOSTAT 160°C
with manual reset - 16A 250V
for Fry top (FIAMMA RST)



FIAMMA RST 4.0.066.0108

FIAMMA RST 4.0.066.0109

3744158 CONTACT THERMOSTAT 95°C
with manual reset
for Bain-marie (FIAMMA RST)



FIAMMA RST 4.0.160.0020

Contactors


3446214 CONTACTOR LOVATO BG09T4A
4KW 400V 9A - 4 normally open contacts
coil 230V 50/60Hz



FIAMMA RST 4.0.089.0003

Drain hoses

3450032 DRAIN PIPE \varnothing 38x2000 mm
muffs internal \varnothing 31 and 40 mm
max temperature 90°C



FIAMMA RST 90805.127.024



Electrical gas valves and accessories

3526092 ELETTROSIT VALVE \varnothing 1/2"FF
 inlet \varnothing 1/2" F - outlet \varnothing 1/2" F
 thermocouple connection M9x1
 maximum gas inlet pressure 50 mbar
 pressure adjustment range
 3 ÷ 18 mbar
 ambient temperature 0 ÷ 60°C
 power supply 220/240V 50Hz
 long buttons
 pilot connection and LATERAL thermocouple



FIAMMA RST 91116.127.001

3526108 ELBOW FLANGE \varnothing 1/2" F
 with screws and "O" ring
 for ELETTROSIT VALVE



3526106 STRAIGHT FLANGE \varnothing 1/2" F
 with screws and "O" ring
 for ELETTROSIT VALVE



3526096 VALVE MICROSWITCH
 maximum load 0.2 A
 for VALVE ELETTROSIT-820 NOVA-824 NOVASIT



3526100 COIL 220V
 for VALVE ELETTROSIT



3001008 PIEZO IGNITER
 a \varnothing 14 mm hole is required for the assembly
 faston M \varnothing 2.4 mm



3526107 STRAIGHT FLANGE \varnothing 3/4" F
 with screws and "O" ring
 for ELETTROSIT VALVE



3526138 VALVE PROTECTION 72x44 mm





Suitable for:

FIAMMA RST



3526079 VALVE 820 NOVA \varnothing 1/2"FF
 inlet \varnothing 1/2" F - outlet \varnothing 1/2" F
 thermocouple fitting M9x1
 maximum gas inlet pressure 60 mbar
 outlet pressure setting range
 3÷30 mbar
 room temperature 0÷70°C
 power supply 230V 50Hz



Suitable for:

3526270 VALVE 820 NOVA EXTENSION
 D shaft \varnothing 10x8 mm



FIAMMA RST 91116.127.002

3526098 COIL 220V
 for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



3526099 COIL 24V
 for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



3526077 ELBOW FLANGE \varnothing 1/2" F
 complete with screws and O-Ring
 for valves SIT 820-Honeywell V4400-V4600-VR4605P



3526078 ELBOW FLANGE \varnothing 3/4" F
 complete with screws and O-Ring
 for valves SIT 820-Honeywell V4400-V4600-VR4605P



3526102 ELECTRIC COUPLING WITH CABLE
 for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



5047586 EXTENSION FOR VALVE 820 NOVA
 D-shaped pin \varnothing 10x8 mm



3241141 EXTENSION FOR 820 NOVA VALVE
 D-shaped pin 10x8 mm
 for OVEN- FRYER



4057862 FITTING \varnothing 3/4" M-3/4" M BRASS





Suitable for:

3526124 KNOB EXTENSION LENGTH 77 mm
for VALVE 820 NOVA-824 NOVASIT



3182008 MAGNETIC UNIT SIT
ø head 35 mm - ø end 20 mm - length 47 mm
for valve SIT NOVASIT 820



FIAMMA RST 91116.127.005

3020084 NUT & OLIVE ø 6 mm



3526103 PROTECTING COVER
for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



3526076 STRAIGHT FLANGE ø 3/4"
complete with screws and O-Ring
for valves SIT 820-Honeywell V4400-V4600-VR4605P



3526096 VALVE MICROSWITCH
maximum load 0.2 A
for VALVE ELETTROSIT-820 NOVA-824 NOVASIT



FIAMMA RST



Suitable for:

3241142 KNOB GASKET ø 44 mm



3020083 NUT & OLIVE ø 4 mm



3001008 PIEZO IGNITER
a ø 14 mm hole is required for the assembly
faston M ø 2.4 mm



3526075 STRAIGHT FLANGE ø 1/2"
complete with screws and O-Ring
for valves SIT 820-Honeywell V4400-V4600-VR4605P



5012595 VALVE EXTENSION 820 NOVA
D-shaped pin ø 6x4.6 mm



3526269 VALVE 820 NOVA EXTENSION
D shaft ø 10x8 mm





Suitable for:

FIAMMA RST



3523084 VALVE 826 NOVA \varnothing 1/2"FF
 inlet \varnothing 1/2" F - outlet \varnothing 1/2" F
 maximum gas inlet pressure 60 mbar
 outlet pressure range setting
 2÷50 mbar
 room temperature 0÷60°C
 power supply 230V 50Hz



FIAMMA RST 91101.220.003

3526099 COIL 24V
 for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



3526098 COIL 220V
 for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



3526077 ELBOW FLANGE \varnothing 1/2" F
 complete with screws and O-Ring
 for valves SIT 820-Honeywell V4400-V4600-VR4605P



3526078 ELBOW FLANGE \varnothing 3/4" F
 complete with screws and O-Ring
 for valves SIT 820-Honeywell V4400-V4600-VR4605P



3030001 ELECTRIC COUPLING WITH CABLE
 for valve sit 824 NOVA-826 NOVA



3526102 ELECTRIC COUPLING WITH CABLE
 for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



3526143 MODULATOR COIL
 220V rectified
 for VALVE 836 TANDEM



3020083 NUT & OLIVE \varnothing 4 mm



3020084 NUT & OLIVE \varnothing 6 mm





Suitable for:

3526103 PROTECTING COVER
for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA



FIAMMA RST



Suitable for:

3526075 STRAIGHT FLANGE \varnothing 1/2"
complete with screws and O-Ring
for valves SIT 820-Honeywell V4400-V4600-VR4605P



3526076 STRAIGHT FLANGE \varnothing 3/4"
complete with screws and O-Ring
for valves SIT 820-Honeywell V4400-V4600-VR4605P



Electronic printed-circuit boards

7108882 MAIN CIRCUIT BOARD 105x70 mm
for Fry top (FIAMMA RST)



FIAMMA RST 4.0.201.0050

Energy regulators

3350026 ENERGY ADJUSTER
contact capacity 230V 13A - max temperature 125°C
D-shaped pin \varnothing 6x4.6 mm
double rotation direction
for PYROCERAM. TOPS-SALAMANDERS-POTATO WARMERS
for Salamander (FIAMMA RST)



FIAMMA RST 4.0.130.0009

Fittings

3349318 NICHEL-PLATED FITTING \varnothing 1/8" M-1/8" M



FIAMMA RST 5.0.000.0725



Suitable for:

FIAMMA RST



Suitable for:

Fryer baskets and accessories

3055757 FRYER BASKET 250x220x105 mm
for Fryer (FIAMMA RST)



FIAMMA RST 4.0.085.1031

5037567 FRYER BASKET 275x210x110 mm
in chrome plated iron



FIAMMA RST 91152.129.009

3055191 FRYER BASKET 365x240x120 mm
in chrome-plated iron



FIAMMA RST 91152.127.010

Gas burners

3023347 BURNER \varnothing 40x290 mm
overall length 330 mm
made of STAINLESS steel
for Bain-marie gas (FIAMMA RST)



FIAMMA RST 7.0.100.0105

3023282 BURNER 450x325 mm
made of stainless steel



FIAMMA RST 91190.127.001

3500356 GAS NOZZLE M11x1 \varnothing 1,60 mm






Gas taps and accessories

3348205 GAS TAP

no pilot burner flame
 connection to pipe flange \varnothing 13 mm
 outlet connection \varnothing 1/4"
 thermocouple connection M9x1
 pin length 25 mm
 D-shaped pin \varnothing 6x4.6 mm
 for Bain-marie gas (FIAMMA RST)



FIAMMA RST 4.0.150.0010

3348014 GAS TAP 20/S

without pilot flame
 fittings \varnothing M16x1.5mm
 thermocouple fitting M8x1
 D-shaped pin \varnothing 8x6.5mm



FIAMMA RST 91110.36.013

5014757 CONNECTION PIPE \varnothing 6 mm

thread M10x1 mm




3348059 MAGNET PROTECTION NUT M9x1

thread M18x1mm
 for model PEL 20-21-22



3348020 CAP WITH PIN \varnothing 8x6.5 mm

pin length 22 mm
 for model PEL 20S



3348058 MAGNET PROTECTION NUT M8x1

thread M18x1 mm
 for model PEL 20-21-22



3182011 MAGNETIC UNIT PEL SMALL HEADED

\varnothing head 15 mm - \varnothing end 11 mm - length 44 mm
 for PEL tap models 20-21
 for EGA tap model 25213
 for JUNKERS tap model CH110






Suitable for:

3348037 OLIVE FOR PILOT PIPE \varnothing 6 mm
for model PEL 21-22-25



3348043 PIPE FITTING \varnothing 10 mm
thread M16x1.5
for model PEL 20-21



3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



3348074 GAS TAP 21S
with pilot flame
flange pipe connection \varnothing 21 mm
outlet fittings \varnothing M16x1.5mm
with flow regulator
thermocouple connection M8x1
D-shaped pin \varnothing 8x6.5 mm



FIAMMA RST 91140.220.017

3348058 MAGNET PROTECTION NUT M8x1
thread M18x1 mm
for model PEL 20-21-22



FIAMMA RST




Suitable for:

3348036 OLIVE FOR 4 mm \varnothing PIPE
for model PEL 21-22



3348029 PIPE FITTING \varnothing 4 mm
thread M10x1
for model PEL 21-22



3348044 PIPE OLIVE \varnothing 10 mm
for model PEL 20 - 21



5014757 CONNECTION PIPE \varnothing 6 mm
thread M10x1 mm



3348059 MAGNET PROTECTION NUT M9x1
thread M18x1mm
for model PEL 20-21-22





Suitable for:


3182011 MAGNETIC UNIT PEL SMALL HEADED
ø head 15 mm - ø end 11 mm - length 44 mm
for PEL tap models 20-21
for EGA tap model 25213
for JUNKERS tap model CH110



3348036 OLIVE FOR 4 mm ø PIPE
for model PEL 21-22



3348029 PIPE FITTING ø 4 mm
thread M10x1
for model PEL 21-22



3348044 PIPE OLIVE ø 10 mm
for model PEL 20 - 21



3348003 GAS TAP 22S/V
with pilot flame
with vertical flange
fittings ø M20x1.5mm
with flow regulator
thermocouple connection M9x1
D-shaped pin ø 10x8 mm



FIAMMA RST

Suitable for:

3348037 OLIVE FOR PILOT PIPE ø 6 mm
for model PEL 21-22-25



3348043 PIPE FITTING ø 10 mm
thread M16x1.5
for model PEL 20-21



3020078 PIPE FITTING ø 6 mm
thread M10x1




3348017 CAP WITH PIN ø 10x8 mm
pin length 26 mm
for model PEL 22





Suitable for:

3348019 CAP WITH PIN \varnothing 10x9 mm
pin length 26 mm
for model PEL 22



FIAMMA RST



Suitable for:


5014757 CONNECTION PIPE \varnothing 6 mm
thread M10x1 mm



3348024 FLANGE VERTICAL \varnothing 12/10 mm
thread M20x1.5
for model PEL 22



3348023 HORIZONTAL FLANGE \varnothing 12/10 mm
thread M20x1.5
for model PEL 22



3348025 HORIZONTAL FLANGE CONICAL \varnothing 12/10 mm
thread M20x1.5
for model PEL 22



3348058 MAGNET PROTECTION NUT M8x1
thread M18x1 mm
for model PEL 20-21-22



3348059 MAGNET PROTECTION NUT M9x1
thread M18x1mm
for model PEL 20-21-22



3182009 MAGNETIC UNIT PEL BIG HEADED
 \varnothing head 15.5 mm - \varnothing end 14 mm - length 44 mm
for PEL tap model 22-24



3348037 OLIVE FOR PILOT PIPE \varnothing 6 mm
for model PEL 21-22-25




3020082 OLIVE FOR 12 mm \varnothing PIPE



3348036 OLIVE FOR 4 mm \varnothing PIPE
for model PEL 21-22



3348031 PIPE FITTING \varnothing 10 mm
thread M20x1.5
for model PEL 22





Suitable for:

3348032 PIPE FITTING \varnothing 12 mm
thread M20x1.5
for model PEL 22



3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



FIAMMA RST



Suitable for:


3348029 PIPE FITTING \varnothing 4 mm
thread M10x1
for model PEL 21-22




3348038 PIPE OLIVE \varnothing 10 mm
for model PEL 22



3348011 GAS TAP 23S/O
with pilot flame
with horizontal flange
inlet fitting M28x1.5mm
outlet connection M24x1.5mm
with flow regulator
thermocouple connection M9x1
D-shaped pin \varnothing 10x8 mm




3348060 CAP WITH PIN \varnothing 10x8 mm
pin length 25 mm
for model PEL 23



FIAMMA RST 91115.220.013


3348062 CAP WITH PIN \varnothing 10x8 mm
pin length 35 mm
for model PEL 23



5014757 CONNECTION PIPE \varnothing 6 mm
thread M10x1 mm



3348028 FLANGE VERTICAL \varnothing 12/16 mm
thread M24x1.5
for model PEL 23



3348027 HORIZONTAL FLANGE \varnothing 12/16 mm
thread M24x1.5 mm
for model PEL 23






Suitable for:


3348037 OLIVE FOR PILOT PIPE \varnothing 6 mm
for model PEL 21-22-25



3348033 PIPE FITTING \varnothing 12 mm
thread M24x1.5
for model PEL 23



3348035 PIPE FITTING \varnothing 20 mm
thread M28x1.5
for model PEL 23



3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



3348041 PIPE OLIVE \varnothing 16 mm
for model PEL 23



FIAMMA RST




Suitable for:


3348036 OLIVE FOR 4 mm \varnothing PIPE
for model PEL 21-22



3348034 PIPE FITTING \varnothing 16 mm
thread M24x1.5
for model PEL 23



3348029 PIPE FITTING \varnothing 4 mm
thread M10x1
for model PEL 21-22



3348040 PIPE OLIVE \varnothing 12 mm
for model PEL 23



3348042 PIPE OLIVE \varnothing 20 mm
for model PEL 23




3348013 GAS TAP 23S/V
 with pilot flame
 with vertical flange
 inlet fitting M28x1.5mm
 outlet connection M24x1.5mm
 with flow regulator
 thermocouple connection M10x1
 D-shaped pin \varnothing 10x8 mm



FIAMMA RST 91115.127.007


3348062 CAP WITH PIN \varnothing 10x8 mm
 pin length 35 mm
 for model PEL 23



3348060 CAP WITH PIN \varnothing 10x8 mm
 pin length 25 mm
 for model PEL 23



3348028 FLANGE VERTICAL \varnothing 12/16 mm
 thread M24x1.5
 for model PEL 23



5014757 CONNECTION PIPE \varnothing 6 mm
 thread M10x1 mm



3182010 MAGNETIC UNIT PEL
 \varnothing head 24 mm - \varnothing end 18 mm - length 59 mm
 thermocouple coupling M10x1
 for PEL tap model 23



3348027 HORIZONTAL FLANGE \varnothing 12/16 mm
 thread M24x1.5 mm
 for model PEL 23




3348036 OLIVE FOR 4 mm \varnothing PIPE
 for model PEL 21-22



3348037 OLIVE FOR PILOT PIPE \varnothing 6 mm
 for model PEL 21-22-25




3348033 PIPE FITTING \varnothing 12 mm
 thread M24x1.5
 for model PEL 23





Suitable for:

3348034 PIPE FITTING \varnothing 16 mm
thread M24x1.5
for model PEL 23




FIAMMA RST




Suitable for:

3348035 PIPE FITTING \varnothing 20 mm
thread M28x1.5
for model PEL 23



3348029 PIPE FITTING \varnothing 4 mm
thread M10x1
for model PEL 21-22



3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



3348040 PIPE OLIVE \varnothing 12 mm
for model PEL 23



3348041 PIPE OLIVE \varnothing 16 mm
for model PEL 23



3348042 PIPE OLIVE \varnothing 20 mm
for model PEL 23




Gas valves and accessories

3526131 EUROSIT VALVE FOR FRYER 110÷190°C
inlet \varnothing 3/8" F - outlet \varnothing 3/8" F
thermocouple connection M9x1
maximum gas inlet pressure 50 mbar
outlet pressure adjustment range
3÷18 mbar
ambient temperature 0÷80°C
capillary length 1050 mm
bulb \varnothing 4x200 mm



4056009 CAP FOR VALVE EUROSIT





Suitable for:

3526260 EUROSIT VALVE CAP



3526126 EUROSIT VALVE EXTENSION
D shaft \varnothing 10x8 mm



3526127 FLANGE FOR KNOB EXTENSION



3020084 NUT & OLIVE \varnothing 6 mm



3001111 PIEZO IGNITER EUROSIT
male faston \varnothing 2.4 mm



3526123 RUBBER PROTECTION FOR EUROSIT VALVE



FIAMMA RST

Suitable for:

3241435 EUROSIT VALVE EXTENSION
D shaft \varnothing 10x8 mm



3526677 EXTENSION FOR EUROSIT VALVE
D-shaped pin \varnothing 10x8 mm



3020083 NUT & OLIVE \varnothing 4 mm



3020082 OLIVE FOR 12 mm \varnothing PIPE



3020079 PIPE FITTING \varnothing 12 mm
thread \varnothing 3/8" F





Suitable for:

3523043 MINISIT SENSING ELEMENT 110÷190°C
capillary length 1050 mm
button bulb ø 14.4x26 mm



FIAMMA RST 91172.127.002

Suitable for:

3523042 MINISIT SENSING ELEMENT 50÷190°C
capillary length 1200 mm
bulb ø 5x95 mm



FIAMMA RST 91161.220.019

Heating elements

3455512 HEATING ELEMENT QUARTZ 250W 75V
length 420 mm - ø 12 mm
for Toaster (FIAMMA RST)



FIAMMA RST 4.0.075.1137

3455511 HEATING ELEMENT QUARTZ 330W 75V
length 420 mm - ø 12 mm
for Toaster (FIAMMA RST)



FIAMMA RST 4.0.075.1135

3455513 HEATING ELEMENT QUARTZ 450W 115V
length 420 mm - ø 12 mm
for Toaster (FIAMMA RST)



FIAMMA RST 4.0.074.1003

7107328 HEATING ELEMENT 1150W 240V
length 210 mm - width 215 mm
height 30 mm
for Panini grill electric (FIAMMA RST) - Series GR



FIAMMA RST 4.0.066.0083

3455514 HEATING ELEMENT 1300W 230V
length 430 mm - width 255 mm
connections ø 1/4"
for Salamander electric (FIAMMA RST) SEF450



FIAMMA RST 4.0.130.0007

3455515 HEATING ELEMENT 1300W 230V
length 630 mm - width 300 mm
connections ø 1/4"
for Salamander electric (FIAMMA RST) SEF650



FIAMMA RST 4.0.132.0005

3455521 HEATING ELEMENT 1300W 230V
length 465 mm - width 215 mm
for Bain-marie electric (FIAMMA RST)



FIAMMA RST 4.0.155.0003

3455518 HEATING ELEMENT 1350W 240V UPPER
length 200 mm - width 310 mm
height 26 mm
for Panini grill (FIAMMA RST) GR6



FIAMMA RST 4.0.069.0050



Suitable for:

3755569 HEATING ELEMENT 1500W 230V
length 330 mm - width 25 mm
height 220 mm - flange 33x31 mm



FIAMMA RST 91160.05.003

Suitable for:

3455516 HEATING ELEMENT 1700W 230V
length 610 mm - width 210 mm
connections \varnothing 1/4"
for Salamander electric (FIAMMA RST) SEF650



FIAMMA RST 4.0.132.0007

3455525 HEATING ELEMENT 1700W 230V LOWER
length 280 mm - width 105 mm
height 205 mm - connections \varnothing 1/4"
for Fryer electric (FIAMMA RST)




FIAMMA RST 4.0.089.1005

3455524 HEATING ELEMENT 1700W 230V UPPER
length 280 mm - width 70 mm
height 195 mm - connections \varnothing 1/4"
for Fryer electric (FIAMMA RST)



FIAMMA RST 4.0.089.1004

3455517 HEATING ELEMENT 1900W 240V LOWER
length 190 mm - width 335 mm
height 30 mm
for Panini grill (FIAMMA RST) GR6



FIAMMA RST 4.0.069.0045

5070224 HEATING ELEMENT 2300W 230V
length 425 mm - width 235 mm
connections \varnothing 1/4"
for Salamander electric (FIAMMA RST) SEF450



FIAMMA RST 4.0.130.0005

3455522 HEATING ELEMENT 3000W 230V
length 280 mm - width 180 mm
height 160 mm - connections \varnothing 1/4"
for Fryer electric (FIAMMA RST)




FIAMMA RST 4.0.085.1005

3455520 HEATING ELEMENT 3000W 230V LOWER
length 320 mm - width 145 mm
height 210 mm - connections \varnothing 1/4"
for Fryer electric (FIAMMA RST)



FIAMMA RST 4.0.091.0005

3455519 HEATING ELEMENT 3000W 230V UPPER
length 320 mm - width 115 mm
height 200 mm - connections \varnothing 1/4"
for Fryer electric (FIAMMA RST)



FIAMMA RST 4.0.091.0004

5065081 HEATING ELEMENT 3400W 230V
length 300 mm - width 155 mm
height 180 mm - connections \varnothing 1/4"
for Fryer electric (FIAMMA RST) FCF10 - FCF10+10
FF10 - FF10+10



FIAMMA RST 4.0.087.0005



Suitable for:

FIAMMA RST



345523 HEATING ELEMENT 3500W 230V
length 280 mm - width 180 mm
height 195 mm - connections \varnothing 1/4"
for Fryer electric (FIAMMA RST)



FIAMMA RST 4.0.087.1005

Suitable for:


5062408 HEATING ELEMENT 850W 240V
length 200 mm - width 215 mm
height 25 mm
for Panini grill electric (FIAMMA RST) - Series GR



FIAMMA RST 4.0.066.0084

Hinges, catches and accessories

3053007 LEFTHAND DOOR HINGE FOR OVEN
distance between holes 175 mm - overall length 205
height 160 mm



FIAMMA RST 91110.129.021

3053003 DOOR HINGE ROLL HOLDER
distance between holes 95 mm - overall length 118
height 23 mm



3053234 HINGE COVER
distance between holes 95 mm - size 124x20 mm



3053299 HINGE COVER
distance between holes 77 mm - size 129x26 mm



3053006 RIGHTHAND DOOR HINGE FOR OVEN
distance between holes 175 mm - overall length 205
height 160 mm



FIAMMA RST 91110.129.020

3053003 DOOR HINGE ROLL HOLDER
distance between holes 95 mm - overall length 118
height 23 mm



3053234 HINGE COVER
distance between holes 95 mm - size 124x20 mm



3053299 HINGE COVER
distance between holes 77 mm - size 129x26 mm



Ignitors

- 3001020 PIEZO IGNITER**
a \varnothing 18 mm hole is required for the assembly
faston M \varnothing 2.4 mm



FIAMMA RST 4.0.100.0070

- 5035512 WATERTIGHT PIEZO CAP**
of silicone rubber



- 3001120 PIEZO IGNITER**
for installation it is necessary a \varnothing 18 mm hole
male faston \varnothing 2.4 mm



FIAMMA RST 4.0.100.0070

Indicator lights

- 3221132 GREEN INDICATOR LAMP 230V**
head \varnothing 13.5 mm - hole \varnothing 10 mm - 120°C
universal application



FIAMMA RST 4.0.025.0130

- 3221008 GREEN LAMP RECEPTACLE**
head \varnothing 15 mm - hole \varnothing 12.5 mm
universal application



FIAMMA RST 91100.05.025

- 3221126 INDICATOR LAMP 24V**
head \varnothing 8 mm



- 3221097 NEUTRAL INDICATOR LAMP 220V**
head \varnothing 8 mm - 120°C





Suitable for:

FIAMMA RST



3221262 GREEN LAMP RECEPTACLE
head \varnothing 14.5 mm - hole \varnothing 12 mm



FIAMMA RST 91100.05.025

Suitable for:

3221095 ORANGE INDICATOR LAMP 230V
head \varnothing 13.5 mm - hole \varnothing 10 mm - 120°C
universal application



FIAMMA RST 4.0.025.0135

3221337 ORANGE INDICATOR LAMP 250V
head \varnothing 12 mm - hole \varnothing 9 mm - 125°C
wire connection length 200 mm
for Bain-marie (FIAMMA RST)
for Salamander (FIAMMA RST)
for Toaster (FIAMMA RST)



FIAMMA RST 4.0.085.0022

FIAMMA RST 4.0.085.0023

3221170 ORANGE INDICATOR LIGHT 230V
head \varnothing 10 mm - hole \varnothing 9 mm - 120°C



FIAMMA RST 4.0.085.0025

3221176 GREEN INDICATOR LAMP 230V
head \varnothing 10 mm - hole \varnothing 9 mm - 120°C



3221177 INDICATOR LAMP WHITE 230V
 \varnothing head 10 mm - \varnothing hole 9 mm - 120°C



Ironmongery (screws,nuts,washers)

1349504 NUT \varnothing 1/2" KEY 25x6 mm



FIAMMA RST 4.0.155.0015



Knobs

- 3444187 BLACK KNOB \varnothing 50 mm 50-500°C**
D-shaped pin \varnothing 6x4.6 mm
for EGO thermostat



FIAMMA RST 91040.48.034

- 3241197 BLACK KNOB 46x51 mm**
D-shaped hole 8x6.5 mm



FIAMMA RST 91140.05.010


- 3241195 KNOB RING NUT \varnothing 84 mm SILK-SCREEN PRINTE**



- 3241801 FASTENING RING - 10 PCS**



- 3241196 KNOB RING NUT \varnothing 84 mm SILK-SCREEN PRINTE**



- 3241234 GREY KNOB \varnothing 71 mm SILK-SCREEN PRINTED**
D shaft hole 10x8 mm



FIAMMA RST 91160.505.001

- 7109419 KNOB BLACK \varnothing 52 mm**
D-shaped hole 6x4.6 mm
for Fry top (FIAMMA RST)



FIAMMA RST 4.0.066.0101

Magnet groups

- 3182008 MAGNETIC UNIT SIT**
 \varnothing head 35 mm - \varnothing end 20 mm - length 47 mm
for valve SIT NOVASIT 820



FIAMMA RST 91116.127.005



Suitable for:

FIAMMA RST



Suitable for:

Microswitches

3803080 MICRO SWITCH 16A 250V
for Fryer (FIAMMA RST)



FIAMMA RST 4.0.085.0021

3240623 MICROSWITCH CHAIN 4 BURNERS
0.2A 250V - max 140°C



FIAMMA RST 91140.129.061


Pilot burners and accessories

3020147 PILOT BURNER
supplied without nozzle, fittings



FIAMMA RST 91140.05.009

3020441 COUPLING FOR HOSE \varnothing 7 mm
thread M11x1 mm



3020200 FITTING FOR THERMOCOUPLE \varnothing 6.5 mm
thread M10x1



3020541 NOZZLE FOR PILOT BURNER 0.35 mm



3345021 OLIVE FOR PIPE \varnothing 4 mm




3020111 OLIVE FOR 4 mm \varnothing PIPE



3020423 PILOT BURNER EXTENSION 60 mm
thread M10x1 mm



3020557 PILOT JET \varnothing 0.20 mm



3020157 PILOT JET \varnothing 0.25 mm



3020040 PILOT JET \varnothing 0.30 mm




FIAMMA RST 91140.220.044



Suitable for:

3020041 PILOT JET \varnothing 0.41 mm



**3020077 PIPE FITTING \varnothing 4 mm
thread M10x1**



3020440 PIPE OLIVE \varnothing 7 mm



3020139 PILOT BURNER CAP



FIAMMA RST 91110.310.001

3020037 THREE-FLAME PRINTED PILOT BURNER SIT
without sparking plug, gas nozzle and gasket
thermocouple fitting included



FIAMMA RST 91161.220.032

3020085 FITTING FOR SPARKING PLUG FIXING M10x1mm



FIAMMA RST



Suitable for:


3020187 PILOT NOZZLE \varnothing 0.51 mm



**3348029 PIPE FITTING \varnothing 4 mm
thread M10x1
for model PEL 21-22**



3020157 PILOT JET \varnothing 0.25 mm



FIAMMA RST 91140.220.044

**5014757 CONNECTION PIPE \varnothing 6 mm
thread M10x1 mm**




**3020200 FITTING FOR THERMOCOUPLE \varnothing 6.5 mm
thread M10x1**





Suitable for:

3020541 NOZZLE FOR PILOT BURNER 0.35 mm



3348036 OLIVE FOR 4 mm ø PIPE
for model PEL 21-22



3020086 PILOT GASKET




3020157 PILOT JET ø 0.25 mm



FIAMMA RST 91140.220.044

3020041 PILOT JET ø 0.41 mm



3020077 PIPE FITTING ø 4 mm
thread M10x1



FIAMMA RST

Suitable for:


3020111 OLIVE FOR 4 mm ø PIPE



3020112 OLIVE FOR 6 mm ø PIPE



3020557 PILOT JET ø 0.20 mm



3020040 PILOT JET ø 0.30 mm



3020187 PILOT NOZZLE ø 0.51 mm



3348029 PIPE FITTING ø 4 mm
thread M10x1
for model PEL 21-22





Suitable for:

3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



3001003 ROUND SPARKING PLUG \varnothing 7x44 mm
male faston M4x1 mm
total length 65 mm



3020124 SPARKING PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 58 mm



3020038 THREE-FLAME PRINTED PILOT BURNER SIT
without sparking plug, gas nozzle and gasket
thermocouple fitting included



FIAMMA RST 91121.127.001

3020085 FITTING FOR SPARKING PLUG FIXING M10x1mm



3020541 NOZZLE FOR PILOT BURNER 0.35 mm



FIAMMA RST



Suitable for:

3020294 ROUND IGNITION ELECTRODE \varnothing 7x44 mm
M faston M4x1 mm
overall length 67 mm



3020060 SPARKING PLUG ROUND \varnothing 7x44 mm
faston M 4x1 mm
overall length 82 mm
model CB505/021 Junkers
for model P502F



3020365 SPARKING PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 52 mm



5014757 CONNECTION PIPE \varnothing 6 mm
thread M10x1 mm



3020200 FITTING FOR THERMOCOUPLE \varnothing 6.5 mm
thread M10x1



3020111 OLIVE FOR 4 mm \varnothing PIPE





Suitable for:


3348036 OLIVE FOR 4 mm \varnothing PIPE
for model PEL 21-22



3020086 PILOT GASKET



3020157 PILOT JET \varnothing 0.25 mm



FIAMMA RST 91140.220.044

3020041 PILOT JET \varnothing 0.41 mm



3020077 PIPE FITTING \varnothing 4 mm
thread M10x1



3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



FIAMMA RST



Suitable for:

3020112 OLIVE FOR 6 mm \varnothing PIPE



3020557 PILOT JET \varnothing 0.20 mm




3020040 PILOT JET \varnothing 0.30 mm



3020187 PILOT NOZZLE \varnothing 0.51 mm



3348029 PIPE FITTING \varnothing 4 mm
thread M10x1
for model PEL 21-22



3020294 ROUND IGNITION ELECTRODE \varnothing 7x44 mm
M faston M4x1 mm
overall length 67 mm





Suitable for:

3001003 ROUND SPARKING PLUG \varnothing 7x44 mm
male faston M4x1 mm
total length 65 mm



3020124 SPARKING PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 58 mm



FIAMMA RST



Suitable for:

3020060 SPARKING PLUG ROUND \varnothing 7x44 mm
faston M 4x1 mm
overall length 82 mm
model CB505/021 Junkers
for model P502F



3020365 SPARKING PLUG ROUND \varnothing 7x44 mm
connection \varnothing 2.4 mm
overall length 52 mm



Probes

3445109 PROBE TCJ VETROTEX 3000 mm
2-wire probe temperature range 0+600°C
temperature cable max 350°C
error limit $\pm 0.75\%$ below 0°C
response time 30 sec
bulb \varnothing 6x100 mm



FIAMMA RST 91100.220.061

Reamers

3003002 REAMER FOR NOZZLES 12 PCS
12 pieces package with case
with mandrel
diameter range from 0.6 to 1.9 mm



3003001 REAMER FOR JETS 6 PIECES
6 pieces set
diameter range 0.6-0.8-1-1.3-1.6-2 mm



FIAMMA RST 91110.127.029



Suitable for:

FIAMMA RST



Suitable for:

Relays

3351021 POWER RELAY FINDER 62.82.8.230.0000
230V 50/60Hz
2 exchange contacts 16A



FIAMMA RST 5.0.096.3324

Spark generators

3181002 SPARK GENERATOR 2 OUTLETS
220/240V 50/60Hz



FIAMMA RST 91116.220.005

Sparking and detection plugs

3020475 SPARKING PLUG ROUND \varnothing 7x43 mm
with cable 255 mm
for Bain-marie gas (FIAMMA RST)



FIAMMA RST 4.0.100.0075

Springs

5062404 SPRING \varnothing 27x105 mm
for Panini grill electric (FIAMMA RST) - Series GR



FIAMMA RST 4.0.066.0020



Switches

1319902 BLACK BIPOLAR SWITCH 16A 250V

with indicator led lamp
mounting hole 22x30 mm
for Fryer (FIAMMA RST)



FIAMMA RST 90440.127.061

3319920 BLACK TWO-POLE SWITCH 16A 250V



FIAMMA RST 4.0.000.0513

3319923 BLACK/RED CAM



3319646 GREEN/ORANGE CAM



1319395 COMPLETE MONOPOLAR SWITCH 10A 250V

for coffee delivery
for Toaster (FIAMMA RST)



FIAMMA RST 4.0.000.0510

3319468 SWITCH 1-POLE BLACK 16A 250V

16(4)A 250V
silk-screen printing 0 - I
max. temperature 120°C
mounting hole 11x30 mm



FIAMMA RST 90490.317.055

3319780 BLOCK CONNECTION WHITE 30x22 mm





Suitable for:

3319779 BLOCK CONNECTIONS BLACK 30x22 mm



FIAMMA RST



Suitable for:

3319781 CONNECTION BLOCK BLACK 11x30 mm



1319936 SWITCH COVER

external dimensions 36x18 mm
for switch with mounting hole 30x11 mm



3319512 SWITCH 2-POLE ORANGE 16A 250V

16(4)A 250V - with indicator lamp
silk-screen printing 0 - I
max temperature 120°C
mounting hole 22x30 mm
for Bain-marie (FIAMMA RST)



FIAMMA RST 4.0.085.0018

FIAMMA RST 4.2.000.9234

3319780 BLOCK CONNECTION WHITE 30x22 mm



3319779 BLOCK CONNECTIONS BLACK 30x22 mm



3319782 FRAME SAFETY 2 SIDES BLACK 30x22 mm



3319783 FRAME SAFETY 4 SIDES BLACK 30x22 mm



3319501 PUSH-BUTTON PROTECTION CAP
external dimensions 29x36 mm
for switches with mounting hole 22x30 mm





Suitable for:

Suitable for:

3319016 SWITCH 2-POLE RED 16A 250V
 16(4)A 250V - max. temperature 120°C
 with indicator lamp - silk screen printing 0 - I
 mounting hole 22x30 mm

3319780 BLOCK CONNECTION WHITE 30x22 mm



FIAMMA RST 4.2.000.9236

3319779 BLOCK CONNECTIONS BLACK 30x22 mm

3319782 FRAME SAFETY 2 SIDES BLACK 30x22 mm



3319783 FRAME SAFETY 4 SIDES BLACK 30x22 mm

3319501 PUSH-BUTTON PROTECTION CAP
 external dimensions 29x36 mm
 for switches with mounting hole 22x30 mm



Terminal blocks

3247009 6-POLE TERMINAL BLOCK FV122/B 40A 600V
 for cable max 6 mm²
 operating temperature 150°C
 nominal voltage 450 V



FIAMMA RST 90805.08.067

Thermocouples and accessories

3440186 THERMOCOUPLE M8x1 22 cm JOINT M8x1
 for Bain-marie gas (FIAMMA RST)

3440187 THERMOCOUPLE M8x1 32 cm JOINT M8x1
 for Bain-marie gas (FIAMMA RST)



FIAMMA RST 4.0.100.0055

FIAMMA RST 4.0.153.0001



Suitable for:

FIAMMA RST



Suitable for:

3440087 THERMOCOUPLE M9x1 60 cm COUPLING M6x0.75



FIAMMA RST 91140.220.010

Thermostatic gas valves

3345006 THERMOSTATIC TAP 24ST
Adjustment temperature 120-320°C
connections M20x1.5 mm
thermocouple connection M9x1
bulb \varnothing 6x100 mm
capillary length 1200 mm
D-shaped pin \varnothing 10x8 mm



FIAMMA RST 91114.220.006

3348037 OLIVE FOR PILOT PIPE \varnothing 6 mm
for model PEL 21-22-25



3348036 OLIVE FOR 4 mm \varnothing PIPE
for model PEL 21-22



3348043 PIPE FITTING \varnothing 10 mm
thread M16x1.5
for model PEL 20-21



5014757 CONNECTION PIPE \varnothing 6 mm
thread M10x1 mm




3020082 OLIVE FOR 12 mm \varnothing PIPE



3348031 PIPE FITTING \varnothing 10 mm
thread M20x1.5
for model PEL 22



3348032 PIPE FITTING \varnothing 12 mm
thread M20x1.5
for model PEL 22





Suitable for:

3348029 PIPE FITTING \varnothing 4 mm
thread M10x1
for model PEL 21-22



3348038 PIPE OLIVE \varnothing 10 mm
for model PEL 22



FIAMMA RST



Suitable for:

3020078 PIPE FITTING \varnothing 6 mm
thread M10x1



3348044 PIPE OLIVE \varnothing 10 mm
for model PEL 20 - 21




Thermostats

3444224 BULB HOLDING CLIP
for heating element thermostat
for pipe \varnothing 8 mm - for bulb \varnothing 6 mm



FIAMMA RST 4.0.085.0016

3744157 FASTENING CLIP BULB \varnothing 7 mm
for heating element thermostat
for Fryer (FIAMMA RST)



FIAMMA RST 4.0.085.0017

3444009 KNOB BLACK \varnothing 41 mm 0-120°C
D-shaped hole 6x4.6 mm
for thermostat IMIT



FIAMMA RST 90914.12.097

3444628 SINGLE-PHASE THERMOSTAT 50-250°C
D-shaped pin \varnothing 6x4.6 mm
capillary length 800 mm
bulb \varnothing 3x180 mm
for Panini grill (FIAMMA RST) GR6.1



FIAMMA RST 4.0.066.0114

5065082 THERMOSTAT SINGLE PHASE 235°C
with manual reset
capillary covered length 1030 mm
bulb \varnothing 5x68 mm
for Fryer electric (FIAMMA RST) - Series FCF
Series FF



FIAMMA RST 4.0.085.0011

3744159 THERMOSTAT SINGLE PHASE 30-85°C
D-shaped pin \varnothing 6x4.6 mm
capillary covered length 840 mm
bulb \varnothing 6x94 mm
for Bain-marie (FIAMMA RST)



FIAMMA RST 4.0.160.0022




Suitable for:

FIAMMA RST




3744156 THERMOSTAT SINGLE PHASE 50-180°C
D-shaped pin \varnothing 6x4.6 mm
capillary covered length 625 mm - 16A 400V
bulb \varnothing 5x90 mm
for Fryer (FIAMMA RST)



FIAMMA RST 4.0.085.0009

3444005 THERMOSTAT SINGLE-PHASE TR2 0-120°C
D-shaped pin \varnothing 6x4.6 mm
capillary length 1500 mm - 15A 250V
bulb \varnothing 6.5x95 mm



FIAMMA RST 90914.12.025


Timers

3446137 TIMER 15 MINUTES M2
mechanical movement with balance wheel
manually set mechanical timer
manually set cycle 15 minutes
bipolar with contact capacity 16(4)A 250V
max temperature 125°C
D-shaped pin \varnothing 6x4.6 mm
for all models
for Toaster (FIAMMA RST)




FIAMMA RST 4.0.075.0002

3241173 BLACK KNOB \varnothing 44 mm
D shaft hole 6x4.6 mm




















3241174 BLACK KNOB \varnothing 44 mm
D shaft hole 6x4.6 mm



The data herewith contained may change without notice and LF SpA cannot be held responsible for possible errors stated or resulting by the use of this document. All rights reserved. No part of this publication may be reproduced without written permission by LF SpA.



Distributing Components, Spare Parts & Accessories in original quality worldwide

-
-  **LF SpA HEADQUARTERS**
via Voltri, 80 - 47522 Cesena (FC) ITALY
Tel. +39 0547 34 11 11 - Fax +39 0547 34 11 10
www.lfcomb724.it - www.lfcomb724.mobi - info@lfcomb.it
Export Dept.: Tel. +39 0547 34 11 50 - Fax: +39 0547 34 11 55
www.lfspareparts724.com - www.lfspareparts724.mobi
export@lfspareparts.com
 -  **OOO LF RUSSIAN FEDERATION**
Ul. Anatoliya Zhivova, 8 - office 1 - 123100 Moscow
Tel. +7 499 259 85 75
Fax +7 495 725 26 53
www.lfspareparts724.ru
www.lfspareparts724.mobi
info@lfspareparts.ru
 -  **EPGC Sas FRANCE**
13, Rue des Forts - 59960 Neuville en Ferrain
Tel. +33 (0)3 20 25 06 21
Fax +33 (0)3 20 25 34 12
www.epgc.com
www.epgc724.mobi
epgc@epgc.com
 -  **LF Repuestos Horeca S.L.U. SPAIN**
Calle Ciudad Real, 10 - 45517 Escalonilla - Toledo
Tel. +34 91 477 91 00
Fax +34 91 477 90 81
www.lfrepuestos-horeca724.es
www.lfrepuestos724.mobi
info@lfrepuestos.es
 -  **LF GmbH GERMANY**
Junkersstrasse, 1 - D-82178 Puchheim - München
Tel. +49 89 89 45 78 66
Fax +49 89 89 45 78 88
www.lfersatzteile724.de
www.lfersatzteile724.mobi
info@lfersatzteile.de
 -  **LF SpA Cesena (IT) Swiss Branch Steinhausen SWITZERLAND**
Sennweidstrasse, 45 - CH-6312 Steinhausen
Tel. +41 (0)41 760 15 80-1
Fax +41 (0)41 760 15 85
www.lfersatzteile724.ch
www.lfersatzteilech724.mobi
info@lfersatzteile.ch
 -  **LF China REPUBLIC OF CHINA**
Room 403, No.2, Huadu Mansion, Lane 422, Huanghua Rd.
Minhang Dist. - 201103 Shanghai
Tel. +86 (0)21 33 53 66 31
Fax +86 (0)21 33 53 66 32
www.lfspareparts724.com
www.lfspareparts724.mobi
china@lfspareparts.com
 -  **LF Spare Parts Ltd. UNITED KINGDOM**
A10a Lakeside Business Park, Broadway Lane
South Cerney, Gloucestershire GL7 5XL
Tel. +44 (0)1285 86 16 25
Fax +44 (0)1285 86 39 49
www.lfspareparts724.co.uk
www.lfspareparts724.mobi
info@lfspareparts.co.uk
-
-  **AUSTRALIA AND NEW ZEALAND**
www.lfspareparts724.com
andrea.calvio@lfspareparts.com
 -  **DENMARK**
www.lfspareparts724.dk
michael.lenth@lfspareparts.com
 -  **AUSTRIA**
www.lfspareparts724.at
ludwig.neier@lfersatzteile.at
 -  **SOUTH KOREA**
www.lfspareparts724.com
fabio.doni@lfspareparts.com
 -  **BALKAN COUNTRIES**
www.lfspareparts724.com
matija.ramov@lfspareparts.com
 -  **TURKEY**
www.lfyedekparca724.com
basar.ergun@lfyedekparca.com
 -  **BALTIC COUNTRIES**
www.lfspareparts724.com
inara.silina@lfspareparts.com
 -  **USA AND CANADA**
www.lfspareparts724.us
sauro.dallaglio@lfspareparts.us
howard.truitt@lfspareparts.us
 -  **CENTRAL AND EASTERN EUROPE**
www.lfspareparts724.cz
jiri.kremla@lfspareparts.cz