

Spare parts for:

Cooking equipment



Suitable for:





This catalogue is automatically generated. Therefore, the sequence of the items might not be always shown at best. Updates will be issued in case of additions and/or amendments. Suitable **universal spare parts** may not be included







				Group
Suitable for:	Electric	Suitable for:	tes	
3311168	ELECTRIC HOT PLATE ø 165 mm 1200W 230V faston electric connections complete with energy adjuster for glass-ceramic cooking top	3311096	ELECTRIC HOT PLATE ø 180 mm 2000W 230V terminal block electric connections with STAINLESS steel edge for electric cooking top	
HAKA		HAKA 9016		
3311169	ELECTRIC HOT PLATE ø 200 mm 1700W 230V faston electric connections complete with energy adjuster for glass-ceramic cooking top	3311100	ELECTRIC HOT PLATE ø 220 mm 2600W 230V terminal block electric connections with STAINLESS steel edge for electric cooking top	
НАКА		HAKA 9017		
3311088	ELECTRIC HOT PLATE ø 230 mm 2100W 230V faston electric connections complete with energy regulation			
НАКА				
	Energy	regulate	ors	
3350026	ENERGY ADJUSTER contact capacity 230V 13A - max temperature 125°C D-shaped pin ø 6x4.6 mm double rotation direction for PYROCERAM. TOPS-SALAMANDERS-POTATO WARMERS	3350035	ENERGY ADJUSTER contact capacity 230V 13A max temperature 125°C D-shaped pin ø 6x4.6 mm	
НАКА		НАКА		







	Hea	ating elemer	nts	
355829	CERAMIC HEATING ELEMENT 650W 230V length 245 mm - width 60 mm	3355736	HEATING ELEMENT 1500W 230V length 295 mm - width 40 mm height 25 mm - fittings M14x1 mm operating ambient: immersion for Bain-marie electric (HAKA)	
HAKA 9187		HAKA 9007		
	Incandescen	t lamps and	neon lamps	
3221041	OVEN LAMP E14 15W 230V max temperature 300°C for OVEN – PIZZA OVEN			
HAKA 9064				
	Lamp recep	otacles and s	pare parts	
3221233	GLASS FOR OVEN LAMP RECEPTACLE ø 42 mm thread ø 33 mm - overall height 26 mm	3221350	LAMP RECEPTACLE WITH LAMP E14 15W 230V lamp glass ø 42 mm	
			mounting hole ø 38 mm max temperature 300°C	
			mounting hole ø 38 mm	
HAKA 9058	tillead & 33 mill - overall neight 20 mill	HAKA 9063	mounting hole ø 38 mm	
HAKA 9058		HAKA 9063	mounting hole ø 38 mm max temperature 300°C	
			mounting hole ø 38 mm max temperature 300°C	
нака 9058 3057017	Ender Example 2 Example 2 Exam	otary switche	mounting hole ø 38 mm max temperature 300°C For the second secon	







Suitable for:

3057092 SELECTOR SWITCH 0-6 POSITIONS contact capacity 16A 250V - max 150°C

D-shaft ø 6x4.6 mm



HAKA 300004

Thermostats

3444076 THREE-PHASE THERMOSTAT 30-110°C

D-shaped pin ø 6x4.6 mm covered capillary length 1200 mm - 10A 400V bulb ø 6x130 mm



3444561 TH

HAKA 9044

44561 THREE-PHASE THERMOSTAT 50-300°C

D-shaped pin ø 6x4.6 mm covered capillary length 1740 mm - 16A 230V bulb ø 6x80 mm



HAKA 9041

3444166 THREE-PHASE THERMOSTAT 95-180°C

D-shaped pin ø 6x4.6 mm covered capillary length 1800 mm - 10A 400V bulb ø 6x135 mm - with adapter nipple bland M9x1 with complete tank joint M12x1



HAKA 9042

The data herewith contained may change without notice and LF SpA cannot be held responsible for possible errors stated or resulting by the use of this document. All rights reserved. No part of this publication may be reproduced without written permission by LF SpA.



Distributing Components, Spare Parts & Accessories in original quality worldwide

