




Spare parts for:

## Cooking equipment



Suitable for:

# ROSINOX



This catalogue is automatically generated.  
Therefore, the sequence of the items might  
not be always shown at best.

Updates will be issued in case of additions  
and/or amendments.

*Suitable **universal spare parts** may not be included*





Suitable for:


# ROSINOX

Suitable for:



## Alarms

**3397302 ALARM BELL 220V**



ROSINOX RX94027794

## Ball valves and accessories

**5028318 BALL VALVE  $\varnothing$  1"FF**



ROSINOX RX94812667

**5009882 DRAIN TAP  $\varnothing$  3/4" F**  
outlet  $\varnothing$  internal 22 mm



ROSINOX RX94806742

**3526632 GAS/WATER BALLCOCK VALVE  $\varnothing$  3/4" FF**  
heavy series with PN 40 total passage  
DIN - DVGW approved  
aluminium throttle



ROSINOX RX94032687

ROSINOX RX94812688


**3359535 2-WAY BALL TAP**  
coupling  $\varnothing$  1/2" FF = 15/21  
with brass case  
operating pressure 20 bar



ROSINOX RX94020443

## Bearings

**9063012 BEARING 6004 DDU NSK**  
external  $\varnothing$  42mm - internal  $\varnothing$  20mm - thickness 12mm



ROSINOX RX94008067

## Burners, flame spreaders and accessories

**3025168 BURNER  $\varnothing$  75 mm 3.5 KW**  
for Kitchen gas (ROSINOX) SI766E  
for Pot stove gas (ROSINOX) SI766E



ROSINOX RX94800125

**3025171 BURNER  $\varnothing$  95 mm 5.5Kw**  
for Kitchen gas (ROSINOX) SI766E  
for Pot stove (ROSINOX) SI766E



ROSINOX RX94800166



# ROSINOX



Suitable for:

**3025713 BURNER ASSEMBLY MOUNTING DISTANCE 325 mm**  
with central flame  
15000-20000 Kcal/h  
height 80 mm -  $\varnothing$  200 mm - pipe  $\varnothing$  34 mm



ROSINOX RX94008463

Suitable for:

**3025811 BURNER BASE  $\varnothing$  100 mm 7kW**  
for Pot stove gas (ROSINOX)  
since 1/02/03




ROSINOX RX9404421

**3025810 BURNER BASE  $\varnothing$  120 mm 10kW**  
for Pot stove gas (ROSINOX)  
since 1/02/03



ROSINOX RX9404422

**3025179 BURNER RING  $\varnothing$  90 mm**



ROSINOX RX94805595

**3025627 FLAME SPREADER  $\varnothing$  100 mm**




ROSINOX RX9404419

**3025613 FLAME SPREADER  $\varnothing$  120 mm**



ROSINOX RX24180598

**3025809 FLAME SPREADER  $\varnothing$  120 mm**  
for Pot stove gas (ROSINOX)  
since 1/02/03



ROSINOX RX9404420

**3025810 BURNER BASE  $\varnothing$  120 mm 10kW**  
for Pot stove gas (ROSINOX)  
since 1/02/03



ROSINOX RX9404422

**3025808 VENTURI 100 mm 4.5kW**  
inlet  $\varnothing$  3/8" - height 45 mm  
for Pot stove gas (ROSINOX)  
since 1/02/03



ROSINOX RX9404469



Suitable for:

**3025169 FLAME SPREADER  $\varnothing$  75 mm 4.3Kw**  
for Kitchen gas (ROSINOX) SI766E  
for Pot stove gas (ROSINOX) SI766E



ROSINOX RX94800182

Suitable for:

**3025176 FLAME SPREADER  $\varnothing$  80 mm**



ROSINOX RX94805553

**3025172 FLAME SPREADER 6.4Kw  $\varnothing$  95 mm**  
for Kitchen gas (ROSINOX) SI766E  
for Kitchen (ROSINOX) SI766E



ROSINOX RX94800174

**3025679 GAS BURNER SUPPORT GR5  $\varnothing$  27 mm**



ROSINOX RX94007267

**3025312 SPARKING PLUG SUPPORT**  
for burners  $\varnothing$  75-95 mm



ROSINOX RX94806049

**3025313 THERMOCOUPLE SUPPORT**  
for burners  $\varnothing$  75-95 mm



ROSINOX RX94806411

**3025170 VENTURI F/FLAME SPREADER 75 mm 3.5Kw**  
for Kitchen gas (ROSINOX) SI766E  
for Kitchen gas (ROSINOX) SI766E



ROSINOX RX94806841

**3025173 VENTURI F/FLAME SPREADER 95 mm 5.5Kw**  
for Kitchen gas (ROSINOX) SI766E  
for Kitchen gas (ROSINOX) SI766E



ROSINOX RX94806437

**3025807 VENTURI FOR BURNER 7-10kW**  
mounting distance 180 mm - lateral outlet  $\varnothing$  3/8"  
pipe fixing - internal  $\varnothing$  35 mm  
for Pot stove gas (ROSINOX)  
since 1/02/03



ROSINOX RX94044423

**3025808 VENTURI 100 mm 4.5kW**  
inlet  $\varnothing$  3/8" - height 45 mm  
for Pot stove gas (ROSINOX)  
since 1/02/03



ROSINOX RX94044469





## Cables for piezo igniters

**3001016 IGNITION LEAD 1000 mm**  
with faston  $\varnothing$  2.4 mm for ignition  
with faston  $\varnothing$  4 mm for electrode



ROSINOX RX94805074

ROSINOX RX94805694

**5017976 IGNITION LEAD 1700 mm**  
with faston  $\varnothing$  2.4 mm for ignition  
with faston  $\varnothing$  4 mm for electrode



ROSINOX RX94805199

## Capacitors, electrical

**3068019 CAPACITOR  $\mu$ F 12.5 450V 50/60Hz**  
operating temperature  $-25+85^{\circ}\text{C}$   
in compliance with EEC 93/68 and 92/31 regulations



ROSINOX RX94814010

**3068008 CAPACITOR  $\mu$ F 5 450V 50/60Hz**  
operating temperature  $-25+85^{\circ}\text{C}$   
in compliance with EEC 93/68 and EEC 92/31 regulat



ROSINOX RX94801305

## Castors, rollers and accessories

**3738016 SWIVELLING WHEEL**  
with STAINLESS STEEL supports  
dimension  $\varnothing$  100x32 mm - load capacity 150 Kg  
pin hole  $\varnothing$  13 mm



ROSINOX RX94051265

**3738017 SWIVELLING WHEEL WITH BRAKE**  
with STAINLESS STEEL supports  
dimension  $\varnothing$  100x30 mm - load capacity 150 Kg  
pin hole  $\varnothing$  12 mm



ROSINOX RX94051273

## Contactors

**3397402 AEG MOTOR OVERLOAD CUTOUT Mbs25 50/60Hz**  
1.1Kw /  $1.6 \div 2.5\text{A}$   
3 normally open contacts



ROSINOX RX94810904

**3397405 AEG MOTOR OVERLOAD CUTOUT Mbs25 50/60Hz**  
1.5Kw /  $2.5 \div 4\text{A}$   
3 normally open contacts



ROSINOX RX94810902



Suitable for:

# ROSINOX



Suitable for:

**3351209 CONTACTOR AEG LS05 9A 230V 4Kw**  
 coil 230V 50/60Hz  
 3 normally open contacts  
 1 normally closed auxiliary contact



ROSINOX RX94804408

ROSINOX RX94813830

**3351221 CONTACTOR AEG LS15K 32A 230V 16Kw**  
 coil 230V 50/60Hz  
 3 normally open contacts  
 no auxiliary contact



ROSINOX RX27400282

**3351222 CONTACTOR AEG LS22K 50A 230V 22Kw**  
 coil 230V 50/60Hz  
 3 normally open contacts  
 no auxiliary contact



ROSINOX RX27400290

**3351223 CONTACTOR AEG LS30K 65A 230V 30Kw**  
 coil 230V 50/60Hz  
 3 normally open contacts  
 no auxiliary contact




ROSINOX RX27400308

**3351212 CONTACTOR AEG LS4K 9A 230V 4Kw**  
 coil 230V 50/60Hz  
 3 normally open contacts  
 1 normally open auxiliary contact



ROSINOX RX27400324

**3446582 CONTACTOR LOVATO BF1810A**  
 coil 18A 230V 50/60Hz 7.5Kw  
 3 normally open contacts  
 1 normally open auxiliary contact



ROSINOX RX94810801

**3446214 CONTACTOR LOVATO BG09T4A**  
 4KW 400V 9A - 4 normally open contacts  
 coil 230V 50/60Hz



ROSINOX RX94807062

**3454066 CONTACTOR SCHNEIDER LC1D25P7**  
 25A 400V 11Kw - coil 230V 50/60Hz  
 3 normally open contacts  
 1 normally open auxiliary contact  
 1 normally closed auxiliary contact  
 for Bratt pan electric (ROSINOX) MBM80E



ROSINOX RX94019155



## Cooking baskets and accessories

- 3055282 PASTA COOKER BASKET 280x135x160 mm**  
made of stainless steel



ROSINOX RX94812611

## Drain assembly

- 3316150 DRAIN ASSEMBLY  $\varnothing$  3/4"**  
with nut and gasket  
external  $\varnothing$  38 mm - internal  $\varnothing$  20 mm  
connections  $\varnothing$  26 mm



ROSINOX RX94806775

## Drain taps and accessories

- 3356116 DRAIN TAP  $\varnothing$  1"1/2"**  
fixed connection  $\varnothing$  1"1/2"F - folding handle  
for Boiling pan (ROSINOX)



ROSINOX RX94020237


## Electric hot plates

- 3311092 ELECTRIC HOT PLATE  $\varnothing$  145 mm 1500W 230V**  
terminal block electric connections  
with STAINLESS steel edge  
for electric cooking top



ROSINOX

- 3311168 ELECTRIC HOT PLATE  $\varnothing$  165 mm 1200W 230V**  
faston electric connections  
complete with energy adjuster  
for glass-ceramic cooking top



ROSINOX RX94806171



Suitable for:

# ROSINOX



**3311096 ELECTRIC HOT PLATE ø 180 mm 2000W 230V**  
terminal block electric connections  
with STAINLESS steel edge  
for electric cooking top



ROSINOX RX94012804


Suitable for:

**3311169 ELECTRIC HOT PLATE ø 200 mm 1700W 230V**  
faston electric connections  
complete with energy adjuster  
for glass-ceramic cooking top




ROSINOX RX94806163

**3311100 ELECTRIC HOT PLATE ø 220 mm 2600W 230V**  
terminal block electric connections  
with STAINLESS steel edge  
for electric cooking top




ROSINOX RX94012796

**3311101 ELECTRIC HOT PLATE ø 220 mm 2600W 400V**  
terminal block electric connections  
with STAINLESS steel edge  
for electric cooking top




ROSINOX

**3311089 ELECTRIC HOT PLATE ø 300 mm 3500W 230V**  
terminal block electric connections  
with STAINLESS steel edge



ROSINOX RX94012770

**3311078 ELECTRIC HOT PLATE ø 300 mm 3500W 400V**  
terminal block electric connections  
with STAINLESS steel edge  
for electric cooking top



ROSINOX

**3311053 ELECTRIC HOT PLATE 2600W 230V**  
dimensions 220x220 mm  
terminal block electric connections  
with STAINLESS steel edge  
for electric cooking top



ROSINOX RX94806866



## Electrical gas valves and accessories

**3526285 COIL mV**  
for LPG GAS  
for VALVE GAS UNITROL 7000



ROSINOX

**3526098 COIL 220V**  
for VALVE 820 NOVA-824 NOVASIT-822 NOVA-826 NOVA




ROSINOX 27440130

**3526090 ELETTSIT VALVE  $\varnothing$  3/4"FF**  
inlet  $\varnothing$  3/4" F - outlet  $\varnothing$  3/4" F  
thermocouple connection M9x1  
maximum gas inlet pressure 50 mbar  
pressure adjustment range  
3 ÷ 18 mbar  
ambient temperature 0 ÷ 60°C  
power supply 230V 50Hz  
long buttons  
pilot connection and LATERAL thermocouple



ROSINOX RX94024965

**3523073 GAS VALVE UNITROL U7000ER-240-S7CL/S**  
inlet  $\varnothing$  3/4" F - outlet  $\varnothing$  3/4" F  
thermocouple connection 11/32"  
NATURAL GAS pressure switch 6.7"W.C.  
power supply 220/240Vac 50/60Hz




ROSINOX

**3523076 GAS VALVE UNITROL 7000BER-S7CL**  
inlet  $\varnothing$  3/4" F - outlet  $\varnothing$  3/4" F  
thermocouple connection 11/32"  
NATURAL GAS pressure switch 6.7"W.C.  
slow opening  
supply 12Vdc/24Vac 50/60Hz



ROSINOX

**3523079 GAS VALVE UNITROL 7000BGO-S7B**  
inlet  $\varnothing$  3/4" F - outlet  $\varnothing$  3/4" F  
thermocouple connection 11/32"  
without pressure regulator




ROSINOX

**3440128 THERMOPILE  $\varnothing$  9x65 mm**  
250 ÷ 750mV  
cable length 900 mm - with fitting M9X1  
with supply fixing M10x1  
per VALVOLA GAS UNITROL 7000



ROSINOX RX24802365

**3523074 UNITROL GAS VALVE 7000BMV-S7CL**  
inlet  $\varnothing$  3/4" F - outlet  $\varnothing$  3/4" F  
without pressure regulator  
power supply 350mV through THERMOPILE



ROSINOX RX24867038





Suitable for:

**3523082 VALVE MICROSWITCH**  
length 415 mm  
for GAS VALVE UNITROL 7000 BER



ROSINOX

Suitable for:

**3526096 VALVE MICROSWITCH**  
maximum load 0.2 A  
for VALVE ELETTROSIT-820 NOVA-824 NOVASIT



ROSINOX RX94034683


**3526079 VALVE 820 NOVA  $\varnothing$  1/2"FF**  
inlet  $\varnothing$  1/2" F - outlet  $\varnothing$  1/2" F  
thermocouple fitting M9x1  
maximum gas inlet pressure 60 mbar  
outlet pressure setting range  
3÷30 mbar  
room temperature 0÷70°C  
power supply 230V 50Hz



ROSINOX 94023744

## Electronic printed-circuit boards

**3390356 CONTROL ELECTRONIC BOARD 130x80 mm**  
model SERSA n° 940310  
for Fryer gas (ROSINOX)  
FR25G  
for Fryer (ROSINOX)  
FR30ENP



ROSINOX RX94035029


**3390359 LEVEL ELECTRONIC BOARD**  
model SERSA n° 921216a - 13 poles  
for Bratt pan electric (ROSINOX)  
MBM80E  
for Bratt pan gas (ROSINOX)  
MBM80G



ROSINOX RX94023587

## Energy regulators

**3350024 ENERGY ADJUSTER**  
contact capacity 240V 13A  
max temperature 125°C  
D-shaped pin  $\varnothing$  6x4.6 mm  
double rotation direction  
for Hot plate electric (ROSINOX) ROSICHEF 200E  
ROSICHEF 400E



ROSINOX RX94045299

**3350026 ENERGY ADJUSTER**  
contact capacity 230V 13A - max temperature 125°C  
D-shaped pin  $\varnothing$  6x4.6 mm  
double rotation direction  
for PYROCERAM. TOPS-SALAMANDERS-POTATO WARMERS




ROSINOX RX94812641



Suitable for:

**3350065 ENERGY REGULATOR**  
 contact capacity 230V 12A  
 D-shaped pin  $\varnothing$  6x4.6 mm



ROSINOX RX94027786


Suitable for:

**3350066 ENERGY REGULATOR**  
 contact capacity 400V 7A  
 D-shaped pin  $\varnothing$  6x4.6 mm



ROSINOX RX24848012

**3350067 ENERGY REGULATOR**  
 contact capacity 24V 16A  
 D-shaped pin  $\varnothing$  6x4.6 mm



ROSINOX

## Feet

**3313061 ADJUSTABLE PLASTIC FOOT  $\varnothing$  1" x h 78 mm**  
 with plastic support for tubular foot 40x40 mm  
 adjustable height 78÷100 mm  
 max capacity 90 Kg



ROSINOX

**3313005 STAINLESS STEEL FOOT  $\varnothing$  2" x h 125 mm**  
 with fixed screw M12x25 mm



ROSINOX RX94809563

## Filters

**3160007 WATER FILTER  $\varnothing$  3/4" FF**



ROSINOX RX94024528

## Fittings

**3349346 NICHEL-PL.HOSE-END FITTING  $\varnothing$  1/4" M  $\varnothing$  12**



ROSINOX RX94813991

**3349337 NICHEL-PL.T-FITTING  $\varnothing$  1/4" F-1/4" F-1/4" F**



ROSINOX RX94814314



Suitable for:

**3349324 NICHEL-PLATED FITTING  $\varnothing$  1/4"M-1/2"M**



ROSINOX 12033

Suitable for:

**3349330 NICHEL-PLATED FITTING  $\varnothing$  1/4"M-1/8"F**



ROSINOX RX94814405

## Fryer baskets and accessories

**3055197 FRYER BASKET 290x165x120 mm**  
in chromium plated iron



ROSINOX RX94806247

**3055360 FRYER BASKET 290x230x120 mm**  
made of chrome plated iron



ROSINOX RX94806221

## Fuses

**3049020 DELAY FUSE  $\varnothing$  5x20 mm - 10 PCS**  
250V 6.3A



ROSINOX RX27630086

**3049052 QUICK ACTING FUSE  $\varnothing$  5x20 mm - 10 PCS**  
250V 4A



ROSINOX RX27630268

## Gas burners

**3023341 BURNER  $\varnothing$  40x190 mm**  
made of STAINLESS steel  
for Fry top gas (ROSINOX) GR20G  
for Pot stove gas (ROSINOX) 120MFNDET



ROSINOX RX94561040



## Gas burners

- 3023339 BURNER  $\varnothing$  40x510 mm**  
 made of STAINLESS steel  
 for Bratt pan gas (ROSINOX) MBM80G  
 for Pot stove gas (ROSINOX) 121G



ROSINOX RX94006715

- 3023338 NOZZLE HOLDER FOR BURNER**  
 tapered coupling for pipe M18x1.5 mm  
 nozzle threading M13x1 mm  
 external thread  $\varnothing$  3/8" - internal  $\varnothing$  10 mm  
 pipe  $\varnothing$  12 mm  
 for Bratt pan gas (ROSINOX) MBM80G - SBM50G  
 for Fry top gas (ROSINOX) GR20G  
 for Pot stove gas (ROSINOX) 120MFMDDET



ROSINOX RX94018736

- 3023340 BURNER  $\varnothing$  40x510 mm**  
 made of STAINLESS steel  
 for Bratt pan gas (ROSINOX) SBM50G - SBM80G  
 for Bratt pan gas (ROSINOX) SBM50G



ROSINOX RX94494564

- 3023230 BURNER 525x205 mm**  
 made of STAINLESS steel



ROSINOX RX94814483

- 3023338 NOZZLE HOLDER FOR BURNER**  
 tapered coupling for pipe M18x1.5 mm  
 nozzle threading M13x1 mm  
 external thread  $\varnothing$  3/8" - internal  $\varnothing$  10 mm  
 pipe  $\varnothing$  12 mm  
 for Bratt pan gas (ROSINOX) MBM80G - SBM50G  
 for Fry top gas (ROSINOX) GR20G  
 for Pot stove gas (ROSINOX) 120MFMDDET



ROSINOX RX94018736

- 3023236 VERTICAL BURNER LH 300x55 mm**  
 NICKEL PLATED



ROSINOX RX94805710



Suitable for:

# ROSINOX

Suitable for:



## Gas taps and accessories

### 3348159 GAS TAP


without pilot flame  
clamp connection for pipe  $\varnothing$  8 mm  
outlet fitting M14x1.5 mm  
pin length 35 mm  
D-shaped pin  $\varnothing$  6x4.6 mm



ROSINOX RX94019874

### 3348149 GAS TAP STN3R

with pilot flame  
clamp connection for pipe  $\varnothing$  27 mm  
outlet fitting  $\varnothing$  1/2" F - pilot fitting  $\varnothing$  1/8" F  
thermocouple connection M9x1  
pin length 38 mm  
square pin 8x8 mm  
for Bratt pan gas (ROSINOX) SB50G  
for Kitchen gas (ROSINOX) 121GTS



ROSINOX RX94019932

### 3348014 GAS TAP 20/S

without pilot flame  
fittings  $\varnothing$  M16x1.5mm  
thermocouple fitting M8x1  
D-shaped pin  $\varnothing$  8x6.5mm



ROSINOX RX94805017

### 3348191 GAS TAP 21N

with connections and olives  
without pilot flame  
connections M16x1.5 mm  
D-pin  $\varnothing$  6x4.6 mm - long pin  
for Pot stove gas (ROSINOX) 020G - 040G  
120MFNDET - 121GFNC - 121GFND



ROSINOX RX94020500

### 3348016 GAS TAP 21S

with pilot flame  
fittings  $\varnothing$  M16x1.5mm  
with flow regulator  
thermocouple connection M9x1 mm  
D-shaped pin  $\varnothing$  8x6.5 mm



ROSINOX RX94805868

### 3348190 GAS TAP 21S

with connections and olives  
with pilot flame  
inlet fittings  $\varnothing$  M10x1 mm  
outlet connection M16x1.5 mm  
thermocouple connection M9x1  
D-shaped long pin  $\varnothing$  6x4.6 mm  
for Fry top gas (ROSINOX) GR20G  
for Pot stove gas (ROSINOX) 120MFNDET - 121GFNC  
121GFND



ROSINOX RX94020518





Suitable for:

Suitable for:

**3348002 GAS TAP 22S/0**  
 with pilot flame  
 with horizontal flange  
 fittings  $\varnothing$  M20x1.5mm  
 with flow regulator  
 thermocouple connection M9x1  
 D-shaped pin  $\varnothing$  10x8 mm

**3348158 GAS TAP 22S/0**  
 complete with connections and olives  
 with pilot flame  
 fittings M20x1.5 mm  
 with flow regulator  
 thermocouple connection M9x1  
 pin length 48 mm  
 square pin 8x8 mm  
 for Bratt pan gas (ROSINOX) SBM35G - SBM50G




ROSINOX RX94805298

ROSINOX RX94020484

**3348012 GAS TAP 23S/0**  
 with pilot flame  
 with horizontal flange  
 inlet fitting M28x1.5mm  
 outlet connection M24x1.5mm  
 with flow regulator  
 thermocouple connection M10x1  
 D-shaped pin  $\varnothing$  10x8 mm

**3348192 GAS TAP 23S/0**  
 with connections and olives  
 with pilot flame  
 with horizontal flange  
 inlet connection M28x1.5 mm  
 outlet fitting M24x1.5 mm  
 thermocouple fitting M9x1  
 pin length 46 mm  
 square pin 8x8 mm  
 for Bratt pan gas (ROSINOX) SBM80G



ROSINOX RX94805462

ROSINOX RX94020492

**3348036 OLIVE FOR 4 mm  $\varnothing$  PIPE**  
 for model PEL 21-22



ROSINOX RX94812588

## Gas valves and accessories

**3526131 EUROSIT VALVE FOR FRYER 110÷190°C**  
 inlet  $\varnothing$  3/8" F - outlet  $\varnothing$  3/8" F  
 thermocouple connection M9x1  
 maximum gas inlet pressure 50 mbar  
 outlet pressure adjustment range  
 3÷18 mbar  
 ambient temperature 0÷80°C  
 capillary length 1050 mm  
 bulb  $\varnothing$  4x200 mm

**3526130 EUROSIT VALVE FOR OVEN 100÷340°C**  
 inlet  $\varnothing$  3/8" F - outlet  $\varnothing$  3/8" F  
 thermocouple connection M9x1  
 maximum gas inlet pressure 50 mbar  
 outlet pressure adjustment range  
 3÷18 mbar  
 ambient temperature 0÷120°C  
 capillary length 1050 mm  
 bulb  $\varnothing$  4x72 mm



ROSINOX RX94812670

ROSINOX 94044054




Suitable for:

**3523035 KNOB MINISIT BLACK  $\varnothing$  37 mm**



ROSINOX RX26645036

**3523093 MINISIT VALVE FOR FRYER 70÷210°C**  
inlet  $\varnothing$  1/2" F - outlet  $\varnothing$  3/8" F  
thermocouple connection M9x1  
maximum gas inlet pressure 50 mbar  
ambient temperature 0÷60°C  
length capillary 1300 mm  
bulb  $\varnothing$  4x122 mm  
without cover. knob and flanges



ROSINOX

**3523091 MINISIT VALVE FOR OVEN 70÷310°C**  
inlet  $\varnothing$  1/2" F - outlet  $\varnothing$  3/8" F  
thermocouple connection M9x1  
maximum gas inlet pressure 50 mbar  
ambient temperature 0÷60°C  
capillary length 1300 mm  
bulb  $\varnothing$  4x75 mm  
without cover. knob and flanges



ROSINOX RX94024916

**3526134 VALVE EUROSIT FOR FRY TOP 40÷280°C**  
inlet  $\varnothing$  3/8" F - outlet  $\varnothing$  3/8" F  
thermocouple connection M9x1  
maximum gas inlet pressure 50 mbar  
outlet pressure calibration range  
outlet 3÷18 mbar  
ambient temperature 0÷80°C  
capillary length 1050 mm  
bulb  $\varnothing$  4x72 mm




ROSINOX RX94805660

# ROSINOX



Suitable for:

**3523047 MINISIT COVER**



ROSINOX

**3523949 MINISIT VALVE FOR FRYER 110÷190°C**  
inlet  $\varnothing$  1/2" F - outlet  $\varnothing$  3/8" F  
thermocouple connection M9x1  
maximum gas inlet pressure 50 mbar  
ambient temperature 0÷60°C  
capillary length 1050 mm  
bulb  $\varnothing$  6x105 mm  
supplied without lid knob and flanges



ROSINOX RX94805793

**3523060 OIL SEAL FITTING  $\varnothing$  6.5 mm**  
internal thread M10x0.75 - external thread M14x1.5



ROSINOX RX94008893




## Gaskets and seals

**3186009 ASBESTOS FREE FLAT GASKET  $\varnothing$  45x33x2 mm**




ROSINOX RX94801446

**3786715 FIBERGLASS GASKET  $\varnothing$  14 mm - 6m**  
max temperature 600°C  
COLOUR WHITE



ROSINOX RX94051653

**3186297 GASKET FLAT  $\varnothing$  18x10x2 mm**



ROSINOX RX94802659

**5010462 GASKET FLAT ASBESTOS FREE  $\varnothing$  24x17x2 mm**



ROSINOX RX94804820

ROSINOX RX94813770

ROSINOX RX94813967

**3786614 OVEN LAMP RECEPTACLE GASKET**  
dimensions 48x41x3 mm



ROSINOX RX24390700

## Glues

**3392012 BLACK SEALING NOVASIL 556 310 ml**  
max operating temperature +265°C  
HIGHLY ADHESIVE AND SEALING  
suitable for PYROCERAMIC RANGE



ROSINOX RX94032679

## Handles

**3242718 DOOR HANDLE STRIKE**  
for high temperatures  
mounting distance 43 mm  
for OVEN



ROSINOX LF-3242042



Suitable for:

# ROSINOX



Suitable for:

## Handles

### 3242945 LH-RH CATCH WITH LOCK 571 CR

straight handgrip  
base length 150x23x30h mm  
mounting distance 110 mm



ROSINOX

### 3242922 STRIKE FOR DOOR CATCH



ROSINOX

### 3242579 LH-RH CATCH WITHOUT LOCK 570 CR

straight handgrip  
base length 150x23x31h mm  
mounting distance 110 mm  
catch height 16.5 mm



ROSINOX RX94026184

### 3242922 STRIKE FOR DOOR CATCH



ROSINOX

## Heating elements

### 3355286 BUSH FOR HEATING ELEMENT



ROSINOX RX94812604

### 3355066 HEATING ELEMENT 1000W 220V

length 295 mm - width 90 mm  
fittings M14x1 mm  
operating ambient: dry



ROSINOX RX94812669

### 3755856 HEATING ELEMENT 10200W 230/400V

length 300 mm - width 180 mm  
coupling M54x1.5 mm - complete with cables  
complete with OR gaskets



ROSINOX RX94805397

### 3186697 O-RING 0159 EPDM



ROSINOX RX94806155



Suitable for:

**3186601 O-RING 04200 EPDM**



ROSINOX RX94806924

ROSINOX RX94812565

# ROSINOX



Suitable for:

**3755652 RING NUT 1-3/4" FOR HEATING ELEMENT**



ROSINOX RX94805330

ROSINOX RX94812677

**3755649 HEATING ELEMENT 10500W 230V**  
length 320 mm - width 253 mm  
connection M54x1.5 mm - complete with cables  
with two holes for bulb



ROSINOX RX94812639

**3786459 O-RING 04200 VITON**



ROSINOX RX94812518

**3755652 RING NUT 1-3/4" FOR HEATING ELEMENT**



ROSINOX RX94805330

ROSINOX RX94812677

**3355888 HEATING ELEMENT 1100W 240V**  
length 375 mm - width 95 mm  
fittings M10x1 mm



ROSINOX RX94805223

**3355441 HEATING ELEMENT 1135W 220/240V**  
length 425 mm - width 65 mm  
height 80 mm



ROSINOX RX94805678

**3455380 HEATING ELEMENT 1200W 240V**  
length 535 mm - width 75 mm  
fittings M14x1.5 mm



ROSINOX RX94004264

**3755488 HEATING ELEMENT 1580W 230V**  
length 455 mm - width 65 mm  
height 70 mm



ROSINOX RX94814020





Suitable for:

**3755492 HEATING ELEMENT 1600W 240V**  
length 450 mm - width 175 mm



ROSINOX RX94805488

Suitable for:

**3755004 HEATING ELEMENT 1650W 240V**  
length 490 mm - width 43 mm  
height 45 mm - fittings  $\varnothing$  1/4"



ROSINOX RX94800224

**3755487 HEATING ELEMENT 1840W 230V**  
length 280 mm - width 70 mm  
fittings  $\varnothing$  1/4"



ROSINOX ROSINOX

**3455382 HEATING ELEMENT 2000/2600W 220/240V**  
length 425 mm - width 115 mm  
height 40 mm - fittings  $\varnothing$  1/4"  
for Fry top electric (ROSINOX) GR20E




ROSINOX RX94001930

**3455136 HEATING ELEMENT 2000W 220V**  
length 265 mm width 160 mm  
height 40 mm - fittings M12x1 mm  
for Fry top electric (ROSINOX)  
ROYALCHEF PL25E - ROYALCHEF SPM25E  
for Fry top (ROSINOX) ROSIPLSN20E



ROSINOX RX94001872

**3455137 HEATING ELEMENT 2000W 230V**  
length 270 mm width 190 mm  
height 40 mm - fittings M12x1 mm  
for Fry top electric (ROSINOX) ERACHEF 200E  
ERACHEF 400E - ROYALCHEF PL25E  
ROYALCHEF SPM25E



ROSINOX RX94001807

**3755482 HEATING ELEMENT 2500W 230V**  
external  $\varnothing$  193 mm - total height 75 mm  
flange 70x22 mm



ROSINOX RX94806387

**3755592 HEATING ELEMENT 2900W 230V**  
length 285 mm - width 80 mm  
height 250 mm - flange 85x30 mm



ROSINOX RX94808631

**3755490 HEATING ELEMENT 3400W 230V**  
length 305 mm - width 190 mm  
height 80 mm



ROSINOX RX94806718

**3455383 HEATING ELEMENT 4200W 240V**  
length 580 mm - width 170 mm  
overall height 100 mm  
for Bratt pan electric (ROSINOX) SBM35E



ROSINOX RX94030558

Suitable for:

Suitable for:

**3455381 HEATING ELEMENT 4500/5400W 220/240V**

length 540 mm - width 30 mm  
height 33 mm - fittings M14x1.5 mm  
for Bratt pan electric (ROSINOX) MBM80E



ROSINOX RX94004629

**3755468 HEATING ELEMENT 5670W 230V**

length 295 mm - width 225 mm  
fitting  $\varnothing$  40 mm  
with gaskets and cables  
with cables - with bulb sheath



ROSINOX RX94812607

**3186580 OR GASKET 04131 VITON**



ROSINOX RX94803079

ROSINOX RX94803616

ROSINOX RX94812605

**3355445 HEATING ELEMENT 6000W 230V**

length 310 mm - width 250 mm  
overall height 257 mm - complete with cables  
operating ambient: immersion



ROSINOX RX94812636

**5012749 HEATING ELEMENT 650W 230V**

length 280 mm - width 75 mm  
flange 115x25 mm



ROSINOX RX94812603

**3755489 HEATING ELEMENT 6800W 230V**

length 300 mm - width 110 mm  
connection M54x1.5 mm - with cables  
with O-rings



ROSINOX RX94806916

**3186697 O-RING 0159 EPDM**



ROSINOX RX94806155

**3186601 O-RING 04200 EPDM**



ROSINOX RX94806924

ROSINOX RX94812565

**3755652 RING NUT 1-3/4" FOR HEATING ELEMENT**



ROSINOX RX94805330

ROSINOX RX94812677



Suitable for:

**3355887 HEATING ELEMENT 800W 230V**  
length 385 mm - width 110 mm  
2 flanges 55x17 mm



ROSINOX RX94805777

Suitable for:

**3755486 HEATING ELEMENT 990W 240V**  
length 470 mm - width 105 mm  
height 25 mm - 2 flanges 55x17 mm



ROSINOX RX94806460

**3755101 MIDDLE HEATING ELEMENT 2500W 220V**  
immersed length 490 mm - body  $\varnothing$  30 mm  
threaded connection  $\varnothing$  48 mm - flange 70x60 mm  
with bulb sheath - complete with cables



ROSINOX RX94800273

**3755652 RING NUT 1-3/4" FOR HEATING ELEMENT**



ROSINOX RX94805330

ROSINOX RX94812677

## Hinges, catches and accessories

**3053003 DOOR HINGE ROLL HOLDER**  
distance between holes 95 mm - overall length 118  
height 23 mm



ROSINOX RX94805280

**3053007 LEFTHAND DOOR HINGE FOR OVEN**  
distance between holes 175 mm - overall length 205  
height 160 mm



ROSINOX RX94805272

**3053003 DOOR HINGE ROLL HOLDER**  
distance between holes 95 mm - overall length 118  
height 23 mm



ROSINOX RX94805280

**3053006 RIGHTHAND DOOR HINGE FOR OVEN**  
distance between holes 175 mm - overall length 205  
height 160 mm



ROSINOX RX94805264

**3053003 DOOR HINGE ROLL HOLDER**  
distance between holes 95 mm - overall length 118  
height 23 mm



ROSINOX RX94805280



## Hydraulic piping

**3450152 HOSE RUBBER REINFORCED  $\varnothing$  13/19 mm**  
 internal  $\varnothing$  13 mm - external  $\varnothing$  19 mm  
 SOLD PER METER



ROSINOX RX94813948

**3450736 PRESSURE SWITCH PIPE  $\varnothing$  4x8.5 mm - 10 m**  
 made of black rubber  
 external  $\varnothing$  8.5 mm  
 internal  $\varnothing$  4 mm



ROSINOX RX94813947

## Igniters

**3001005 PIEZO IGNITER**  
 a  $\varnothing$  18 mm hole is needed for assembling  
 faston M  $\varnothing$  2.4 mm



ROSINOX RX94805009

## Incandescent lamps and neon lamps

**3221067 NEON LAMP FOR OVEN E10 2W 230V**  
 dimensions  $\varnothing$  10x28 mm  
 for OVEN



ROSINOX RX27610179

**3221041 OVEN LAMP E14 15W 230V**  
 max temperature 300°C  
 for OVEN - PIZZA OVEN



ROSINOX RX27610120

## Indicator lights

**3221544 GREEN INDICATOR LAMP 400V**  
 head  $\varnothing$  14 mm - hole  $\varnothing$  12 mm  
 wire connection length 190 mm  
 nichel plated brass case  
 for Pyroceramic plate (ROSINOX) RCM3F



ROSINOX RX94005832

**3221162 GREEN LAMP RECEPTACLE**  
 head  $\varnothing$  14.5 mm - hole  $\varnothing$  10 mm



ROSINOX RX94810956



Suitable for:

**3221194 GREEN NEON INDICATOR LAMP 220V**  
ø head 9 mm



ROSINOX RX94813811

Suitable for:

**3221192 LAMP SUPPORT**



ROSINOX RX94813812

**3221166 INDICATOR LAMP GREEN 400V**  
ø head 14 mm - ø hole 11.5 mm - 120°C  
universal application



ROSINOX RX94806346

**3221025 INDICATOR LAMP ORANGE 230V**  
head ø 15 mm - hole ø 13 mm - 120°C  
faston M 6.3x0.8 mm  
universal application



ROSINOX RX94801529

ROSINOX RX94801537

**3221165 INDICATOR LAMP ORANGE 400V**  
ø head 14 mm - ø hole 11.5 mm - 120°C  
universal application



ROSINOX RX94806353

**3221166 INDICATOR LAMP GREEN 400V**  
ø head 14 mm - ø hole 11.5 mm - 120°C  
universal application



ROSINOX RX94806346

**3221024 INDICATOR LAMP RED 230V**  
head ø 15 mm - hole ø 13 mm - 120°C  
faston M 6.3x0.8 mm  
universal application



ROSINOX RX94801511

**3221025 INDICATOR LAMP ORANGE 230V**  
head ø 15 mm - hole ø 13 mm - 120°C  
faston M 6.3x0.8 mm  
universal application



ROSINOX RX94801529

ROSINOX RX94801537

**3221192 LAMP SUPPORT**



ROSINOX RX94813812

**3221097 NEUTRAL INDICATOR LAMP 220V**  
head ø 8 mm - 120°C



ROSINOX RX94801073

ROSINOX RX94809845





# ROSINOX



Suitable for:

**3221095 ORANGE INDICATOR LAMP 230V**  
head  $\varnothing$  13.5 mm - hole  $\varnothing$  10 mm - 120°C  
universal application



ROSINOX RX94812468

Suitable for:

**3221543 ORANGE INDICATOR LAMP 400V**  
head  $\varnothing$  14 mm - hole  $\varnothing$  12 mm  
wire connection length 190 mm  
nichel plated brass case  
for Pyroceramic plate (ROSINOX) RCM3F



ROSINOX RX94005857

**3221167 RED LAMP RECEPTACLE**  
head  $\varnothing$  15 mm - hole  $\varnothing$  10 mm



ROSINOX RX94810215

**3221162 GREEN LAMP RECEPTACLE**  
head  $\varnothing$  14.5 mm - hole  $\varnothing$  10 mm



ROSINOX RX94810956

## Injectors

**3500194 CONICAL GAS NOZZLE M17x1  $\varnothing$  2,10 mm**



ROSINOX RX94033859

**3500024 GAS JET M10x1  $\varnothing$  1.15 mm**




ROSINOX RX94806874

**3500061 GAS JET M7x1  $\varnothing$  0.80 mm**



ROSINOX RX94812640

**3500063 GAS JET M7x1  $\varnothing$  0.95 mm**



ROSINOX RX94806668

## Interference suppression filters

**3160479 INTERFERENCE SUP. FILTER D.E.M.FC701Y2FL**  
0.47 $\mu$ F



ROSINOX RX94808409



Suitable for:

# ROSINOX



Suitable for:

## Ironmongery (screws,nuts,washers)

**3528010 FLAT WASHER M6**  
ø internal/external 6,4/12 mm - thickness 1,6 mm  
st./steel - UNI 6592 - DIN 125 A - ISO 7089



ROSINOX RX94801651

**3060069 HEXAGONAL NUT M8 MEDIUM**  
stainless steel - UNI 5588 - DIN 934 - ISO 4032



ROSINOX

## Knobs

**3241725 BLACK KNOB ø 45 mm**  
D shaft hole 6x4.6 mm  
for energy regulator



ROSINOX

**3241724 INDEXED PLATE ø 70 mm 0-100**  
for energy regulator




ROSINOX

**3241081 BLACK KNOB ø 65 mm SILK-SCREEN PRINTED**  
D shaft hole 8x6.5 mm



ROSINOX RX94806189

**3241573 BLACK KNOB ø 65 mm 0-295°C**  
D shaft hole 6x4.6 mm



ROSINOX RX94812578

**5035322 CHROME-PLATED BUSHING FOR KNOB ø 72 mm**



ROSINOX RX94812686



Suitable for:

**3241910 GAS TAP KNOB**  
 square hole 16x16 mm  
 for Bratt pan electric (ROSINOX)  
 MBM80E - SBM50E  
 for Bratt pan gas (ROSINOX)  
 MBM80G - SBM50G  
 for Fry top gas (ROSINOX)  
 GR20G



ROSINOX RX94030939

Suitable for:

**3241909 KNOB CAP FOR GAS TAP**  
 square cap 16x16 mm  
 D shaft hole 6x4.6 mm  
 for Bratt pan electric (ROSINOX)  
 MBM80E - SBM50E  
 for Bratt pan gas (ROSINOX)  
 MBM80G  
 for Fry top electric (ROSINOX)  
 GR20E  
 for Fry top gas (ROSINOX)  
 GR20G



ROSINOX RX94006830

**3241916 KNOB CAP RING NUT  $\varnothing$  46 mm**  
 for Bratt pan gas (ROSINOX)  
 MBM80G  
 for Bratt pan gas (ROSINOX) MBM100G-RCS



ROSINOX RX94030277

**3241707 GREY KNOB  $\varnothing$  30 mm ON-OFF-PILOT**  
 for USA MARKET



ROSINOX RX26645069

**3241724 INDEXED PLATE  $\varnothing$  70 mm 0-100**  
 for energy regulator



ROSINOX

**3241909 KNOB CAP FOR GAS TAP**  
 square cap 16x16 mm  
 D shaft hole 6x4.6 mm  
 for Bratt pan electric (ROSINOX)  
 MBM80E - SBM50E  
 for Bratt pan gas (ROSINOX)  
 MBM80G  
 for Fry top electric (ROSINOX)  
 GR20E  
 for Fry top gas (ROSINOX)  
 GR20G



ROSINOX RX94006830

**3241916 KNOB CAP RING NUT  $\varnothing$  46 mm**  
 for Bratt pan gas (ROSINOX)  
 MBM80G  
 for Bratt pan gas (ROSINOX) MBM100G-RCS



ROSINOX RX94030277



Suitable for:

# ROSINOX



Suitable for:

## Lamp receptacles and spare parts

**3221052 GLASS FOR OVEN LAMP RECEPTACLE  $\varnothing$  57 mm**  
thread  $\varnothing$  33.5 mm - overall height 34 mm



ROSINOX RX27610112

**3221350 LAMP RECEPTACLE WITH LAMP E14 15W 230V**  
lamp glass  $\varnothing$  42 mm  
mounting hole  $\varnothing$  38 mm  
max temperature 300°C



ROSINOX RX27610104

## Level gauges

**3201001 WATER LEVEL GAUGE HCX127 162x32 mm**  
distance between holes 130 mm  
for PANS



ROSINOX RX94800216

## Level sensors

**3397192 LEVEL PROBE  $\varnothing$  1/4" M-270 mm**  
overall length 330 mm  
for Bratt pan electric (ROSINOX)  
MBM80E  
for Bratt pan gas (ROSINOX)  
MBM80G



ROSINOX RX94023512

**3341068 LEVEL PROBE  $\varnothing$  1/4" M-350 mm**



ROSINOX RX94812665

## Magnet groups

**3182010 MAGNETIC UNIT PEL**  
 $\varnothing$  head 24 mm -  $\varnothing$  end 18 mm - length 59 mm  
thermocouple coupling M10x1  
for PEL tap model 23



ROSINOX 244761276

**3182009 MAGNETIC UNIT PEL BIG HEADED**  
 $\varnothing$  head 15.5 mm -  $\varnothing$  end 14 mm - length 44 mm  
for PEL tap model 22-24



ROSINOX 244761275

Suitable for:

Suitable for:

**3182003 MAGNETIC UNIT SIT**  
 ø head 25 mm - ø end 17 mm - length 56 mm  
 for valve SIT AC2 - VR8-MINISIT



ROSINOX


## Microswitches

**3240189 MICRO SWITCH M1DX20 10A 250V**



ROSINOX RX94806130

**3240198 MICROSWITCH FR501 3A 400V**



ROSINOX RX94807872

**3240407 MICROSWITCH KIT 16A 250V**  
 3 locking positions  
 the kit includes 5 levers:  
 lever 75 mm - lever 27 mm - lever 15 mm  
 lever 15 mm with wheel - lever 27 mm with wheel



ROSINOX RX94810935

**3240820 MICROSWITCH 16A 250V**



ROSINOX RX94812476

**3240054 MICROSWITCH 83731 5A 250V**  
 with cable length 500 mm



ROSINOX RX94050119

**3240181 PROTECTED MAGNET 62x18x10 mm**



ROSINOX RX94809266

## OR and ORM gaskets

**3186143 GASKET OR 04093 EPDM**



ROSINOX RX94807351

**3186013 O-RING GASKET 06187 EPDM ø 58 mm**



ROSINOX RX94807781



# ROSINOX



Suitable for:

Suitable for:

**3186014 O-RING GASKET 06225 EPDM  $\varnothing$  67 mm**

**3243069 O-RING OR 02068 EPDM**



ROSINOX RX94807294

ROSINOX RX94801214

**3186697 O-RING 0159 EPDM**

**1186411 O-RING 02031 EPDM**



ROSINOX RX94806155

ROSINOX RX94809761

**3243266 O-RING 02081 EPDM**

**1186238 O-RING 04081 EPDM**



ROSINOX RX94807450

ROSINOX RX94801172

**3067198 O-RING 04162 EPDM**

**3186601 O-RING 04200 EPDM**



ROSINOX RX94810256

ROSINOX RX94806924

ROSINOX RX94812565

**3786459 O-RING 04200 VITON**

**3186340 OR GASKET 03037 EPDM**



ROSINOX RX94812518

ROSINOX RX94807765

ROSINOX RX94812680

ROSINOX RX94813760

**3186580 OR GASKET 04131 VITON**



ROSINOX RX94803079

ROSINOX RX94803616

ROSINOX RX94812605





## Pilot burners and accessories

**3020085 FITTING FOR SPARKING PLUG FIXING M10x1mm**



ROSINOX RX94805082

**3020200 FITTING FOR THERMOCOUPLE  $\varnothing$  6.5 mm thread M10x1**



ROSINOX RX94805090

**3020285 GASKET FOR TARGET PILOT**



ROSINOX RX94806510

**3020082 OLIVE FOR 12 mm  $\varnothing$  PIPE**



ROSINOX RX94810978

**3020001 ONE-FLAME PILOT BURNER SIT**  
multigas with jet  $\varnothing$  0.20 mm  
with 2 positions bracket



ROSINOX LF-3020434

**3001003 ROUND SPARKING PLUG  $\varnothing$  7x44 mm**  
male faston M4x1 mm  
total length 65 mm



ROSINOX RX94034642

ROSINOX 94805207

**3020117 PILOT DEFLECTOR 3 FLAMES 53x40 mm**



ROSINOX RX94034634

**3020042 PILOT GAS JET  $\varnothing$  0.19 mm**



ROSINOX 822140380

**3020202 PILOT GAS JET  $\varnothing$  0.27 mm**



ROSINOX RX94806072

**3500385 PILOT GAS JET  $\varnothing$  0.30 mm**  
for Pot stove gas (ROSINOX)  
since 1/02/03



ROSINOX RX94814110



Suitable for:

**3500386 PILOT GAS JET  $\varnothing$  0.40 mm**  
for Pot stove gas (ROSINOX)  
since 1/02/03



ROSINOX RX94814111

Suitable for:

**3020449 PILOT GAS JET  $\varnothing$  0.54 mm**



ROSINOX RX94034519

**3020156 PILOT JET  $\varnothing$  0.25 mm**



ROSINOX RX94812644

**3020077 PIPE FITTING  $\varnothing$  4 mm**  
thread M10x1



ROSINOX RX94812587

**3020010 TARGET PILOT BURNER SIT 2 FLAMES**  
supplied without sparking plug, nozzle and gasket  
with thermocouple fitting



ROSINOX RX94805041

**3020042 PILOT GAS JET  $\varnothing$  0.19 mm**



ROSINOX 822140380


**3001003 ROUND SPARKING PLUG  $\varnothing$  7x44 mm**  
male faston M4x1 mm  
total length 65 mm



ROSINOX RX94034642

ROSINOX 94805207

**3020289 THREE-FLAME PILOT BURNER**  
supplied without sparking plug, nozzle  
'with pipe fitting and pipe pilot olive  
with thermocouple fitting  
with sparking plug fitting



ROSINOX RX94034485

**3001003 ROUND SPARKING PLUG  $\varnothing$  7x44 mm**  
male faston M4x1 mm  
total length 65 mm




ROSINOX RX94034642

ROSINOX 94805207



Suitable for:

**3020006 THREE-FLAME PILOT BURNER SIT**  
multigas with jet  $\varnothing$  0.20 mm  
with 3 positions bracket  
for Bratt pan gas (ROSINOX)  
MBM100G-RCS



ROSINOX RX94034659

ROSINOX 94034659

Suitable for:

**3001003 ROUND SPARKING PLUG  $\varnothing$  7x44 mm**  
male faston M4x1 mm  
total length 65 mm



ROSINOX RX94034642

ROSINOX 94805207

**3020002 TWO-FLAME PILOT BURNER SIT**  
multigas with jet  $\varnothing$  0.20 mm  
with 2 positions bracket



ROSINOX

**3001003 ROUND SPARKING PLUG  $\varnothing$  7x44 mm**  
male faston M4x1 mm  
total length 65 mm



ROSINOX RX94034642

ROSINOX 94805207

## Pressure gauges

**3054034 PRESSURE GAUGE  $\varnothing$  60 mm**  
coupling  $\varnothing$  1/8" M  
range 0-1 bar



ROSINOX RX94812660

## Probes

**3397193 TEMPERATURE PROBE  $\varnothing$  3x470 mm**  
cable length 600 mm  
for Fryer gas (ROSINOX)  
FR25G  
for Fryer electric (ROSINOX) FR15EHP



ROSINOX RX94035813



Suitable for:

# ROSINOX



Suitable for:

## Rating-plates

**7101453 CONTROL PLATE ADHESIVE 148x91 mm**  
for Bratt pan (ROSINOX) RCSSBM50G IONISATION  
for Fryer (ROSINOX)



ROSINOX RX94034345

## Relays

**3351901 POWER RELAY FINDER 60.62.8.230.0000**  
230V 50/60Hz  
2 exchange contacts 10A



ROSINOX RX94804291

**3351021 POWER RELAY FINDER 62.82.8.230.0000**  
230V 50/60Hz  
2 exchange contacts 16A



ROSINOX RX94807054

ROSINOX RX94813866

**3351008 POWER RELAY FINDER 62.83.8.230.0000**  
230V 50/60Hz  
3 exchange contacts 16A



ROSINOX RX94813837

**3351102 TIME LIMIT RELAY 80.11 16A 240V 50/60Hz**  
1 switching contact  
slow release on excitation



ROSINOX RX27470236


## Rotary switches

**3057050 CONNECTING BRACKET 28x21x16 mm**  
distance between hooking brackets 27 mm  
for the connection between selector switch and the  
for Bain-marie (ROSINOX) BHE2/1



ROSINOX RX94002813

**3057014 SELECTOR SWITCH 0-1 POSITIONS**  
contact capacity 16A 250V - max 150°C  
D spindle  $\varnothing$  6x4.6 mm  
back connection for thermostat




ROSINOX RX94805892



Suitable for:


**3057082 SELECTOR SWITCH 0-1 POSITIONS**  
 contact capacity 16A 250V - max 150°  
 D-shaft 6x4.6 mm



ROSINOX RX94805405


Suitable for:

**3057176 SELECTOR SWITCH 0-1 POSITIONS**  
 contact capacity 32A 250V - max 150°C  
 D-shaft  $\varnothing$  6x4.6 mm




ROSINOX RX94804994

**3057177 SELECTOR SWITCH 0-1 POSITIONS**  
 contact capacity 16A 250V - max 150°C  
 D-shaped pin  $\varnothing$  6x4.6 mm




ROSINOX RX94806098

**3057255 SELECTOR SWITCH 0-1 POSITIONS**  
 contact capacity 16A 250V - max 150°C  
 D spindle  $\varnothing$  6x4.6 mm  
 for Bain-marie (ROSINOX) BHE2/1




ROSINOX RX94015070

**3057094 SELECTOR SWITCH 0-1 0-1 POSITIONS**  
 contact capacity 32A 250V - max 150°C  
 D-shaped pin  $\varnothing$  6x4.6 mm




ROSINOX RX94014842

**3057015 SELECTOR SWITCH 0-1-0-1 POSITIONS**  
 contact capacity 16A 250V - max 150°C  
 D-shaped pin  $\varnothing$  6x4.6 mm




ROSINOX RX94805256

**3057001 SELECTOR SWITCH 0-3 POSITIONS**  
 contact capacity 32A 250V - max 150°C  
 D spindle  $\varnothing$  6x4.6 mm



ROSINOX RX273349196


**3057002 SELECTOR SWITCH 0-3 POSITIONS**  
 contact capacity 32A 250V - max 150°C  
 D-shaped pin  $\varnothing$  6x4.6 mm



ROSINOX RX27334937


ROSINOX RX94015088

**3057180 SELECTOR SWITCH 0-3 POSITIONS**  
 contact capacity 16A 250V - max 150°C  
 D-shaft  $\varnothing$  6x4.6 mm



ROSINOX RX94806478

**3057023 SELECTOR SWITCH 0-6 POSITIONS**  
 contact capacity 32A 250V - max 150°C  
 D shaft  $\varnothing$  6x4.6 mm



ROSINOX RX94015021




Suitable for:

# ROSINOX



Suitable for:

**3057024 SELECTOR SWITCH 0-6 POSITIONS**  
 contact capacity 16A 250V - max 150°C  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 for Bratt pan (ROSINOX) SBM60G



ROSINOX RX94015013

ROSINOX RX94806010

## Safety groups for pans and spare parts

**3184011 DEPRESSION VALVE  $\varnothing$  1/4" M**  
 in chrome plated brass  
 for safety group  $\varnothing$  3/4"  
 for safety group  $\varnothing$  1" 1/4



ROSINOX RX94806056

**3184018 SAFETY VALVE  $\varnothing$  1" 1/4 M**  
 max pressure 0.5 atm  
 for safety group 1" 1/4  
 ISPEL approved



ROSINOX RX94812663

**3184017 SAFETY VALVE  $\varnothing$  3/4" M**  
 max pressure 0.5 atm  
 for safety group  $\varnothing$  3/4"



ROSINOX RX94812619

## Solenoid valves

**3120261 SOLENOID VALVE MULLER 180°**  
 inlet 3/4" - outlet  $\varnothing$  12 mm  
 coil 230V 50/60Hz - max. temperature 90°C



ROSINOX RX94820016

**3120546 SOLENOID VALVE 220V  $\varnothing$  1/4" FF**  
 for water  
 COIL LUCIFER 121K0103 14W - 7 bar  
 dimensions of the body 35 mm - height 80 mm  
 for Bratt pan electric (ROSINOX)  
 MBM80E  
 for Bratt pan gas (ROSINOX)  
 MBM80G  
 for Boiling pan gas (ROSINOX) RCSMBM100G  
 RCSMBM150G - RCSMBM250G



ROSINOX RX94016201

ROSINOX 9401620



Suitable for:


**3120404 SOLENOID VALVE 230V  $\varnothing$  10.5 mm**  
solenoid valve 90° - 230V 50/60Hz - max 90°C  
3/4" inlet - 1 outlet  $\varnothing$  10.5 mm



ROSINOX RX94813749

Suitable for:

**3120407 SOLENOID VALVE 230V  $\varnothing$  10.5 mm**  
solenoid valve 180° - 230V 50/60Hz - max 90°C  
inlet 3/4" - 2 outlets  $\varnothing$  10.5 mm




ROSINOX RX94807480

**3120004 SOLENOID VALVE 319 220/240V  $\varnothing$  10 mm**  
solenoid valve 90° - 220/240V 50/60Hz - max 90°C  
inlet 3/4" - outlet  $\varnothing$  10 mm



ROSINOX RX94805520

**3120007 SOLENOID VALVE 349 220/240V  $\varnothing$  10 mm**  
solenoid valve 180° - 220/240V 50/60Hz - max 90°C  
inlet 3/4" - dual outlet  $\varnothing$  10 mm




ROSINOX RX94050168

**3120507 SOLENOID VALVE 349 24V  $\varnothing$  10 mm**  
solenoid valve 180° - 24V 50/60Hz - max 90°C  
inlet 3/4" - 2 outlets  $\varnothing$  10 mm



ROSINOX RX94804671

**3120009 SOLENOID VALVE 351 220/240V  $\varnothing$  14 mm**  
solenoid valve 180° - 220/240V 50/60Hz - max 90°C  
inlet 3/4" - outlet  $\varnothing$  14 mm



ROSINOX RX94809282

**3120010 SOLENOID VALVE 352 220/240V  $\varnothing$  14 mm**  
solenoid valve 90° - 220/240V 50/60Hz - max 90°C  
inlet 3/4" - dual outlet  $\varnothing$  14 mm



ROSINOX RX94809795

## Spark generators

**3181002 SPARK GENERATOR 2 OUTLETS**  
220/240V 50/60Hz



ROSINOX RX94027802

ROSINOX RX94805108

**3181003 SPARK GENERATOR 4 OUTLETS**  
220/240V 50/60Hz



ROSINOX RX94039229

ROSINOX RX94805116



Suitable for:

Suitable for:

**3181004 SPARK GENERATOR 6 OUTLETS**  
220/240V - 50/60Hz



ROSINOX RX94805124

## Sparking and detection plugs

**3806021 ROUND DETECTOR ELECTRODE**  
with flange  
for Bratt pan gas (ROSINOX) RCSSBM60G



ROSINOX RX94051521

**3806020 ROUND SPARKING PLUG**



ROSINOX RX94044214

**3001003 ROUND SPARKING PLUG  $\varnothing$  7x44 mm**  
male faston M4x1 mm  
total length 65 mm



ROSINOX RX94034642

ROSINOX 94805207

**3020230 ROUND SPARKING PLUG  $\varnothing$  7x54 mm**  
male faston M4x1 mm  
overall length 63 mm  
for COOKING RANGE series 700 PROTAGONISTA NUOVA  
for COOKING RANGE series 900 PROTAGONISTA NUOVA  
for COOKING RANGE series 1100 PROTAGONISTA NUOVA



ROSINOX RX94034493

**3806003 ROUND SPARKING PLUG  $\varnothing$  9.5x48 mm**  
total length 97 mm  
for HONEYWELL BURNER



ROSINOX RX94051513

**3020126 SPARKING PLUG ROUND  $\varnothing$  6.5x55 mm**  
connection  $\varnothing$  2.4 mm  
with silicone lead 1760 mm  
overall length with cable 1830 mm



ROSINOX RX94805157

**3020127 SPARKING PLUG ROUND  $\varnothing$  6.5x55 mm**  
connection  $\varnothing$  2.4 mm  
with silicone lead 625 mm  
overall length with cable 680 mm



ROSINOX RX94805132

**3020138 SPARKING PLUG ROUND  $\varnothing$  6.5x55 mm**  
connection  $\varnothing$  2.4 mm  
with silicone lead 970 mm  
overall length with cable 1030 mm



ROSINOX RX94805140



Suitable for:

**3020073 SPARKING PLUG ROUND  $\varnothing$  7/10x52 mm**  
 model 1/B  
 connection F 2.8x0.8 mm - complete with spring  
 overall length 54 mm



ROSINOX RX94805033

Suitable for:

**3020060 SPARKING PLUG ROUND  $\varnothing$  7x44 mm**  
 faston M 4x1 mm  
 overall length 82 mm  
 model CB505/021 Junkers  
 for model P502F



ROSINOX RX94805066

ROSINOX RX94805306

ROSINOX RX94805686

**3020124 SPARKING PLUG ROUND  $\varnothing$  7x44 mm**  
 connection  $\varnothing$  2.4 mm  
 overall length 58 mm



ROSINOX RX94027729

ROSINOX 94027729

## Springs

**3250233 LID SPRING  $\varnothing$  24x240 mm**  
 length without hooks 195 mm  
 for BRATT PAN SBM50G-SBM35E  
 for BOILING PAN MBM80G-MBM80E



ROSINOX RX94024791

## Switches

**3319150 BIPOLAR PUSH-BUTTON 16A 250V BLACK**  
 mounting hole  $\varnothing$  25 mm



ROSINOX RX94805173

**3319091 CHANGEOVER SWITCH 2 POLE GREEN 16A 250V**  
 16(4)A 250V  
 with indicator lamp and push-button cap  
 max. temperature 120°C  
 mounting hole 22x30 mm




ROSINOX RX94809506



Suitable for:


**3319944 SWITCH 2-POLE GREEN 16A 250V**  
16(4)A 250V - with indicator lamp  
silk-screen printing 0 - I  
max. temperature 120°C  
mounting hole 22x30 mm



ROSINOX RX94805496


Suitable for:

**3319090 SWTCH 2-POLE GREEN 16A 250V**  
16(4)A 250V  
with indicator lamp and switch cover  
max. temperature 120°C  
mounting hole 22x30 mm



ROSINOX RX94809514

**3319714 TWO-POLE LEVER SWITCH 16A 250V**  
threaded coupling  $\varnothing$  12 mm  
ON-OFF function  
for Bain-marie electric (ROSINOX) BME1/1



ROSINOX RX94026036

## Taps for tank refilling

**3359129 WATER INLET TAP  $\varnothing$  1/2" FF**



ROSINOX RX94806338

## Telethermometers

**3441011 BLACK TELETHERMOMETER 56x25 mm 0-120°C**  
plastic case  
capillary length 1500 mm  
bulb  $\varnothing$  6x15 mm



ROSINOX RX94807252

**3441007 TELETHERMOMETER WHITE  $\varnothing$  60 mm 0-120°C**  
metal case  
PVC covered capillary 3000 mm  
spring bulb  $\varnothing$  8x32 mm  
bulb fitting M10x1



ROSINOX RX94803038



## Terminal blocks

### 3247009 6-POLE TERMINAL BLOCK FV122/B 40A 600V

for cable max 6 mm<sup>2</sup>  
operating temperature 150°C  
nominal voltage 450 V



ROSINOX RX94810223

## Thermocouples and accessories

### 3440837 THERMOCOUPLE SIT M9x1 100 cm - 10 PCS



ROSINOX RX94015112

### 3440037 THERMOCOUPLE SIT M9x1 100 cm.



ROSINOX RX94015112

### 3440837 THERMOCOUPLE SIT M9x1 100 cm - 10 PCS



ROSINOX RX94015112

### 3440859 THERMOCOUPLE SIT M9x1 60 cm - 10 PCS GIUNTO M8x1



ROSINOX RX94805025

### 3440059 THERMOCOUPLE SIT M9x1 60 cm THREAD M8x1



ROSINOX RX94805025

### 3440859 THERMOCOUPLE SIT M9x1 60 cm - 10 PCS GIUNTO M8x1



ROSINOX RX94805025



Suitable for:

Suitable for:

**3440836 THERMOCOUPLE SIT M9x1 85 cm - 10 PCS**



ROSINOX RX94024973

**3440836 THERMOCOUPLE SIT M9x1 85 cm.**

**3440836 THERMOCOUPLE SIT M9x1 85 cm - 10 PCS**



ROSINOX RX94024973

ROSINOX RX94024973

**3440165 THERMOCOUPLE 11/32 P.ASA 60 cm COUPLING with fitting M11x1**




ROSINOX

## Thermostatic gas valves

**3348170 THERMOSTATIC TAP ROBERTSHAW BJW**  
adjustment temperature 93-287°C  
inlet fitting  $\varnothing$  10 mm  
outlet pipe fitting  $\varnothing$  3/8"NPT  
bulb  $\varnothing$  5x290 mm  
capillary length 1200 mm

**3345006 THERMOSTATIC TAP 24ST**  
Adjustment temperature 120-320°C  
connections M20x1.5 mm  
thermocouple connection M9x1  
bulb  $\varnothing$  6x100 mm  
capillary length 1200 mm  
D-shaped pin  $\varnothing$  10x8 mm




ROSINOX

ROSINOX RX94806536

## Thermostats

**3444012 KNOB BLACK  $\varnothing$  41 mm SILK-SCREEN PRINTED**  
D-shaped hole 6x4.6 mm  
for thermostat IMIT

**3444008 KNOB BLACK  $\varnothing$  41 mm 0-90°C**  
D-shaped hole 6x4.6 mm  
for thermostat IMIT




ROSINOX RX94800935

ROSINOX RX94813937



Suitable for:

**3444974 SINGLE-PHASE THERMOSTAT 100-615°C**  
 complete with switch  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 covered capillary length 1100 mm - 16A 250V  
 bulb  $\varnothing$  4x230 mm



ROSINOX RX94090032


Suitable for:

**3444771 SINGLE-PHASE THERMOSTAT 125°C**  
 with manual reset  
 covered capillary length 900 mm - 16A 230V  
 bulb  $\varnothing$  3.1x120 mm



ROSINOX RX94805231

**3444239 SINGLE-PHASE THERMOSTAT 240°C**  
 with manual reset  
 capillary length covered 860 mm - 16A 250V  
 bulb  $\varnothing$  6x77 mm - with stuffing gland fitting M10x1



ROSINOX RX94805702

**3444372 SINGLE-PHASE THERMOSTAT 245°C**  
 with manual reset  
 covered capillary length 1170 mm - 16A 250V  
 bulb  $\varnothing$  6x133 mm



ROSINOX RX94804986

**3444346 SINGLE-PHASE THERMOSTAT 30-90°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 covered capillary length 900 mm - 16A 250V  
 bulb  $\varnothing$  6x130 mm - with stuffing gland fitting M9x1




ROSINOX RX94805249

**3444774 SINGLE-PHASE THERMOSTAT 45-295°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 covered capillary length 900 mm - 16A 230V  
 bulb  $\varnothing$  4x95 mm




ROSINOX RX94812577

**3444467 SINGLE-PHASE THERMOSTAT 55-180°C**  
 complete with selector switch  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 covered capillary length 870 mm - 16A 250V  
 bulb  $\varnothing$  4x120 mm



ROSINOX RX94812560

**3744068 SINGLE-PHASE THERMOSTAT 60-200°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 capillary length 900 mm  
 bulb  $\varnothing$  6x80 mm - with adapter nipple band M9x1  
 with complete tank joint M12x1




ROSINOX RX94016680



Suitable for:

**3444376 SINGLE-PHASE THERMOSTAT 95-190°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 covered capillary length 1010 mm - 16A 250V  
 bulb  $\varnothing$  6x100 mm - with adapter nipple band M10x1



ROSINOX RX94805371

Suitable for:

**5009025 STUFFING GLAND THERMOSTAT M10x1**  
 hole  $\varnothing$  4.5 mm



ROSINOX RX94812566


**3444312 THERMOSTAT THREE-PHASE 360°C**  
 with manual reset  
 capillary length covered 1500 mm - 16A 250V  
 bulb  $\varnothing$  4x110 mm



ROSINOX RX94800158

ROSINOX RX94812622

**3444479 THREE-PHASE THERMOSTAT 120°C**  
 with manual reset  
 covered capillary length 900 mm - 10A 400V  
 bulb  $\varnothing$  6x100 mm



ROSINOX RX94800505

**3444769 THREE-PHASE THERMOSTAT 132°C**  
 with automatic reset  
 capillary length 900 mm - 16A 230V  
 bulb  $\varnothing$  6x80 mm - with adapter nipple band M9x1




ROSINOX RX94812642

**3444770 THREE-PHASE THERMOSTAT 157°C**  
 with manual reset  
 covered capillary length 900 mm - 16A 230V  
 bulb  $\varnothing$  6x80 mm




ROSINOX RX94805413

**3444775 THREE-PHASE THERMOSTAT 159°C**  
 with manual reset  
 capillary length 1100 mm - 16A 230V  
 bulb  $\varnothing$  3.1x185 mm




ROSINOX RX94812646

**3444375 THREE-PHASE THERMOSTAT 225°C**  
 with manual reset  
 covered capillary length 900 mm - 10A 400V  
 bulb  $\varnothing$  6x90 mm - with adapter nipple band M10x1




ROSINOX RX94812594

**3444307 THREE-PHASE THERMOSTAT 230°C**  
 with manual reset  
 covered capillary length 900 mm - 10A 400V  
 bulb  $\varnothing$  6x100 mm - with adapter nipple band M10x1



ROSINOX RX94016599

**3744113 THREE-PHASE THERMOSTAT 230°C**  
 with manual reset  
 covered capillary length 600 mm - 10A 400V  
 bulb  $\varnothing$  4x122 mm




ROSINOX RX94812559



Suitable for:

**3444088 THREE-PHASE THERMOSTAT 30-110°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 capillary length covered 900 mm - 10A 400V  
 bulb  $\varnothing$  6x130 mm - with stuffing gland fitting M9x1



ROSINOX


Suitable for:

**3444620 THREE-PHASE THERMOSTAT 45-120°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 covered capillary length 870 mm - 16A 380V  
 bulb  $\varnothing$  6x140 mm




ROSINOX RX94805421

**3444694 THREE-PHASE THERMOSTAT 50-300°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 capillary length 880 mm  
 bulb  $\varnothing$  6x77 mm




ROSINOX

**3444052 THREE-PHASE THERMOSTAT 50-320°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 capillary length 900 mm - 10A 400V  
 bulb  $\varnothing$  3x230 mm




ROSINOX RX94805645

**3444594 THREE-PHASE THERMOSTAT 65-200°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 capillary length 880 mm  
 bulb  $\varnothing$  6x77 mm - with adapter nipple bland M9x1  
 with complete tank joint M12x1




ROSINOX RX24845588

**3444371 THREE-PHASE THERMOSTAT 70-195°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 covered capillary length 1500 mm - 10A 400V  
 bulb  $\varnothing$  6x135 mm



ROSINOX RX94804978

**3444779 THREE-PHASE THERMOSTAT 75-295°C**  
 D-shaped pin  $\varnothing$  6x4.6 mm  
 covered capillary length 900 mm - 16A 230V  
 bulb  $\varnothing$  4x92 mm



ROSINOX RX94812621



Suitable for:

# ROSINOX



Suitable for:


## Timers

**3446159 TIMER 120 MINUTES C53**  
 manually set mechanical timer  
 manually set cycle 120 minutes  
 contact capacity 16A 250V  
 max temperature 125°C  
 2 normally closed contacts  
 2 normally closed contacts  
 complete with silkscreen printed plate and knob  
 dimensions 49.5x58 mm depth 52 mm



ROSINOX RX94027836

**3446155 TIMER 120 MINUTES S43V**  
 mechanical timer with sound alarm  
 manual winding cycle 120 minutes  
 complete with screenprinted plate and knob  
 size ø 60x27 mm




ROSINOX

**3446157 TIMER 30 MINUTES C53**  
 manually set mechanical timer  
 manually set cycle 30 minutes  
 contact capacity 16A 250V  
 max temperature 125°C  
 2 normally closed contacts  
 2 normally closed contacts  
 complete with silkscreen printed plate and knob  
 dimensions 49.5x58 mm depth 52 mm



ROSINOX RX94027869

**3446150 TIMER 30 MINUTES S43V**  
 mechanical timer with sound alarm  
 manual winding cycle 30 minutes  
 complete with screenprinted plate and knob  
 size ø 60x27 mm



ROSINOX

**3446154 TIMER 60 MINUTES S43V**  
 mechanical timer with sound alarm  
 manual winding cycle 60 minutes  
 complete with screenprinted plate and knob  
 size ø 60x27 mm



ROSINOX

## Wheels and accessories

**7102729 WHEEL ø 150 mm**  
 central hole ø 14 mm - with pin groove 24x6 mm  
 complete with folding handle



ROSINOX RX94806020

**3522045 WHEEL ø 200 mm**  
 hole ø 16 mm - with key slot 5 mm  
 complete with folding handle



ROSINOX RX94030871



Suitable for:

**ROSINOX**



Suitable for:

## **Wire pan supports**

**3354001 GRID REDUCER FOR MOKA 265x265 mm**  
in stainless steel




















ROSINOX RX94806759

*The data herewith contained may change without notice and LF SpA cannot be held responsible for possible errors stated or resulting by the use of this document. All rights reserved. No part of this publication may be reproduced without written permission by LF SpA.*



## Distributing Components, Spare Parts & Accessories in original quality worldwide

- 
-  **LF SpA HEADQUARTERS**  
via Voltri, 80 - 47522 Cesena (FC) ITALY  
Tel. +39 0547 34 11 11 - Fax +39 0547 34 11 10  
[www.lfcomb724.it](http://www.lfcomb724.it) - [www.lfcomb724.mobi](http://www.lfcomb724.mobi) - [info@lfcomb.it](mailto:info@lfcomb.it)  
Export Dept.: Tel. +39 0547 34 11 50 - Fax: +39 0547 34 11 55  
[www.lfspareparts724.com](http://www.lfspareparts724.com) - [www.lfspareparts724.mobi](http://www.lfspareparts724.mobi)  
[export@lfspareparts.com](mailto:export@lfspareparts.com)
  -  **OOO LF RUSSIAN FEDERATION**  
Ul. Anatoliya Zhivova, 8 - office 1 - 123100 Moscow  
Tel. +7 499 259 85 75  
Fax +7 495 725 26 53  
[www.lfspareparts724.ru](http://www.lfspareparts724.ru)  
[www.lfspareparts724.mobi](http://www.lfspareparts724.mobi)  
[info@lfspareparts.ru](mailto:info@lfspareparts.ru)
  -  **EPGC Sas FRANCE**  
13, Rue des Forts - 59960 Neuville en Ferrain  
Tel. +33 (0)3 20 25 06 21  
Fax +33 (0)3 20 25 34 12  
[www.epgc.com](http://www.epgc.com)  
[www.epgc724.mobi](http://www.epgc724.mobi)  
[epgc@epgc.com](mailto:epgc@epgc.com)
  -  **LF Repuestos Horeca S.L.U. SPAIN**  
Calle Ciudad Real, 10 - 45517 Escalonilla - Toledo  
Tel. +34 91 477 91 00  
Fax +34 91 477 90 81  
[www.lfrepuestos-horeca724.es](http://www.lfrepuestos-horeca724.es)  
[www.lfrepuestos724.mobi](http://www.lfrepuestos724.mobi)  
[info@lfrepuestos.es](mailto:info@lfrepuestos.es)
  -  **LF GmbH GERMANY**  
Junkersstrasse, 1 - D-82178 Puchheim - München  
Tel. +49 89 89 45 78 66  
Fax +49 89 89 45 78 88  
[www.lfersatzteile724.de](http://www.lfersatzteile724.de)  
[www.lfersatzteile724.mobi](http://www.lfersatzteile724.mobi)  
[info@lfersatzteile.de](mailto:info@lfersatzteile.de)
  -  **LF SpA Cesena (IT) Swiss Branch Steinhausen SWITZERLAND**  
Sennweidstrasse, 45 - CH-6312 Steinhausen  
Tel. +41 (0)41 760 15 80-1  
Fax +41 (0)41 760 15 85  
[www.lfersatzteile724.ch](http://www.lfersatzteile724.ch)  
[www.lfersatzteile724.mobi](http://www.lfersatzteile724.mobi)  
[info@lfersatzteile.ch](mailto:info@lfersatzteile.ch)
  -  **LF China REPUBLIC OF CHINA**  
Room 403, No.2, Huadu Mansion, Lane 422, Huanghua Rd.  
Minhang Dist. - 201103 Shanghai  
Tel. +86 (0)21 33 53 66 31  
Fax +86 (0)21 33 53 66 32  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[www.lfspareparts724.mobi](http://www.lfspareparts724.mobi)  
[china@lfspareparts.com](mailto:china@lfspareparts.com)
  -  **LF Spare Parts Ltd. UNITED KINGDOM**  
A10a Lakeside Business Park, Broadway Lane  
South Cerney, Gloucestershire GL7 5XL  
Tel. +44 (0)1285 86 16 25  
Fax +44 (0)1285 86 39 49  
[www.lfspareparts724.co.uk](http://www.lfspareparts724.co.uk)  
[www.lfspareparts724.mobi](http://www.lfspareparts724.mobi)  
[info@lfspareparts.co.uk](mailto:info@lfspareparts.co.uk)
- 
-  **AUSTRALIA AND NEW ZEALAND**  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[andrea.calvio@lfspareparts.com](mailto:andrea.calvio@lfspareparts.com)
  -  **DENMARK**  
[www.lfspareparts724.dk](http://www.lfspareparts724.dk)  
[michael.lenth@lfspareparts.com](mailto:michael.lenth@lfspareparts.com)
  -  **AUSTRIA**  
[www.lfspareparts724.at](http://www.lfspareparts724.at)  
[ludwig.neier@lfersatzteile.at](mailto:ludwig.neier@lfersatzteile.at)
  -  **SOUTH KOREA**  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[fabio.doni@lfspareparts.com](mailto:fabio.doni@lfspareparts.com)
  -  **BALKAN COUNTRIES**  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[matija.ramov@lfspareparts.com](mailto:matija.ramov@lfspareparts.com)
  -  **TURKEY**  
[www.lfyedekparca724.com](http://www.lfyedekparca724.com)  
[basar.ergun@lfyedekparca.com](mailto:basar.ergun@lfyedekparca.com)
  -  **BALTIC COUNTRIES**  
[www.lfspareparts724.com](http://www.lfspareparts724.com)  
[inara.silina@lfspareparts.com](mailto:inara.silina@lfspareparts.com)
  -  **USA AND CANADA**  
[www.lfspareparts724.us](http://www.lfspareparts724.us)  
[sauro.dallaglio@lfspareparts.us](mailto:sauro.dallaglio@lfspareparts.us)  
[howard.truitt@lfspareparts.us](mailto:howard.truitt@lfspareparts.us)
  -  **CENTRAL AND EASTERN EUROPE**  
[www.lfspareparts724.cz](http://www.lfspareparts724.cz)  
[jiri.kremla@lfspareparts.cz](mailto:jiri.kremla@lfspareparts.cz)