

Spare parts for:

Espresso coffee machines



Suitable for: **BWT WATER MORE**



This catalogue is automatically generated. Therefore, the sequence of the items might not be always shown at best. Updates will be issued in case of additions and/or amendments. Suitable **universal spare parts** may not be included





Suitable for:

Water purification filters 3010700 FILTER HEAD WATER+MORE 3/8" with wall support

3010706 FILTER CARTRIDGE BESTMAX L for water treatment for TECHNICAL purposes cartridge height with head 490 mm water temperature $+4^{\circ}C$ to $+30^{\circ}C$ capacity at $10^{\circ}Kh$ 6240 L nominal flow rate 60 L/h operating pressure 2/8 bar both horizontal and vertical operation



BWT WATER MORE FS26I00A00

BWT WATER MORE FS00Y03A00

3010705

BWT WATER MORE M0812113

LITER COUNTER ACQUAMETER WATER+MORE 3010708 with LCD display



BWT WATER MORE FS00Y00A00

BWT WATER MORE FS00Y51A00

BWT WATER MORE FS00Y00X00


BWT WATER MORE FS00Y51V00

VENT TAP BESTFLUSH 3/8" 3010701 It allows an extremely simple venting, thus saving your time and money Filtering capacity used at 100%



BWT WATER MORE M0812196

3010700 FILTER HEAD WATER+MORE 3/8" with wall support



BWT WATER MORE M0812136

for water treatment for TECHNICAL purposes



FILTER CARTRIDGE BESTMAX M

BWT WATER MORE FS24I00A00 BWT WATER MORE M0812112

LITER COUNTER ACQUAMETER WATER+MORE 3010708 with LCD display



BWT WATER MORE FS00Y00A00 BWT WATER MORE FS00Y00X00

3010701





BWT WATER MORE FS00Y03A00

BWT WATER MORE M0812136

BWT WATER MORE FS00Y51A00

BWT WATER MORE FS00Y51V00

BWT WATER MORE M0812196



Suitable for:

3010700



3010703

FILTER CARTRIDGE BESTMAX S for water treatment for TECHNICAL purposes cartridge height with head 350 mm water temperature +4°C to +30°C capacity at 10°Kh 1200 L nominal flow rate 60 L/h operating pressure 2/8 bar both horizontal and vertical operation



BWT WATER MORE FS22I00A00 BWT WATER MORE M0812111

3010708 LITER COUNTER ACQUAMETER WATER+MORE with LCD display



FILTER HEAD WATER+MORE 3/8"

with wall support

BWT WATER MORE FS00Y00A00 BWT WATER MORE FS00Y00X00

3010701 VENT TAP BESTFLUSH 3/8" It allows an extremely simple venting, thus saving your time and money Filtering capacity used at 100%



BWT WATER MORE FS00Y51V00

BWT WATER MORE M0812196

3010700 FILTER HEAD WATER+MORE 3/8" with wall support

cartridge height with head 410 mm water temperature $+4^{\circ}$ C to $+30^{\circ}$ C capacity at 10°Kh 3000 L nominal flow rate 60 L/h operating pressure 2/8 bar both horizontal and vertical operation

FILTER CARTRIDGE BESTMAX V

BWT WATER MORE M0812136

for water treatment for TECHNICAL purposes



BWT WATER MORE FS23I00A00

BWT WATER MORE FS00Y03A00

3010704

BWT WATER MORE M0812115

LITER COUNTER ACQUAMETER WATER+MORE 3010708 with LCD display





BWT WATER MORE FS00Y00A00

BWT WATER MORE FS00Y51A00

BWT WATER MORE FS00Y00X00 3010701

VENT TAP BESTFLUSH 3/8" It allows an extremely simple venting, thus saving your time and money Filtering capacity used at 100%



BWT WATER MORE FS00Y03A00

BWT WATER MORE M0812136

BWT WATER MORE FS00Y51A00 BWT WATER MORE FS00Y51V00 BWT WATER MORE M0812196





3010702 FILTER CARTRIDGE BESTMAX X

for water treatment for TECHNICAL purposes cartridge height with head 270 mm water temperature +4°C to +30°C capacity at 10°Kh 720 L nominal flow rate 60 L/h operating pressure 2/8 bar both horizontal and vertical operation Suitable for: 3010700 FILTER HE

10700 FILTER HEAD WATER+MORE 3/8" with wall support



BWT WATER MORE FS20I00A00 BWT WATER MORE M0812110

3010708 LITER COUNTER ACQUAMETER WATER+MORE with LCD display

BWT WATER MORE M0812136

for water treatment for TECHNICAL purposes

FILTER CARTRIDGE BESTMAX XL

cartridge height with head 492 mm water temperature +4°C to +30°C



BWT WATER MORE FS00Y00A00 BWT WATER MORE FS00Y00X00

3010701 VENT TAP BESTFLUSH 3/8" It allows an extremely simple venting, thus saving your time and money Filtering capacity used at 100%



BWT WATER MORE FS00Y51V00

BWT WATER MORE M0812196

3010700 FILTER HEAD WATER+MORE 3/8" with wall support



capacity at 10°Kh 8160 L nominal flow rate 60 L/h operating pressure 2/8 bar

BWT WATER MORE FS28100A00

BWT WATER MORE FS00Y03A00

3010707

BWT WATER MORE M0812114

3010708 LITER COUNTER ACQUAMETER WATER+MORE with LCD display



BWT WATER MORE FS00Y00A00

3010701

BWT WATER MORE FS00Y51A00

WATER MORE FS00Y00A00

VENT TAP BESTFLUSH 3/8" It allows an extremely simple venting, thus saving your time and money

BWT WATER MORE FS00Y00X00

Filtering capacity used at 100%



BWT WATER MORE FS00Y03A00 BWT WA

BWT WATER MORE M0812136

BWT WATER MORE FS00Y51A00 BWT WATER MORE FS00Y51V00 BWT WATER MORE M0812196





7150446 FILTER CARTRIDGE BESTMAX 2XL for water treatment for TECHNICAL purposes cartridge height with head 574 mm water temperature +4°C to +30°C capacity at 10°Kh 8270 L

nominal flow rate 60 L/h operating pressure 2/8 bar

Suitable for:

3010700 FILTER HEAD WATER+MORE 3/8" with wall support



BWT WATER MORE FS30I00A00 BWT WATER MORE M0812116

3010708 LITER COUNTER ACQUAMETER WATER+MORE with LCD display



BWT WATER MORE FS00Y03A00 BWT WATER MORE M0812136

7150448 PLASTIC NIPPLES 3/4"M-3/8"F



BWT WATER MORE M0812153

3010701 VENT TAP BESTFLUSH 3/8" It allows an extremely simple venting, thus saving your time and money Filtering capacity used at 100%



BWT WATER MORE FS00Y51A00

BWT WATER MORE FS00Y51V00

BWT WATER MORE M0812196



 BWT WATER MORE
 FS00Y00A00
 BWT WATER MORE
 FS00Y00X00

 7150447
 PLASTIC NIPPLES 1/2"M-3/8"F



BWT WATER MORE M0812152

7150449 PLASTIC NIPPLES 3/8"M-3/4"F



BWT WATER MORE M0812155











Suitable for:

Water softeners and accessories

3010711 **DESCALING TABLET BESTSAVE L** capacity at 10°dKH - 200 l

3010710 **DESCALING TABLET BESTSAVE M** capacity at 10°dKH - 100 l

maximum service life after installation 2 months

maximum service life after installation 2 months

BWT bes DEWT ING P

BWT WATER MORE KS12I00A00

3010709 **DESCALING TABLET BESTSAVE S** capacity at 10°dKH - 50 l

maximum service life after installation 2 months



BWT WATER MORE KS08I00A00

BWT WATER MORE KS1000A00

The data herewith contained may change without notice and LF SpA cannot be held responsible for possible errors stated or resulting by the use of this document. All rights reserved. No part of this publication may be reproduced without written permission by LF SpA.

