



Spare parts for:

Warewashing equipment



Suitable for:

BRITA



This catalogue is automatically generated.
Therefore, the sequence of the items might
not be always shown at best.

Updates will be issued in case of additions
and/or amendments.

Suitable universal spare parts may not be included





Suitable for:

BRITA



Suitable for:

Inlet hoses

3010220 HOSE CLAMP SET
with non-return valve and fittings



BRITA 274000

Water purification filters

3010621 CARBON HARDNESS TEST KIT
before starting any of the water filters BRITA it is necessary to determine the temporary hardness from carbonates in local water. The higher the carbonate hardness is, the higher the limestone deposit in the instrument is.



BRITA 710800

3010615 CARTRIDGE PURITY C 150
for water treatment for TECHNICAL purposes



BRITA 102828

BRITA 102828+1014370

BRITA 102829

3010616 CARTRIDGE PURITY C 300
for water treatment for TECHNICAL purposes



BRITA 102827

BRITA 102827+1014370

3010618 CARTRIDGE PURITY C 50
for water treatment for TECHNICAL purposes



BRITA 102831

BRITA 102831+1014370

3010617 CARTRIDGE PURITY C 500
for water treatment for TECHNICAL purposes



BRITA 1002045

BRITA 1002045+1014370

3010611 CARTRIDGE PURITY CLEAN EXTRA 1200
specific for WASHING



BRITA 1008197

BRITA 1008197+1014370

BRITA 315650

3010610 CARTRIDGE PURITY CLEAN 1200
specific for WASHING



BRITA 315645

BRITA 315645+1014370

BRITA 315849

3010614 CARTRIDGE PURITY ST 1200
specific for HO.RE.CA



BRITA 273400

BRITA 273400+1014370



Suitable for:

Suitable for:

3010612 CARTRIDGE PURITY ST 450
specific for HO.RE.CA



BRITA 273000

BRITA 273000+1014370

3010613 CARTRIDGE PURITY ST 600
specific for HO.RE.CA



BRITA 2732

BRITA 273200

BRITA 273200+1014370

3010258 CARTRIDGE PURITY STEAM 1200 COMPLETE
specific for OVENS



BRITA 1000231

3010257 CARTRIDGE PURITY STEAM 600 COMPLETE
specific for OVENS



BRITA 1000252

BRITA 1000252+1014370

3010070 CONSUMPTION CONTROL FLOWMETER 100-700 L
temperature 4°C-60°C
max pressure 8 bar
to meter the amount of residual liters the
cartridge can process



BRITA 298905

3010622 FILTER HEAD BRITA G3/8"
adjustable by pass 0-70%



BRITA 1002955

BRITA 1013637

BRITA 3010622

3010623 FILTER HEAD BRITA G3/8"
bypass 30%



BRITA 1002952

BRITA 297175

3010620 HARDNESS TEST TOTAL-CARBONIC KIT
kit to test both temporary and total
hardness from carbonates



BRITA 710403



Suitable for:

BRITA



3010605 PURITY C 150
 for water treatment for TECHNICAL purposes
 adjustable bypass
 capacity at 10°KH 2408 L (dispensers)
 flow rate 60 L/h
 max pressure 8.6 bar
 operating temperature 4°C/30°C
 loss of pressure at 0.20 bar flow rate
 dimensions: height 421 mm - ø 117 mm
 weight: empty 1.7 Kg - full 2.5 Kg
 fittings: inlet ø 3/8" M - outlet ø 3/8" M
 horizontal or vertical mounting



BRITA 102829+1002955

BRITA 102829+1013637

BRITA 297166+102829

3010615 CARTRIDGE PURITY C 150
 for water treatment for TECHNICAL purposes



BRITA 102828

BRITA 102828+1014370

BRITA 102829

3010606 PURITY C 300
 for water treatment for TECHNICAL purposes
 adjustable bypass
 capacity at 10°KH 4000 L (dispensers)
 flow rate 60 L/h
 max pressure 8.6 bar
 operating temperature +4°C/+30°C
 loss of pressure at 0.20 bar flow rate
 dimensions: height 476 mm - ø 124 mm
 weight: empty 2.7 Kg - full 3.9 Kg
 fittings: inlet ø 3/8" M - outlet ø 3/8" M
 horizontal or vertical mounting



BRITA 102827+1002955

BRITA 102827+1013637

BRITA 297166+102827

3010616 CARTRIDGE PURITY C 300
 for water treatment for TECHNICAL purposes



BRITA 102827

BRITA 102827+1014370

3010608 PURITY C 50
 for water treatment for TECHNICAL purposes
 adjustable bypass
 capacity at 10°KH 960 L (dispensers)
 flow rate 60 L/h
 max pressure 8.6 bar
 operating temperature 4°C/30°C
 loss of pressure at 0.25 bar flow rate
 dimensions: height 267 mm - ø 117 mm
 weight: empty 1.0 Kg - full 1.4 Kg
 fittings: inlet ø 3/8" M - outlet ø 3/8" M
 horizontal or vertical mounting



BRITA 102831+1002955

BRITA 102831+1013637

3010618 CARTRIDGE PURITY C 50
 for water treatment for TECHNICAL purposes



BRITA 102831

BRITA 102831+1014370



Suitable for:

Suitable for:

3010607 PURITY C 500
 for water treatment for TECHNICAL purposes
 adjustable bypass
 capacity at 10°KH 6800 l (dispensers)
 capacity at 10°KH 4675 l (ovens)
 flow rate 120 l/h
 max pressure 8.6 bar
 operating temperature +4°C/+30°C
 loss of pressure at 0.50 bar flow rate
 dimensions: height 554 mm - ø 149 mm
 weight: empty 4.6 Kg - full 7.1 Kg
 fittings: inlet ø 3/8" M - outlet ø 3/8" M
 horizontal or vertical mounting



BRITA 1002045+1013637

BRITA 1002955+1002045

BRITA 297166+1002045

3010617 CARTRIDGE PURITY C 500
 for water treatment for TECHNICAL purposes



BRITA 1002045

BRITA 1002045+1014370

3010601 PURITY CLEAN EXTRA 1200
 for water treatment for TECHNICAL purposes
 water softener ideal for DISHWASHERS
 specific for HOT WATER
 adjustable bypass
 capacity at 10°dH 5000 L
 flow rate 300 L/h
 max. pressure 6 bar
 min. pressure 2 bar
 operating temperature 4°C/60°C
 loss of pressure at 0.45 bar flow rate
 dimensions: height 550 mm - ø 255 mm
 weight: empty 18 Kg - full 24 Kg
 fittings: inlet ø 1" M - outlet ø 3/4" M
 horizontal or vertical mounting



BRITA 1008200

BRITA 1008200+1014370

BRITA 292084

3010611 CARTRIDGE PURITY CLEAN EXTRA 1200
 specific for WASHING



BRITA 1008197

BRITA 1008197+1014370

3010600 PURITY CLEAN 1200
 for water treatment for TECHNICAL purposes
 water softener ideal for DISHWASHERS
 specific for HOT WATER
 capacity 10°KH 12000 L
 flow rate 300 L/h
 max. pressure 6 bar
 min. pressure 2 bar
 operating temperature 4°C/60°C
 loss of pressure at 0.45 bar flow rate
 dimensions: height 550 mm - ø 255 mm
 weight: empty 18 Kg - full 24 Kg
 fittings: inlet ø 1" M - outlet ø 3/4" M
 horizontal or vertical mounting



BRITA 292083

BRITA 292083+1014370

3010610 CARTRIDGE PURITY CLEAN 1200
 specific for WASHING



BRITA 315645

BRITA 315645+1014370



Suitable for:

BRITA



3010604 PURITY ST 1200
 water softener ideal for COFFEE MACHINES-DISPENSER
 OVENS - ICE MAKERS
 adjustable bypass
 capacity 10°KH 13187 L
 flow rate 200 L/h
 max. pressure 6.9 bar
 min. pressure 2 bar
 operating temperature 4°C/30°C
 loss of pressure at 1.05 bar flow rate
 dimensions: height 550 mm - ø 288 mm
 weight: empty 18 Kg - full 24 Kg
 fittings: inlet ø 3/8"M - outlet ø 3/8"M
 horizontal or vertical mounting



BRITA 1009231

BRITA 1009231+1014370

BRITA 2726+2724

3010614 CARTRIDGE PURITY ST 1200
 specific for HO.RE.CA



BRITA 273400

BRITA 273400+1014370

3010220 HOSE CLAMP SET
 with non-return valve and fittings



BRITA 274000

3010602 PURITY ST 450
 for water treatment for TECHNICAL purposes
 adjustable bypass
 capacity at 10°KH 4217 L
 flow rate 100 L/h
 max pressure 6.9 bar
 min. pressure 2 bar
 operating temperature 4°C/30°C
 loss of pressure at 0.35 bar flow rate
 dimensions: height 408 mm - ø 249 mm
 weight: empty 12 Kg - full 15 Kg
 fittings: inlet ø 3/8"M - outlet ø 3/8"M
 horizontal or vertical mounting



BRITA 1009227

BRITA 1009227+1014370

BRITA 2720+2727

3010612 CARTRIDGE PURITY ST 450
 specific for HO.RE.CA



BRITA 273000

BRITA 273000+1014370

3010220 HOSE CLAMP SET
 with non-return valve and fittings



BRITA 274000



Suitable for:

Suitable for:

3010603 PURITY ST 600
for water treatment for TECHNICAL purposes
adjustable bypass
capacity at 10°KH 7207 L (dispensers)
flow rate 100 L/h
max pressure 6.9 bar
min. pressure 2 bar
operating temperature 4°C/30°C
loss of pressure at 0.35 bar flow rate
dimensions: height 520 mm - ø 249 mm
weight: empty 12 Kg - full 15 Kg
fittings: inlet ø 3/8" M - outlet ø 3/8" M
horizontal or vertical mounting

3010613 CARTRIDGE PURITY ST 600
specific for HO.RE.CA



BRITA 1009229

BRITA 1009229+1014370

BRITA 2720+2728

BRITA 2732

BRITA 273200

BRITA 273200+1014370

3010220 HOSE CLAMP SET
with non-return valve and fittings



BRITA 274000

3010219 PURITY 1200 STEAM
for water treatment for TECHNICAL purposes
water softener suitable for OVENS
with litre counter
adjustable bypass
capacity at 10°KH 10800 L
flow rate 100 L/h
max pressure 6.9 bar
min pressure 2 bar
operating temperature 4°C/30°C
loss of pressure at 0.10 bar flow rate
dimensions: height 550 mm - ø 288 mm
weight: empty 18 Kg - full 24 Kg
fittings: inlet ø 1" M - outlet ø 3/4" M
horizontal or vertical mounting

3010258 CARTRIDGE PURITY STEAM 1200 COMPLETE
specific for OVENS



BRITA 1002923

BRITA 1000231



Suitable for:

BRITA



3010218 PURITY 600 STEAM

for water treatment for TECHNICAL purposes
water softener suitable for OVENS
specific for ODOUR REMOVAL
adjustable bypass
capacity at 10°KH 5830 l
flow rate 100 l/h
max pressure 6.9 bar
min pressure 2 bar
operating temperature 4°C/30°C
loss of pressure at 0.10 bar flow rate
dimensions: height 520 mm - ø 235 mm
weight: empty 12 Kg - full 15 Kg
fittings: inlet ø 1" M - outlet ø 3/4" M
horizontal or vertical mounting



BRITA 1000245

Suitable for:

3010257 CARTRIDGE PURITY STEAM 600 COMPLETE

specific for OVENS





















BRITA 1000252

BRITA 1000252+1014370

The data herewith contained may change without notice and LF SpA cannot be held responsible for possible errors stated or resulting by the use of this document. All rights reserved. No part of this publication may be reproduced without written permission by LF SpA.



Distributing Components, Spare Parts & Accessories in original quality worldwide

-  **LF SpA HEADQUARTERS**
via Voltri, 80 - 47522 Cesena (FC) ITALY
Tel. +39 0547 34 11 11 - Fax +39 0547 34 11 10
www.lfrcambi724.it - www.lfrcambi724.mobi
info@lfrcambi.it
Export Dept.: Tel. +39 0547 34 11 50 - Fax: +39 0547 34 11 55
www.lfspareparts724.com - www.lfspareparts724.mobi
export@lfspareparts.com
-  **LF SpA HOUSEHOLD COMPONENTS DIVISION**
Via Padriciano, 34149 Trieste - Italia - AREA Science Park
Tel. +39 0547 34 12 42 - Fax +39 0547 34 12 48
www.lfspareparts724.com - www.lfspareparts724.mobi
info@lfspareparts.com
-  **EPGC Sas FRANCE**
13, Rue des Forts - 59960 Neuville en Ferrain
Tel. +33 (0)3 20 25 06 21
Fax +33 (0)3 20 25 34 12
www.epgc.com
www.epgc724.mobi
epgc@epgc.com
-  **LF GmbH GERMANY**
Junkersstrasse, 3 - D-82178 Puchheim - München
Tel. +49 89 89 45 78 66
Fax +49 89 89 45 78 88
www.lfersatzteile724.de
www.lfersatzteile724.mobi
info@lfersatzteile.de
-  **LF China REPUBLIC OF CHINA**
Room 403, No.2, Huadu Mansion, Lane 422, Huanghua Rd.
Minhang Dist. - 201103 Shanghai
Tel. +86 (0)21 33 53 66 31
Fax +86 (0)21 33 53 66 32
www.lfspareparts724.com
www.lfspareparts724.mobi
china@lfspareparts.com
-  **OOO LF RUSSIAN FEDERATION**
Ul. Anatoliya Zhivova, 8 - office 1 - 123100 Moscow
Tel./Fax +7 495 725 26 53
www.lfspareparts724.ru
www.lfspareparts724.mobi
info@lfspareparts.ru
-  **LF Repuestos Horeca S.L.U. SPAIN**
Poligono Industrial Carpetania - C/Miguel Faraday, 8 - 28906 Getafe
Tel. +34 91 477 91 00
Fax +34 91 477 90 81
www.lfrepuestos-horeca724.es
www.lfrepuestos724.mobi
info@lfrepuestos.es
-  **LF SpA Cesena (IT) Swiss Branch Steinhausen SWITZERLAND**
Sennweidstrasse, 45 - CH-6312 Steinhausen
Tel. +41 (0)41 760 15 80-1
Fax +41 (0)41 760 15 85
www.lfersatzteile724.ch
www.lfersatzteile724.mobi
info@lfersatzteile.ch
-  **LF Spare Parts Ltd. UNITED KINGDOM**
A10a Lakeside Business Park, Broadway Lane
South Cerney, Gloucestershire GL7 5XL
Tel. +44 (0)1285 86 16 25
Fax +44 (0)1285 86 39 49
www.lfspareparts724.co.uk
www.lfspareparts724.mobi
info@lfspareparts.co.uk
-  **AUSTRALIA AND NEW ZEALAND**
www.lfspareparts724.com
andrea.calvio@lfspareparts.com
-  **AUSTRIA**
www.lfersatzteile724.at
info@lfersatzteile.at
-  **BALKAN COUNTRIES**
www.lfspareparts724.com
matijaramov@lfspareparts.com
-  **BALTIC COUNTRIES**
www.lfspareparts724.com
inara.silina@lfspareparts.com
-  **CENTRAL AND EASTERN EUROPE**
www.lfspareparts724.cz
jiri.kremla@lfspareparts.cz
-  **DENMARK**
www.lfspareparts724.dk
michael.leth@lfspareparts.com
-  **JAPAN**
www.lfspareparts724.jp
hiroshi.ukai@lfspareparts.jp
-  **SOUTH KOREA**
www.lfspareparts724.com
fabio.doni@lfspareparts.com
-  **TURKEY**
www.lfyedekparca724.com
basar.ergun@lfyedekparca.com
-  **USA AND CANADA**
www.lfspareparts724.us
sauro.dallaglio@lfspareparts.us
howard.truitt@lfspareparts.us